

TA-UC-PDQC65-01-W

3-port 67 W GaN USB PowerDelivery fast charger, white

- 67 W of power for your smartphone or laptop
- Type-C port or standard USB port for fast charging most smartphones
- Supports both USB PD and QC 3.0 fast charging protocol
- GaN technology enables a more compact energy efficient design



Features

- 3-port 67 W USB fast charger: supports both QC 3.0 and PowerDelivery (PD) specification
- GaN technology: compact design and increased energy efficiency
- Type-C ports support 65 W PD, Type-A port supports 27 W QC 3.0
- Intelligent over-current, over-voltage, short circuit and overheat protection

Packaging

Q'ty in crtn, pcs
Crtn volume, CUM
Crtn weight, kgs
Individual package size LxWxH:
Carton size LxWxH:
Country of origin
Barcode
Customs code

96
0.078
16.55
40x90x120 mm
550x460x310 mm
CN
8716309128674
8504408390

Certificates



Specifications

Input voltage: 100 V 240 V ~, up to 1.5 A
Standby power consumption: < 0.1 W
Average efficiency: > 87.6 %
Efficiency at 25 % load: > 84 %
Efficiency at 100 % load: > 88.26 %
C1/C2 output: 5.0 V/3.0 A, 9.0 V/3.0 A, 12.0 V/3.0 A, 15.0 V/3.0 A, 20.0 V/3.35 A (67.0 W max.)
A1 output: 3.4 V-5.5 V/5.0 A, 5.0 V/3.0 A, 9.0 V/3.0 A, 12.0 V/3.0 A, 20.0 V/3.0 A (60.0 W max.)
C1 + C2 output: 45.0 W + 20.0 W (65.0 W max.)
C1 + A1: 45.0 W + 18.0 W (63.0 W max.)
C2 + A1: 5.0 V / 4.8 A (24.0 W max.)
C1 + [C2 + A1]: 45.0 W + 15.0 W (60.0 W max.)
Output protection: short circuit, over-voltage, overcharge, overheat

Dimensions: 39 mm x 106 mm x 34 mm
Net weight: 124 g

System requirements

NOTE: If both ports are used simultaneously, total output is limited to: 5V/2A
iPhone fast charging is only supported on iPhone 8 or newer