

Blackmagic PYXIS 12K EF



£4,179

Blackmagic PYXIS 12K EF is an advanced digital film camera with an incredibly versatile design that lets you build the perfect camera rig for your production. This new model features a 12,288 x 8040 full frame RGBW sensor with built in optical low pass filter, 16 stops of dynamic range, dual CFexpress media slots, all in a customizable body with flexible mounting options and side plates. Blackmagic PYXIS 12K EF features a fixed locking EF mount that works with Canon compatible photo and cine lenses.

Camera Features

Effective Sensor Size

35.64mm x 23.32mm (Large Format)

Pixel Pitch

2.9 microns

Lens Mount

Active, locking EF lens mount.

Lens Control

Iris and focus on supported lenses.

Dynamic Range

16 Stops.

Native ISO

800

Shooting Resolutions

- 12,288 x 8040 (12K 3:2 open gate)
- 12,288 x 6912 (12K 16:9)
- 12,288 x 6480 (12K 17:9)
- 12,288 x 5112 (12K 2.4:1)
- 9648 x 8040 (12K 6:5)
- 9408 x 6264 (9K 3:2)
- 8688 x 4896 (9K 16:9)
- 9312 x 4896 (9K 17:9)
- 9312 x 3864 (9K 2.4:1)
- 7680 x 6408 (9K 6:5)
- 8192 x 5360 (8K 3:2 open gate)
- 8192 x 4608 (8K 16:9)
- 8192 x 4320 (8K 17:9)
- 8192 x 3408 (8K 2.4:1)
- 6432 x 5360 (8K 6:5)
- 4096 x 2680 (4K 3:2 open gate)
- 4096 x 2304 (4K 16:9)
- 4096 x 2160 (4K 17:9)
- 4096 x 1704 (4K 2.4:1)
- 3216 x 2680 (4K 6:5)

Frame Rates

Project frame rates of 23.98, 24, 25, 29.97, 30, 50, 59.94 and 60 fps supported. Maximum sensor frame rate dependent on resolution selected.

High Frame Rates

- 12K (3:2 open gate) up to 40 fps
- 12K (16:9) up to 45 fps
- 12K (17:9) up to 50 fps
- 12K (2.4:1) up to 60 fps
- 12K (6:5) up to 40 fps
- 9K (3:2 Super 35) up to 50 fps
- 9K (16:9 Super 35) up to 65 fps
- 9K (17:9 Super 35) up to 65 fps
- 9K (2.4:1 Super 35) up to 80 fps
- 9K (6:5 Super 35) up to 50 fps
- 8K/4K (3:2 open gate) up to 72 fps
- 8K/4K (16:9) up to 84 fps
- 8K/4K (17:9) up to 90 fps
- 8K/4K (2.4:1) up to 112 fps
- 8K/4K (6:5) up to 72 fps

Focus

Auto focus available using compatible lenses.


Iris Control

Iris wheel and touchscreen slider for manual iris adjustment on electronically controllable lenses, iris button for instant auto iris settings using compatible lenses.

Screen Dimensions 4" 1920 x 1080. Screen Brightness 1500 nits Screen Type LCD capacitive touchscreen.	Metadata Support Automatically populated lens data from electronic L-Mount lenses. Automatic recording of camera settings, motion sensor data plus slate data such as project, scene number, take and special notes. A 3D LUT can also be embedded in metadata of Blackmagic RAW files.	Controls Touchscreen menus on 4 inch screen. Push buttons for other controls. 3 assignable shortcut keys. Timecode Clock Highly accurate timecode clock. Less than 1 frame drift every 8 hours.
---	---	--

Connections

Total Video Inputs None Total Video Outputs 1 x 12G-SDI up to 2160p60 1 x Viewfinder USB-C with power, data, video and locking connector.	Analog Audio Inputs 1 x mini XLR analog audio in, switchable between mic with phantom power support and line level (up to +14dBu). 1 x 3.5mm Stereo Input. Analog Audio Outputs 1 x 3.5mm headphone jack. Reference Inputs Tri-Sync/Black Burst and Timecode.	Computer Interface USB Type-C for external drive recording, PTP camera control and software updates. Ethernet 1 x 10Gb/s RJ-45 connector supporting 10/100/1000/10G BASE-T.
---	--	--



Standards

HD Video Standards

1080p23.98, 1080p24, 1080p25,
1080p29.97, 1080p30, 1080p50,
1080p59.94, 1080p60

Ultra HD Video Standards

2160p23.98, 2160p24, 2160p25,
2160p29.97, 2160p30, 2160p50,
2160p59.94, 2160p60

SDI Compliance

SMPTE 424M, SMPTE 425M level A
and B, SMPTE 2081-1,
SMPTE 2081-10, SMPTE 2082-1
and SMPTE 2082-10.

SDI Audio Sampling

Television standard sample rate of 48
kHz and 24-bit.

Audio

Microphone

Integrated stereo microphone.

Built in Speaker

1 x mono speaker.

Media

Media

2 x CFexpress Type B card slot, 1 x 10
Gbps USB-C port for external media
for Blackmagic RAW and H.264
Proxy Recording.
Please refer to either the Manual or
the Information Note at
www.blackmagicdesign.com/support
for compatible media.

Media Format

Can format media to ExFAT
(Windows/Mac) or HFS+ (Mac)
file systems.

Supported Codecs

Codecs

Blackmagic RAW Constant Bitrate 3:1
Blackmagic RAW Constant Bitrate 5:1
Blackmagic RAW Constant Bitrate 8:1
Blackmagic RAW Constant Bitrate
12:1
Blackmagic RAW Constant Bitrate
18:1
Blackmagic RAW Constant Quality Q0
Blackmagic RAW Constant Quality Q1
Blackmagic RAW Constant Quality Q3
Blackmagic RAW Constant Quality Q5
H.264 Proxy in 1920 x 1080, 8-bit
4:2:0

Control

External Control

Blackmagic Zoom Demand and Blackmagic Focus Demand for controlling your camera and lens from tripod handles.

iPad control, Bluetooth control, USB PTP camera control. External control of some camera settings, focus, iris and zoom with compatible lenses. Camera Control REST API over Ethernet.

Network Management

NTP

Network time protocol support allows you to sync the time on your camera, whenever connected to a network with any NTP server of your choice.

Web Media Manager

Using a browser connected over Ethernet, web media manager allows you to access, browse, download and delete files from any drive connected to the camera.

FTP

Download files from any drive attached to your camera using FTP.

SMB

File sharing using SMB

Storage Features

Storage Type

2 x CFexpress Type B

1 x high speed USB-C expansion port for external media.

Storage Rates

Storage rates based on 24 frames per second.

12K - 12,288 x 8040	Recording Formats	Constant Quality storage rates
Blackmagic RAW 3:1 - 1,194 MB/s	Blackmagic RAW 3:1, 8:1, 12:1, 18:1,	quoted are indicative only.
Blackmagic RAW 8:1 - 448 MB/s	Q0, Q1, Q3 and Q5 at full sensor	Actual storage rates are entirely
Blackmagic RAW 12:1 - 298 MB/s	width or height resolutions:	dependent on image subject matter.
Blackmagic RAW 18:1 - 199 MB/s	12,288 x 8,040, 12,288 x 6,912,	
Blackmagic RAW Q0 - 298 to 1,432 MB/s	12,288 x 6,480, 12,288 x 5,112 and	
Blackmagic RAW Q1 - 179 to 716 MB/s	9,648 x 8,040	
Blackmagic RAW Q3 - 119 to 298 MB/s	with film, extended video or video	
Blackmagic RAW Q5 - 90 to 224 MB/s	dynamic range or custom 3D LUT	
9K - 9408 x 6264	embedded in metadata plus	
Blackmagic RAW 3:1 - 713 MB/s	simultaneous recording of H.264	
Blackmagic RAW 8:1 - 268 MB/s	1920 x 1080 Proxies.	
Blackmagic RAW 12:1 - 178 MB/s	Blackmagic RAW 3:1, 8:1, 12:1, 18:1,	
Blackmagic RAW 18:1 - 119 MB/s	Q0, Q1, Q3 and Q5 at Super 35	
Blackmagic RAW Q0 - 178 to 856 MB/s	windowed sensor resolutions:	
Blackmagic RAW Q1 - 107 to 428 MB/s	9,408 x 6,264, 8,688 x 4,896,	
Blackmagic RAW Q3 - 71 to 178 MB/s	9,312 x 4,896, 9,312 x 3,864 and	
Blackmagic RAW Q5 - 54 to 134 MB/s	7,680 x 6,408	
8K - 8192 x 5360	with film, extended video or video	
Blackmagic RAW 3:1 - 533 MB/s	dynamic range or custom 3D LUT	
Blackmagic RAW 5:1 - 320 MB/s	embedded in metadata plus	
Blackmagic RAW 8:1 - 200 MB/s	simultaneous recording of H.264	
Blackmagic RAW 12:1 - 133 MB/s	1920 x 1080 Proxies.	
Blackmagic RAW Q0 - 133 to 319 MB/s	Blackmagic RAW 3:1, 5:1, 8:1, 12:1,	
Blackmagic RAW Q1 - 80 to 200 MB/s	Q0, Q1, Q3 and Q5 at full sensor	
Blackmagic RAW Q3 - 53 to 133 MB/s	width or height scaled to:	
Blackmagic RAW Q5 - 40 to 100 MB/s	8,192 x 5,360, 8,192 x 4,608,	
4K - 4096 x 2680	8,192 x 4,320, 8,192 x 3,408 and	
Blackmagic RAW 3:1 - 135 MB/s	6,432 x 5,360	
Blackmagic RAW 4:1 - 101 MB/s	with film, extended video or video	
Blackmagic RAW 5:1 - 81 MB/s	dynamic range or custom 3D LUT	
Blackmagic RAW 6:1 - 68 MB/s	embedded in metadata plus	
Blackmagic RAW Q0 - 34 to 81 MB/s	simultaneous recording of H.264	
Blackmagic RAW Q1 - 20 to 50 MB/s	1920 x 1080 Proxies.	
Blackmagic RAW Q3 - 13 to 34 MB/s	Blackmagic RAW 3:1, 4:1, 5:1, 6:1, Q0,	
Blackmagic RAW Q5 - 10 to 25 MB/s	Q1, Q3 and Q5 at full sensor width or	
	height scaled to:	
	4,096 x 2,680, 4,096 x 2,304,	
	4,096 x 2,160, 4,096 x 1,704 and	
	3,216 x 2,680	
	with film, extended video or video	
	dynamic range or custom 3D LUT	
	embedded in metadata plus	
	simultaneous recording of H.264	
	1920 x 1080 Proxies.	

Software

Software Included

- Blackmagic OS
 - DaVinci Resolve Studio for Mac and Windows including activation key
 - Blackmagic Camera Setup
 - Blackmagic RAW Player
 - Blackmagic RAW QuickLook Plugin
 - Blackmagic RAW SDK
 - Blackmagic RAW Speed Test
-

Operating Systems



Mac 14.0 Sonoma,
Mac 15.0 Sequoia or later.



Windows 10 and 11.

Power Requirements

Power Supply

1 x External 18V DC 90
W power supply.

External Power Input

1 x 2-pin Lemo compatible locking
connector.

Battery Type

BP-U series.

Power

12V - 18V

Accessories

Optional Accessories

- Blackmagic URSA Cine Handle
- Blackmagic URSA Cine EVF
- Blackmagic PYXIS Rosette Plate
- Blackmagic PYXIS Monitor
- Blackmagic PYXIS Monitor Kit
- Blackmagic PYXIS Monitor EVF Kit

Physical Specifications



Environmental Specifications

Operating Temperature

0°to 40°C (32° to 104°F)

Storage Temperature

-20°to 45°C (-4° to 113°F)

Relative Humidity

0% to 90% non-condensing

What's Included

- Blackmagic PYXIS 12K EF
 - Lens turret dust cap
 - PYXIS Standard Plate
 - PYXIS SSD Plate
 - 90W power supply with locking connector and international adapters
 - Welcome booklet
 - DaVinci Resolve Studio activation key
-

Warranty

Product Warranty

1 Year Limited Manufacturer's Warranty.

All items on this website are copyright Blackmagic Design Pty. Ltd. 2025, all rights reserved.
All trademarks are property of their respective owners. MSRP excludes VAT and local shipping costs.
This website uses remarketing services to advertise on third party websites to previous visitors to our site.
You can opt out at any time by changing cookie settings. [Privacy Policy](#)

Blackmagic Design Authorized Reseller