

ThinkCentre M75n Thin Client 11G4000DGE

Product

ThinkCentre M75n Thin Client

Region

WE

Country/Region

Germany

Machine Type

11G4

TopSeller

TopSeller

Processor

AMD Ryzen 3 PRO 3300U (4C / 4T, 2.1 / 3.5GHz, 2MB L2 / 4MB L3)

Chipset

AMD SoC platform

Graphics

Integrated AMD Radeon Vega 6 Graphics

Memory

8GB Soldered DDR4-2400

Storage

1x 128GB SSD M.2 2242 PCIe 3.0x2 NVMe

Optical

None

Speaker

1Wx1

Ethernet

RTL8111FP-CG, 1x RJ45

WLAN + Bluetooth

None

Chassis Intrusion Switch

Chassis Intrusion Switch

Kensington Cable Lock

None

Adapter Cage

None

Dust Filter

None

VESA Mount

None

Color

Black

Stand

None

Keyboard

USB Calliope Keyboard, Black, German

Mouse

USB Calliope Mouse

Power Supply

65W 89% Adapter

Additional Certificates

None

Monitor Cable

None

System Management

DASH

Operating System

LeTOS V2, German

Bundled Software

None

Base Warranty

3-year, Onsite

Bundled Service

None

EAN / UPC / JAN

0195348686815

End of Support

2026-12-21

Announce Date

2020-09-22

Recommended Services**Better**

4Y Premier Support Upgrade from 3Y Onsite (5WS0T36207)

Good

3Y Premier Support Upgrade from 3Y Onsite (5WS0U26647)

 WWW.LENOVO.COM

Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors.

Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.



<https://psref.lenovo.com>

Visit psref website for the latest version of Product specifications Reference.

© Lenovo, 2020. All rights reserved.



AMD

Lenovo™

ThinkCentre M75n Thin Client Platform Specifications

Product Specifications Reference (PSREF)

Processor	AMD Ryzen 3 / 5 PRO series processor	Security features	<ul style="list-style-type: none"> Security slot (in rear for optional Kensington® MicroSaver® cable) Chassis intrusion switch Power-on password Administrator password Hard disk password 											
	<table border="1"> <thead> <tr> <th>Processor</th> <th>Cores / Threads</th> <th>Frequency Base/Max</th> <th>L2 / L3 Cache</th> <th>Memory Support (Up to)</th> <th>Integrated Graphics</th> </tr> </thead> <tbody> <tr> <td>Ryzen 3 PRO 3300U</td> <td>4 / 4</td> <td>2.1 / 3.5 GHz</td> <td>2 MB / 4MB</td> <td>DDR4-2400</td> <td>Radeon Vega 6</td> </tr> </tbody> </table>	Processor	Cores / Threads	Frequency Base/Max	L2 / L3 Cache	Memory Support (Up to)	Integrated Graphics	Ryzen 3 PRO 3300U	4 / 4	2.1 / 3.5 GHz	2 MB / 4MB	DDR4-2400	Radeon Vega 6	<ul style="list-style-type: none"> Boot sequence control Boot without keyboard and mouse Individual USB port disablement Smart USB protection, allows keyboard/mouse only, blocks all storage devices
Processor	Cores / Threads	Frequency Base/Max	L2 / L3 Cache	Memory Support (Up to)	Integrated Graphics									
Ryzen 3 PRO 3300U	4 / 4	2.1 / 3.5 GHz	2 MB / 4MB	DDR4-2400	Radeon Vega 6									
Memory	8GB / DDR4-2400* / soldered to systemboard, no sockets, dual-channel capable, non-ECC * System automatically clocks down for the processors with lower memory controller	Keyboard	<i>Some:</i> Lenovo Calliope Keyboard (USB connector), black <i>Some:</i> Lenovo Traditional Keyboard (USB connector), black <i>Some:</i> Lenovo Calliope Wireless Keyboard (2.4GHz via USB receiver), black											
Storage	Support up to two M.2 SSD (one PCIe x4, one SATA/PCIe x2) <i>Some:</i> M.2 2280 SSD / PCIe NVMe, PCIe 3.0 x 4* <i>Some:</i> M.2 2242 SSD / PCIe NVMe, PCIe 3.0 x 2 <i>Some:</i> M.2 2242 SSD / SATA interface * M.2 SSD in PCIe 3.0 x2 M.2 slot can only run at PCIe 3.0 x2	Mouse	<i>Some:</i> Lenovo Calliope Mouse (USB connector), black <i>Some:</i> Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black											
RAID	None	Mechanical	Nano (0.35L), Iron Gray top cover / Black mid bezel / Red bottom cover Three M.2 slots: two for M.2 SSD (one PCIe 3.0 x4 and one PCIe 3.0 x2 / SATA) and one for WLAN											
Optical	None		<table border="1"> <thead> <tr> <th></th> <th>Dimensions (WxDxH)</th> <th>Weight (Approx.)</th> </tr> </thead> <tbody> <tr> <td>M75n (with fan, 0.35L)</td> <td>7.05" X 3.46" X 0.87" 179mm X 88mm X 22mm</td> <td>1.11 lb (0.505 kg), vary by config</td> </tr> </tbody> </table>		Dimensions (WxDxH)	Weight (Approx.)	M75n (with fan, 0.35L)	7.05" X 3.46" X 0.87" 179mm X 88mm X 22mm	1.11 lb (0.505 kg), vary by config					
	Dimensions (WxDxH)	Weight (Approx.)												
M75n (with fan, 0.35L)	7.05" X 3.46" X 0.87" 179mm X 88mm X 22mm	1.11 lb (0.505 kg), vary by config												
Graphics	AMD Radeon™ Vega 6 Graphics in processor, uses main memory, DirectX® 12, one DisplayPort™, one USB 3.2 Type-C Gen2 with display function, up to 2 independent displays; <i>Max resolution:</i> 3840x2160 (DP)@60Hz; 3840x2160 (Type-C)@60Hz	Mounting	<i>Some:</i> VESA mount bracket kit, supports VESA 75mm <i>Some:</i> VESA mount bracket kit with adapter holder, supports VESA 75mm <i>Some:</i> DIN rail mount bracket kit											
Monitor cable	Optional DP to VGA dongle, DP to HDMI dongle, Type-C to VGA dongle, Type-C to HDMI dongle, Type-C to DP dongle	Floor Stand	None											
Chipset	AMD SoC (System on Chip) platform	Power supply	65 watts adapter, autosensing, 89% PSU (Not for TIO models)											
Front ports (Std.)*	1x USB 2.0, 1x USB 3.2 Gen 2, 1x USB 3.2 Type-C Gen 2, one headphone / microphone combo jack (3.5mm)	Limited warranty	<i>Some:</i> 1-year, limited onsite service / service upgrades available <i>Some:</i> 3-year, limited onsite service / service upgrades available											
Rear ports (Std.)*	1x USB 2.0, 1x USB 3.2 Gen2, 1x USB 3.2 Type-C Gen 2 (with display function, support power-in [20V and >45W]), 1x ethernet (RJ-45), 1x DisplayPort * Depending on many factors, actual data transfer speed may be lower than theoretical speed	Preload	Preloaded operating system <i>Some:</i> LeTOS V2 (Lenovo Terminal Operating System, Linux-based) <i>Some:</i> Windows 10 IoT Enterprise (Thin Client version)											
Audio support	Realtek ALC233 / internal speaker (1watt)	Environment	ENERGY STAR® 8.0, EPEAT™ Silver rating, ErP Lot 3, TCO 8.0, TUV ultra low noise verified (on some models), RoHS, WEEE, REACH											
WLAN	<i>Some:</i> 11ac wireless, M.2 Card, Realtek RTL8822CE (dual band), Wi-Fi + Bluetooth 5.0 combo adapter, 2x2 <i>Some:</i> 11ac wireless, M.2 Card, Intel Wireless-AC 9260 (dual band), Wi-Fi + Bluetooth 5.0 combo adapter, 2x2	MIL-SPEC test	MIL-STD-810H military certification (Low Pressure [Altitude], High Temperature, Low Temperature, Temperature Shock, Humidity, Sand and Dust, Vibration, Shock, Fungus, Solar Radiation)											
Bluetooth	<i>Some:</i> Bluetooth 4.2 / 5.0 wireless, integrated in Wi-Fi + BT combo adapter	Accessories	For compatible accessories, please go to http://smartfind.lenovo.com											
Ethernet	Gigabit ethernet, Realtek RTL8111FP-CG, Wake on LAN®													
Manageability	Dash 1.1/1.2													
Security chip	Discrete TPM 2.0, TCG Certified													

Note: The specifications above may not be available in all regions.

Lenovo, May 2020



ThinkCentre M75n Thin Client



AMD



AMD



AMD



AMD



AMD



AMD