



Argus KT015 – PCIe Adapter for a M.2 PCIe and M.2 SATA drive

The KT015 Adapter enables connecting a M.2 PCIe SSD and a M.2 SATA SSD (42/ 60/ 80mm) additionally. One M.2 SSD is connected by PCIe X4 interface, which enables a super-fast data transfer of 32 Gbit/s. The other M.2 SSD is connected by SATA data cable and enables a transfer rate of up to 6 Gbit/s.

Just fix the SSDs on the adapter and mount it in a free slot. The scope of delivery includes mounting screws as well as a small screwdriver.

- ✓ Transfer rate up to 32 Gbit/s
- ✓ Included Low-Profile slot bracket
- ✓ Supports NVMe Express (NVMe)
- ✓ SATA III Standard

Specifications

Drive connector	1x M.2 SSD (NGFF, B-Key) 1x M.2 SSD (NGFF, M-Key)
Host connector	1x PCIe x4 v3.0 1x SATA 7pin
HDD Size	No restrictions M.2 PCIe x4 v3.0 Depending on Controller on M.2 S-ATA to S-ATA 7pin
Max. Transfer rate	PCIe x4 v3.0: 32 Gbit/s S-ATA: 6 Gbit/s
Supported M.2 formats	1x Type 2242, 2260, 2280 (Key M) 1x Type 2242, 2260, 2280 (Key B)
Operating System	Windows XP/Vista/7/8/8.1/10 Linux up from Kernel 2.4 MAC OS up from 10.4 <small>(by using M.2 PCIe x4 v2.0 only with MAC compatible firmware)</small>
Plug&Play	•
Material	Metal and hard paper
Dimensions (H/W/D)	20/120/150mm
Package Dimensions (H/W/D)	25/125/165mm
Weight (net)	55g
Weight (gross)	120g
Packing Units	1/x
Warranty	12 Months
Article Number	88885375
EAN-Code	4260455640619
Scope of delivery	Additional Low-Profile Slot bracket Screwdriver Screw set Manual (German)

- = existent
- = non existent