

Key Features

- **Apple Compatible:** MAC Ready with 90W USB-C connectivity plus 98% DCI-P3 International Digital Film Standard colour gamut.
- **Hollywood Colour:** VESA verified HDR400 with Nano IPS meets big screen standards for Cinematic quality.
- **Great for B-Roll:** 165Hz response time ideal for stellar sequences.
- **Instant Colour Adjustment:** Our exclusive ColorPro Wheel puts colour calibration and adjustments at your fingertips with Adobe Software and on-screen displays.
- **Portable Darkroom:** Foldaway hood attaches instantly to eliminate ambient light when you need to "go dark".



Product Description

Introducing the world's first professional monitor with an integrated colour calibrator plus Nano IPS Colour Gamut, 98% DCI-P3 capability & 165Hz refresh rate. Outstanding visual performance and unmatched colour capability combine with award-winning ergonomic design and fingertip controls in our ColorPro VP76 Series Professional Monitors from ViewSonic. Designed exclusively to meet the visual needs of world-class photographers, vloggers, video editors, animators and game designers, ColorPro stands apart through a marriage of the latest tech and human touch. With integrated access to Adobe and Capture One editing software, ColorPro was created to surpass your expectations through a combination of elegant design, outstanding technology and a simple, intuitive interface for easy colour adjustment.

Visit Us  www.viewsonic.com

DISPLAY

Display Size (in.):	27
Viewable Area (in.):	27
Panel Type:	IPS Technology
Resolution:	2560 x 1440
Resolution Type:	QHD
Static Contrast Ratio:	1,000:1 (typ)
Dynamic Contrast Ratio:	20M:1
Light Source:	LED
Brightness:	400 cd/m² (typ)
Colours:	1.07B
Colour Space Support:	10 bit (8 bit + A-FRC)
Aspect Ratio:	16:9
Response Time (Typical GTG):	3ms
Response Time (GTG w/OD):	3ms
Response Time (MPRT):	1ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	165
Adaptive Sync:	Yes
Blue Light Filter:	Yes
Flicker-Free:	Yes

Colour Gamut:	Adobe RGB: 99% size / 87% coverage (Typ) DCI-P3: 98% size / 95% coverage (Typ) EBU: 131% size / 100% coverage (Typ) REC709: 133% size / 100% coverage (Typ) SMPTE-C: 144% size / 100% coverage (Typ) NTSC: 94% size (Typ) sRGB: 133% size / 100% coverage (Typ)
Pixel Size:	0.233 mm (H) x 0.233 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

COMPATIBILITY

PC Resolution (max):	2560x1440
Mac® Resolution (max):	2560x1440
PC Operating System:	Windows 10/11 certified; macOS tested
Mac® Resolution (min):	2560x1440

CONNECTOR

USB 3.1 Type C - Downstream:	1
USB 3.2 Type A Down Stream:	2
USB 3.2 Type B Up Stream:	1
USB 3.2 Type C Up Stream; DisplayPort Alt mode :	1
Micro USB:	1
3.5mm Audio Out:	1
HDMI 2.0 (with HDCP 2.2):	2
DisplayPort:	1
Power in:	3-pin Socket (IEC C14 / CEE22)

AUDIO

Internal Speakers:	3Watts x2
--------------------	-----------

POWER

Eco Mode (Conserve):	33.4W
Eco Mode (optimised):	36.3W
Consumption (typical):	39.5W
Consumption (max):	43.5W
Voltage:	AC 100-240V
Stand-by:	0.5W
Power Supply:	Internal Power Supply

ADDITIONAL HARDWARE

Kensington Lock Slot:	1
Cable Organisation:	Yes

CONTROLS

Physical Controls:	Joystick key: Up, Right, Down, Left, Centre; Power
On Screen Display:	Input Select, Colour Model, ViewMode, Audio Adjust, Setup Menu

OPERATING CONDITIONS

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

WALL MOUNT

VESA Compatible:	100 x 100 mm
------------------	--------------

INPUT SIGNAL

Frequency Horizontal:	15 ~ 284.33KHz
Frequency Vertical:	24 ~ 165Hz

VIDEO INPUT

Digital Sync:	TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.4), Micro-Packet - Type C
---------------	---

ERGONOMICS

Height Adjust (mm):	130
Swivel:	120°
Tilt (Forward/Back):	-3° / 21°
Pivot (Right/Left):	90° / 90°

WEIGHT (IMPERIAL)

Net (lbs):	18.5
Net Without Stand (lbs):	11.2
Gross (lbs):	28.2

WEIGHT (METRIC)

Net (kg):	8.4
Net Without Stand (kg):	5.1
Gross (kg):	12.8

DIMENSIONS (IMPERIAL) (WXHxD)

Packaging (in.):	27.2 x 19.9 x 8.9
Physical (in.):	24.2 x 17.69~22.42 x 9.2
Physical Without Stand (in.):	24.2 x 14.3 x 2.1

DIMENSIONS (METRIC) (WXHxD)

Packaging (mm):	692 x 505 x 225
Physical (mm):	614 x 449.36~569.36 x 234
Physical Without Stand (mm):	614 x 364 x 54

GENERAL

Regulations:

PACKAGE CONTE

Recycle/Disposal:

Warranty: