

## 3 Port CardBus 1394a FireWire Adapter Card - Digital Video Editing Kit

Product ID: CB1394



This 3 Port PCMCIA IEEE 1394 FireWire 400 Laptop Adapter Card allows you to connect FireWire/i.LINK devices such as iPods or DV (digital video) camcorders to your laptop computer through a CardBus slot.

Compatible with both PC and Mac laptop computers, the adapter card supports hot-swapping FireWire device connections, allowing you to unplug and swap peripherals with ease.

The adapter card includes a 5ft FireWire cable as well as a copy of ULEAD's VideoStudio SE Basic video editing software (Windows only), making it easy to capture and edit video on your notebook computer, directly from your digital video camcorder.

### Certifications, Reports and Compatibility



### Applications

- iPods/MP3 players
- Portable hard drives
- External CDR-CDRW drives
- DVD drives
- Digital cameras
- Digital camcorders (compatible with Sony®, Canon®, Panasonic®, JVC®, Samsung® models)
- Scanners
- Printers

### Features

- Includes everything needed to edit your own home movies, add scene transitions and other effects with the included ULEAD® VideoStudio® SE software
- High speed data transfer rates of up to 400 Mbits/sec.
- Hot swap capabilities allows you to connect or disconnect devices without turning off your laptop
- Low power consumption preserves laptop computer battery life
- Connect up to 63 devices by cascading multiple hubs

<b>Hardware</b>	Warranty	Lifetime
	Bustyp	CardBus (PCMCIA)
	Chipset-ID	VIA - VT6306
	Industrienormen	1394A
		IEEE 1394-1995
		OHCI
	Ports	3
Schnittstelle	FireWire 400 (1394a)	
<b>Leistung</b>	Max. Datenübertragungsrate	400 Mbps
<b>Steckverbinder</b>	Steckverbindertyp(en)	1 - PC-Karte (Typ II, Cardbus) 3 - Firewire 400 (6-polig, IEEE 1394a) Buchse
	<b>Software</b>	Betriebssystemkompatibilität
<b>Spezielle Hinweise/Anforderungen</b>	Hinweis	Separate power adapter only required if connecting high-powered FireWire device(s) that draw more power than CardBus slot can provide.
	System- und Kabelanforderungen	32-bit CardBus Compatible PCMCIA Type II slot
<b>Strom</b>	Ausgangsspannung	12 DC
	Ausgangsstrom	1A+
	Mit Stromadapter	Nicht im Lieferumfang (nicht erforderlich für Standardanwendungen)
	Polarität der Mittelspitze	Positiv
<b>Physische Eigenschaften</b>	Produktbreite	2.1 in [5.4 cm]
	Produktgewicht	4.9 oz [140 g]
	Produktgröße	2 in [5 cm]
	Produktlänge	4.5 in [11.5 cm]
<b>Verpackungsinformationen</b>	Versandgewicht (Verpackung)	0.5 lb [0.2 kg]
<b>Verpackungsinhalt</b>	Im Paket enthalten	1 - CardBus FireWire Card 1 - FireWire 6-pin to 4-pin cable 1 - VideoStudio software CD 1 - Instruction Manual

Product appearance and specifications are subject to change without notice.