


50413512



Push-button insert, NO contact with rocker surface-mounted/flush-mounted with labelling field - illuminated, Berker W.1, polar white matt

Technical features

Architecture

Type of control unit	rocker

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC

Electric current

Momentary-contact current	10 A

Materials

RAL colour	RAL 9010 - Pure white
Colour of design line	polar white
Colour	white
Colour	polarwhite
Material	thermoplastic
Surface appearance	matt

Dimensions

Depth	42 mm
Height	71 mm
Width	71 mm
Labelling field (W x H)	50 x 16 mm

Installation, mounting

- for screw fastening

Connection

- Wago clip-in 3-wire connection terminal for wiring
- with N-terminal
- with plug-in terminals

Cable

- with cable entry at top and bottom

Equipment

- with {\b blue} 230 V LED unit

Use

- with labelling field - illuminated

Safety

Protection index IP	IP55

Use conditions

Operating temperature	-40 … 30 °C
Storage/transport temperature	-50 … 50 °C

Identification

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

Instructions

- Pins of quick-release lock made of ZAMAK
- For labelling with name, information notice, etc.
- Labelling field height arranged for P-touch strips 12 mm.
- Inserts will only reach the degree of protection IP55 if mounted with a housing surface mounted or frame for flush-mounted installation.