

Eaton 5E700D

Catalog Number: 5E700D

Eaton 5E Gen2 UPS DIN, 700 VA, 360 W, Input: Schuko, Outputs: (2) DIN, Tower

General specifications

Product Name	Catalog Number
Eaton 5E Gen2 UPS	5E700D
EAN	Product Length/Depth
3553340704147	288 mm
Product Height	Product Width
148 mm	100 mm
Product Weight	Warranty
4.29 kg	2 year
Compliances	Certifications
CB	IEC/EN 62040-1
LVD Directive	IEC/EN 62040-2
EMC Directive	CE
RoHS Directive	EAC
Packaging Directive	Ukr
WEEE Directive	IEC/EN 62040-3
Batteries Directive	UKCA
	Cm



Product specifications

Secondary frequency - max

60 Hz

Wattage

360 W

Form factor

Tower

Includes network card

No

Input connection

Protective contact (SCHUKO)

Input voltage - min

140 V

Output voltage - max

257 V

Secondary frequency - min

50 Hz

Battery type

Sealed, lead-acid

Efficiency

95

Special features

Automatic Voltage Regulation (AVR)

Saves space with a compact tower design

Includes two Schuko (DIN) Outlets

Construction type

Free standing model

Output voltage - min

195 V

Color

Black

Extended battery capability

No

Output voltage range

195-257 V

Topology

Line-interactive

Resources

Brochures

[eaton-dpq-5egen2-ups-quickstartguide-en-gb.pdf](#)

User guides

[eaton-dpq-5egen2-ups-manual-en-gb.pdf](#)

Surge protection

Yes

Input nominal voltage

230V default (220/230/240V)

Input frequency range

45-63 Hz

Internal bypass

No

Input voltage - max

300 V

Voltage type

AC

Phase (output)

1

Battery management

Automatic battery test, deep-discharge protection, cold-start capable

Auto shutdown function

No

Operating temperature - min

0 °C

VA rating

700 VA

Potential free switch contact

No

Receptacle

(2) Schuko

Phase (input)

1

Package contents

Quick start

Safety instructions

Feed type

1

Runtime graph

View runtime graph

User interface

LEDs

Battery quantity

1

Operating temperature - max

40 °C

Voltage

230V

Hot swap power

No

Input cord length

1.5 m

Temperature range

0° to 40°C (32° to 104°F)

Ethernet interface

No

Relative humidity

0-90% non-condensing

Output apparent power

700 VA

Rack mounting kit

No

Num of Outputs PC (SCHUKO)

2

Output frequency

50/60 Hz

Type of interface

None

Primary frequency - min

45 Hz

Battery rating

12 V / 7 Ah

Type

UPS

Output nominal voltage

230V

Expansion slots

No

Input voltage range

140-300 V

Nominal frequency

50/60 Hz

Primary frequency - max

63 Hz



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)