

AXIS Q1941-E PT Mount Thermal Network Camera

Wide thermal coverage with pan/tilt flexibility

The bullet-style, outdoor-ready AXIS Q1941-E PT Mount offers the possibility of mounting the camera on a pan/tilt motor to increase installation flexibility. The broad range of lenses make it easy to detect and verify people, objects and incidents from pitch dark areas to a sunlit parking lot. A noise filter gives improved thermal image contrast while keeping noise levels low, without adding blur and ghost effects. AXIS Q1941-E PT Mount withstands harsh weather conditions and has a built-in heater for the window. Additionally, it offers Power over Ethernet and has a microSD card slot.

- > [PT mount-ready](#)
- > [Powerful performance for video analytics](#)
- > [Electronic Image Stabilization](#)
- > [Axis Zipstream](#)



AXIS Q1941-E PT Mount Thermal Network Camera

Models	AXIS Q1941-E PT Mount 7 mm, 13 mm, 19 mm, 35 mm, 60 mm	Sustainability	PVC free
Camera		Memory	512 MB RAM, 256 MB Flash
Image sensor	Uncooled Micro bolometer 384x288, pixel size: 17 µm Spectral range: 8–14 µm	Power	Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 3 Typical 4.8 W, max 11.8 W 8–28 V DC: typical 6.6 W, max 13 W 20–24 V AC (50/60 Hz): typical 11 VA, max 19 VA Power supply not included.
Lens	7 mm: Horizontal field of view: 55° view, F1.2 13 mm: Horizontal field of view: 28° view, F1.0 19 mm: Horizontal field of view: 19.4° view, F1.23 35 mm: Horizontal field of view: 10.7° view, F1.2 60 mm: Horizontal field of view: 6.2° view, F1.25	Connectors	RJ45 10BASE-T/100BASE-TX PoE Terminal block for power RS485/RS422 for pan/tilt control
Sensitivity	NETD < 70 mK	Storage	Support for microSD/microSDHC/microSDXC card Support for recording to dedicated network-attached storage (NAS) For SD card and NAS recommendations see www.axis.com
Pan/Tilt	Preset positions, Guard tour, Driver selection, Control queue	Operating conditions	–40 °C to 60 °C (–40 °F to 140 °F) Humidity 10–100% RH (condensing)
Video		Storage conditions	–40 °C to 70 °C (–40 °F to 158 °F)
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	Approvals	EMC EN 55022 Class A, EN 50121-4, IEC 62236-4, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR22 Class A
Resolutions	Sensor is 384x288. Image can be scaled up to 768x576.	Safety	IEC/EN/UL 60950-1, IEC/EN/UL 60950-22
Frame rate	Up to 8.3 fps and 30 fps	Environment	EN 50581, NEMA 250 Type 4X, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6 Class 4M4, IEC 60068-2-27, IEC 60068-2-52, IEC 60721-3-4 Class 4K3 IEC 60529 IP66
Video streaming	At least three H.264 and Motion JPEG streams, simultaneous and individually configured in max. resolution in full frame rate Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/MBR H.264	Dimensions	309 x 105 mm (12 3/16 x 4 1/8 in)
Image settings	Compression, Brightness, Sharpness, Contrast, Exposure zone, Text and image overlay, Privacy mask, Mirroring of images, Electronic Image Stabilization, Multiple palettes Rotation: 0°, 180°	Weight	7/13/19 mm: 1800 g (4.0 lb) 35 mm: 1900 g (4.2 lb) 60 mm: 2000 g (4.4 lb)
Network		Included accessories	Torx® T20 screw driver, Terminal block connector Installation Guide, Windows decoder 1-user license
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log, Centralized Certificate Management	Optional accessories	Axis PoE Midspans, AXIS T8129 PoE Extender, AXIS T8640 PoE+ over Coax Adapter Kit, AXIS T8604 Media Converter Switch AXIS T8415 Wireless Installation Tool AXIS T8310 Control Board For more accessories, see www.axis.com
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	Video management software	AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on www.axis.com/techsup/software
System integration		Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Application Programming Interface	Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF® Profiles S and G, specifications at www.onvif.org	Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty
Analytics	Video motion detection, shock detection Support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications, see www.axis.com/acap	Export control	This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.
Event triggers	Analytics, Temperature, External input, Time scheduled, Edge storage events PTZ preset	Environmental responsibility: www.axis.com/environmental-responsibility	
Event actions	File upload: FTP, SFTP, HTTP, HTTPS network share and email Notification: email, HTTP, HTTPS and TCP and SNMP trap External output activation Video recording to edge storage Pre- and post-alarm video buffering PTZ preset, Guard tour, Overlay text		
Data streaming	Event data		
Built-in installation aids	Pixel counter		
General			
Casing	IP66- and NEMA 4X-rated Metal casing (aluminum) with integrated dehumidifying membrane and a germanium window Color: White NCS S 1002-B		