

Alphacool ES Aluminium 280 mm T38 - (for Industry only)

Alphacool article number: 14430

The all-aluminium ES T27 and T38 radiators from Alphacool's ENTERPRISE SOLUTIONS series were specially developed for use in the industrial range. Due to the low construction height of 27mm or 38mm, they find space in the smallest of spaces and enable the water cooling of technical equipment in the automotive industry, in mechanical engineering or in the production of films and videos.

Alphacool ES Aluminium 280 mm T38 - (for Industry only)



- Low overall height & variable use
- Suitable for industrial high-performance fans
- Additional cooling channels for more cooling capacity

We assume no responsibility for any typing errors.

Alphacool International GmbH, Marienberger Strasse 1, 38122 Braunschweig Tel: (+49)0531 288 740 Supportmail: info@alphacool.com

Scope of delivery

1x Alphacool ES Aluminium 280 mm T38, Black
8x M3x30 screw
8x M3x5 screw

Technical data

L x W x H	315 x 140 x 38 mm
Material cooling fins, channels & prechamber	Aluminium
Material outer housing & threads	Aluminium
Fins per Inch	20
Threads	2x G1/4"
Thread size fan mounting	M3
Fan size	140 mm
Fan slots	2 one-sided / 4 double-sided
Max working temperature	90 °C
Pressure tested	2,0 Bar
Weight	593 g
Color	Black

Download Links

Product pics	https://www.alphacool.com/download/1021479_ES_Aluminium_280_mm_T38_Radiator_pics.zip
--------------	---

Packaging dimensions 1 unit

L x W x H	36 x 15 x 5 cm
Weight	0,759 kg

Other data

Certificates	CE, FC, RoHS
EAN	4250197144308
Customs code	84195080900

We assume no responsibility for any typing errors.

Alphacool International GmbH, Marienberger Strasse 1, 38122 Braunschweig Tel: (+49)0531 288 740 Supportmail: info@alphacool.com

Article text

The all-aluminium ES T27 and T38 radiators from Alphacool's ENTERPRISE SOLUTIONS series were specially developed for use in the industrial range. Due to the low construction height of 27mm or 38mm, they find space in the smallest of spaces and enable the water cooling of technical equipment in the automotive industry, in mechanical engineering or in the production of films and videos.

High performance cooling!

Compared to Alphacool's full copper models, all ES T27 and T38 aluminium radiators have additional cooling channels. This technical design allows a significant increase in cooling capacity without restricting the water flow within the radiator. The radiators have a high fin density and are particularly suitable for use with fans with high air pressure and air throughput. This achieves a significant increase in the performance of the water-cooled components.


Fitting and mounting options

The radiator offers an inlet and outlet (IN/OUT) with G1/4" thread. Screws for case mounting (M3x5) and for fan mounting (M3x30) are included with the radiator. Additional screws are not required for single-sided fan mounting.

Important note

This is an Enterprise Solutions Aluminium product. The ES aluminium radiators must not be used together with copper water cooling products (radiators, fitting, etc.). Using aluminium & copper components together will cause severe damage to the liquid cooling loop.

Dimensions



Note

ALU

Attention:

This is an Enterprise Solutions Aluminium Product.
Not compatible to cooling loops with copper parts.

We assume no responsibility for any typing errors.

Alphacool International GmbH, Marienberger Strasse 1, 38122 Braunschweig Tel: (+49)0531 288 740 Supportmail: info@alphacool.com