Additional pan/tilt camera for ABUS EasyLook BasicSets

Art.-Nr. PPDF17620



Up to four cameras per monitor
Add up to 4 cameras to your ABUS EasyLook BasicSet. Commissioning an additional pan/tilt camera is just as easy as with the basic set and done in just a few steps.

Just like the camera in the basic set, an additional camera reliably delivers video images day & night. The security camera performs its job without internet/Wi-Fi, without an app and without a smartphone - all it needs is power. The video data and settings are securely encrypted and quickly transmitted wirelessly between the security camera and the monitor of the basic set.

Commissioning the additional camera is just as easy as with the basic set. A total of up to 4 cameras can be easily operated with one monitor; if needed, the screen displays all live images from the cameras simultaneously - with a simple finger gesture, it is possible to quickly switch between the “quad view” and individual camera images.

So you always have a view of what is happening in your shop or around your home, whether at the entrance, in front of the garage, on the terrace or in the garden.

Technologies

- Extension for the ABUS EasyLook BasicSet; additional pan/tilt camera with high wireless range, person detection, intercom function, night vision, privacy zone masking and much more
- A total of 4 security cameras (with/without pan/tilt function) can be connected to the monitor of the ABUS EasyLook BasicSet
- Very easy to use, even for subsequent commissioning; supply power to the additional camera, add it to the set monitor and the first live image will appear
- Set up surveillance camera just the way you like it on the monitor: Standard motion detection or person detection only, deactivate audio/sound for recordings, image areas with/without recognition, schedules, privacy zones and

Subject to technical modifications. We assume no liability for mistakes and printing errors. © ABUS 11/2024

Additional pan/tilt camera for ABUS EasyLook BasicSets

more.

- Clear night vision in black and white (via infrared LED) up to 15 metres, 3-megapixel camera resolution, zoom function, 82-degree viewing angle, camera protection class IP66 (weatherproof; protection against strong jets of water, dustproof)
- The EasyLook BasicSet Monitor immediately and automatically switches to alarm and recording mode (siren sound on the monitor can be switched on/off as required)
- No further costs (no subscription, no cloud)

Technical data - Additional pan/tilt camera for ABUS EasyLook BasicSets

Area of application	Outdoor use
Base event	Software + Motion Mask
Channel width	20 MHz
Colour	Black
Compatible with	PPDF17000; PPDF17100
Compatible with Secoris	No
Compatible with Secvest	No
Compatible with Smartvest	No
Compatible with wAppLoxx	No
DC voltage supply	12 V
Day/night switching	Auto
Dimensions	210 x 120 x 160 mm
Encryption	WPA2
Focal length	4,1 mm
Frequency range	2,403 - 2,478 GHz
Functions	Intercom (2-way audio), Night vision, Zoom, People recognition
Horizontal viewing angle	85 °
Housing material	Plastic
IP protection class	66
IR LEDs	Yes
IR range (up to)	15 m
Image sensor	1/3" CMOS
Loudspeaker	Yes
Max. humidity	90 %
Max. operating temperature	50 °C
Max. resolution @ frame rate	2304 x 1296 @15fps
Microphone	Yes
Min. humidity	30
Min. operating temperature	-10 °C
Minimum illumination (IR)	0,1 lx

Subject to technical modifications. We assume no liability for mistakes and printing errors. © ABUS 11/2024

Additional pan/tilt camera for ABUS EasyLook BasicSets

Art.-Nr. PPDF17620

Technical data - Additional pan/tilt camera for ABUS EasyLook BasicSets

Minimum illumination (colour)	1 lx
Net weight	0,687 kg
Optical Wave Length	940 nm
Pan/tilt range	270° / 90°
Plug type	DC-plug: 5,5 x 2,0 mm
Power consumption	3,75 W
Power supply	Power adapter
Private zones	4
Resolution modes	2304 x 1296 (3MP)
Sensitivity	-88 dBm
Technology	Wireless
Transmission power	20 dBm
Vertical viewing angle	45 °
Video bit rate	2Mbps
Video compression	H.264+
White balance	Auto
Wireless range	(Depending on installation) 20 - 50 m

Subject to technical modifications. We assume no liability for mistakes and printing errors. © ABUS 11/2024