

47517104

**SCHUKO socket outlet with hinged cover enhanced contact protection, Berker K.5, stainless steel, metal matt finish**

Technical features

**Architecture**

| | |
|---|---|
| Design | according to DIN 49440 |

**Main electrical features**

| | |
|---|---|
| Nominal voltage | 250 V |
| Rated current | 16 A |
| Rated voltage | 250 V AC |

**Cover, door**

- when opening hinged cover, it can be arrested in end position
- Central cover plate

**Materials**

| | |
|---|---|
| RAL colour | RAL 9022 - Pearl light grey |
| Colour of design line | Stainless steel |
| Colour | stainless steel optics |
| Colour | stainless steel |
| Material / workmanship | metal, matt finish |
| Material | stainless steel |
| Surface appearance | matt |

**Installation, mounting**

- with spreader claws

**Connection**

| | |
|---|---|
| Connection terminals | according to IEC 60884-1 |
| Connection terminals | according to VDE 0620-1 |

- with plug-in terminals

**Use**

- enhanced contact protection

**Safety**

| | |
|---|---|
| Protection index IP | IP20 |
| IK protection code against mecanical impacts | 07 |
| Enhanced contact protection (child protection) | according to IEC 60884-1 |
| Enhanced contact protection (child protection) | according to VDE 0620-1 |

- Enhanced contact protection

**Identification**

| | |
|---|---|
| Main design line | Berker K.5 |
| Secondary design line(s) | Berker K.5 |