

47496084

SCHUKO socket outlet with labelling field, enhanced contact protection, Berker Q.1/Q.3/Q.7/Q.9

Technical features

Architecture

Design	according to DIN 49440

Main electrical features

Nominal voltage	250 V
Rated current	16 A
Rated voltage	250 V AC

Cover, door

- Central cover plate

Materials

RAL colour	RAL 9006 - White aluminium
Colour of design line	aluminium
Colour	aluminium optics
Colour	aluminium
Material / workmanship	lacquered
Material	thermoplastic
Surface appearance	velvety

Dimensions

Insertion depth	32 mm

Installation, mounting

- with spreader claws

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1

- with plug-in terminals

Use

- with labelling field
- enhanced contact protection

Safety

Protection index IP	IP20
IK protection code against mecanical impacts	02
Enhanced contact protection (child protection)	according to IEC 60884-1
Enhanced contact protection (child protection)	according to VDE 0620-1

- Enhanced contact protection

Identification

Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.3, Berker Q.1

Instructions

- Labelling field height arranged for P-touch strips 6 mm.