# DATASHEET

## RJ45 Patch cable S/FTP, Cat.6A, 2x TM21 90°, UC900, green



Cat.6A | 10 Gbit | 500 MHz | 100% CU | made in Europe | CE

### Description

The Cat.6A RJ45 patch cable **manufactured in Europe** guarantees very good characteristics for **10 Gigabit** Ethernet applications. The patch cable is composed of the Cat.7 raw cable **UC900 SS27** from Draka and **TM21** connectors from Hirose. Due to the **90° angled grommet**, the patch cable is well suited for limited space conditions.

Cross section 4 x 2 x AWG27/7
Mounted bend protection grommet 90° angled

| General data | |
|---|---|
| Category | 6A (TIA) |
| Type of connector connection 1 | RJ45 8(8) |
| Type of connector connection 2 | RJ45 8(8) |
| Connector type | TM21 red |
| Cable type | Draka UC900 SS27 |
| Contacts | Gold plated |
| Pin assignment | 1:1 |
| Allocation | acc. TIA/EIA 568B |
| Type | Shielded |
| Anti-kink sleeve | put-on |
| Colour anti-kink sleeve | black |
| Locking lever | yes |

| Mechanical characteristics | |
|---|---|
| Mating cycles | ≥750 |
| Bending radius | >25 mm |
| Conductive shield | 360° shield contact |

**This datasheet was created automatically on 05-02-2020 . Technical changes reserved.**

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

# DATASHEET

## RJ45 Patch cable S/FTP, Cat.6A, 2x TM21 90°, UC900, green

| Cable construction | |
|---|---|
| Raw cable | Cat.7 |
| Cable structure | S/FTP |
| Total screening | ca. 45 % |
| Cable construction | 4x2 |
| AWG-size/strands per core | 27/7 |
| Conductor Material | Copper |

| Cable sheath | |
|---|---|
| Jacket material | LSZH |
| Colour outer sheath | green |
| Outer diameter of the cable | 5.9 mm |
| Euro class | Eca |
| Flame-retardant | acc. IEC60332-1 |
| Halogen-free | acc. IEC60754-2 |
| Low smoke | acc. IEC61034 |

| Environmental conditions | |
|---|---|
| Temperature Range (Operation) | -20 – 60 °C |
| Temperature Range (Installation) | 0 – 50 °C |

| Electrical characteristics | |
|---|---|
| NVP value | 79 % |
| Impedance | 100 ±25 Ω |
| Conductor resistance DC | 170 Ω/km |
| Loop resistance | < 340 Ω/km |
| Resistance unbalance | < 3 % |
| Insulation resistance | > 2000 MΩ |
| Test voltage | 1000 (V DC, 1min) core/core und core/screen |

| Transmission characteristics | |
|---|---|
| Bandwidth | 500MHz |

| Standards, approvals, certifications | |
|---|---|
| Connector | IEC 60603-7-51 |
| Harmonised Standard | EN 50575 |

**Available variants**



EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

# DATASHEET

## RJ45 Patch cable S/FTP, Cat.6A, 2x TM21 90°, UC900, green

| Article no. | Title | Length |
|---|---|---|
| K4137GN.0,50 | RJ45 Patch cable S/FTP, Cat.6A, 2x TM21 90°, UC900, 0,5m, green | 0.5 m |
| K4137GN.1 | RJ45 Patch cable S/FTP, Cat.6A, 2x TM21 90°, UC900, 1m, green | 1.0 m |
| K4137GN.1,5 | RJ45 Patch cable S/FTP, Cat.6A, 2x TM21 90°, UC900, 1,5m, green | 1.5 m |
| K4137GN.2 | RJ45 Patch cable S/FTP, Cat.6A, 2x TM21 90°, UC900, 2m, green | 2.0 m |
| K4137GN.3 | RJ45 Patch cable S/FTP, Cat.6A, 2x TM21 90°, UC900, 3m, green | 3.0 m |
| K4137GN.5 | RJ45 Patch cable S/FTP, Cat.6A, 2x TM21 90°, UC900, 5m, green | 5.0 m |
| K4137GN.10 | RJ45 Patch cable S/FTP, Cat.6A, 2x TM21 90°, UC900, 10m, green | 10.0 m |
| K4137GN.15 | RJ45 Patch cable S/FTP, Cat.6A, 2x TM21 90°, UC900, 15m, green | 15.0 m |

| similar product | |
|---|---|
| K4137WS.1 | RJ45 Patch cable S/FTP, Cat.6A, 2x TM21 90°, UC900, white |
| K4137SW.1 | RJ45 Patch cable S/FTP, Cat.6A, 2x TM21 90°, UC900, black |
| K4137RT.1 | RJ45 Patch cable S/FTP, Cat.6A, 2x TM21 90°, UC900, red |
| K4137OR.1 | RJ45 Patch cable S/FTP, Cat.6A, 2x TM21 90°, UC900, orange |
| K4137GR.1 | RJ45 Patch cable S/FTP, Cat.6A, 2x TM21 90°, UC900, grey |
| K4137GE.1 | RJ45 Patch cable S/FTP, Cat.6A, 2x TM21 90°, UC900, yellow |
| K4137BL.1 | RJ45 Patch cable S/FTP, Cat.6A, 2x TM21 90°, UC900, blue |

**This datasheet was created automatically on 05-02-2020 . Technical changes reserved.**

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION