

Hardware Maintenance Manual

Lenovo
IDEAPAD

Lenovo

IdeaPad 5i 2-in-1 (14", 11), IdeaPad 5i 2-in-1 (15", 11), IdeaPad 5a 2-in-1 (14", 11), IdeaPad 5a 2-in-1 (15", 11)

First Edition (February 2026)

© Copyright Lenovo 2026.

LIMITED AND RESTRICTED RIGHTS NOTICE: If data or software is delivered pursuant to a General Services Administration "GSA" contract, use, reproduction, or disclosure is subject to restrictions set forth in Contract No. GS-35F-05925.

Contents

About this manual	. iii
--------------------------	--------------

Chapter 1. Safety requirements for hardware maintenance	. 1
--	------------

General safety requirements	1
Electrical safety requirements	1
Safety inspection guide	3
Handling devices that are sensitive to electrostatic discharge	3
Important danger warning in multiple languages	4

Chapter 2. Diagnostics and troubleshooting	. 17
---	-------------

Diagnostics applications	17
Hardware scan in Vantage	17
UEFI diagnostics application	18
Advanced diagnostics application (Windows version)	18
Advanced diagnostics application (bootable versions for Linux/UEFI)	18
Call Lenovo	19
Before you contact Lenovo	19
Lenovo Customer Support Center	19
Nonwarranted items and activities	20

Chapter 3. Parts, screws, and tools	. 21
--	-------------

Parts	21
Part type definition	21
Look up a part	22
Exploded view and part list (for 14-inch models)	22
Exploded view and part list (for 15-inch models)	24
Screws	26
Screw list	26
Screw notices	27
Service tools	28

Chapter 4. Hardware replacement (for 14-inch models)	. 31
---	-------------

General guidelines	31
Lower case	31
Label locations	33
Battery pack	36
M.2 solid-state drive	36
2242 trans cover	37
Wi-Fi card	38

Type-C bracket	40
Memory	40
Heat sink	41
Handling thermal interface materials	43
Speakers	45
Fan	46
I/O board	46
Display module	47
Panel Self Test	50
Disassemble the display module	50
System board (with I/O board cable, PMIC cable, and PMIC board)	61
Write key product information to a replacement system board	64
Upper case	65

Chapter 5. Hardware replacement (for 15-inch models)	. 66
---	-------------

General guidelines	66
Lower case	66
Label locations	67
Battery pack	71
M.2 solid-state drive	73
2242 trans cover	74
Wi-Fi card	75
Memory	77
Fan	78
Heat sink	79
Handling thermal interface materials	81
Speakers	82
Display module	84
Panel Self Test	86
Disassemble the display module	86
Type-C bracket	98
I/O board	99
System board (with I/O board cable, PMIC cable, and PMIC board)	99
Write key product information to a replacement system board	102
Upper case	103

Appendix A. Artworks for laser etched labels (IdeaPad 5 2-in-1 14AGP11)	. 104
--	--------------

Appendix B. Artworks for laser etched labels (IdeaPad 5 2-in-1 14AHP11)	. 107
--	--------------

Appendix C. Artworks for laser etched labels (IdeaPad 5 2-in-1 15AGP11).	110
---	---------------------

Appendix D. Artworks for laser etched labels (IdeaPad 5 2-in-1 15AHP11).	114
---	---------------------

Appendix E. Artworks for laser etched labels (IdeaPad 5 2-in-1 15IPH11)	117
--	---------------------

Appendix F. Important notice for Quebec consumers	121
--	---------------------

Appendix G. Self-help resources	. . .122
Trademarks	 cxxiv

About this manual

This manual contains hardware maintenance instructions for the products listed in the following table. In this manual, you will read safety requirements for hardware maintenance, diagnostics and troubleshooting, hardware replacement instructions, and other reference information. Use the manual along with the diagnostics applications and service tools to troubleshoot problems effectively.

Product name	Machine type (MT)
IdeaPad 5 2-in-1 14IPH11	83UG
IdeaPad 5 2-in-1 14AGP11	83UH
IdeaPad 5 2-in-1 14AHP11	83UJ
IdeaPad 5 2-in-1 15IPH11	83UL
IdeaPad 5 2-in-1 15AGP11	83UM
IdeaPad 5 2-in-1 15AHP11	83UN

Important:

- Hardware configurations and software programs vary by machine type. Some statements or illustrations in this manual might be slightly different from your computer.
- It is recommended that the computer be repaired by trained service technicians.
- For customers electing to service the computer on their own, it is still recommended to speak to our Customer Support Center so that you can be directed to the correct documentation and repair information. See “Call Lenovo” on page 19. Depending on the complexity of the repair, it may be recommended to have a Lenovo-authorized service provider repair your computer.
- Before servicing a computer, please follow all instructions carefully and be sure to read all the information under Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 31.

Chapter 1. Safety requirements for hardware maintenance

This chapter presents the following safety information that you need to be familiar with before you service a Lenovo notebook computer.

General safety requirements

Meet the following requirements on environment, personnel and outfit, and operation to ensure general safety:

Environment requirements

Observe good housekeeping in the area of the machines during and after maintenance.

Personnel and outfit requirements

- Do not wear loose clothing that can be trapped in the moving parts of a machine. Make sure that your sleeves are fastened or rolled up above your elbows. If your hair is long, fasten it.
- Insert the ends of your necktie or scarf inside clothing or fasten it with a non-conductive clip, about 8 centimeters (3 inches) from the end.
- Do not wear jewelry, chains, metal-frame eyeglasses, or metal fasteners for your clothing.

Attention: Metal objects are good electrical conductors.

- Wear safety glasses when you are hammering, drilling, soldering, cutting wire, attaching springs, using solvents, or working in any other conditions that might be hazardous to your eyes.

Operation requirements

- Before you start the machine, make sure that no one is in a hazardous position.
- Do not perform any action that causes personal injury, or that makes the equipment unsafe.
- Keep your tool case away from walk areas so that other people will not trip over it.
- When lifting any heavy object:
 1. Make sure that you can stand safely without slipping.
 2. Distribute the weight of the object equally between your feet.
 3. Use a slow lifting force. Never move suddenly or twist when you attempt to lift.
 4. Lift by standing or by pushing up with your leg muscles; this action removes the strain from the muscles in your back. Do not attempt to lift any object that weighs more than 16 kg (35 lb) or that you think is too heavy for you.
- Place removed covers and other parts in a safe place, away from all personnel, while you are servicing the machine.
- After service, reinstall all safety shields, guards, labels, and ground wires. Replace any safety device that is worn or defective. Reinstall all covers correctly.
- Fan louvers on the machine help to prevent overheating of internal components. Do not obstruct fan louvers or cover them with labels or stickers.

Electrical safety requirements

To ensure electrical safety, meet the following requirements on environment, outfit, and operation when working on the computer:

Environment requirements

- Find the room emergency power-off (EPO) switch, disconnecting switch, or electrical outlet. If an electrical accident occurs, you can then operate the switch or unplug the power cord quickly.
- Do not work alone under hazardous conditions or near equipment that has hazardous voltages.

- Always look carefully for possible hazards in your work area. Examples of these hazards are moist floors, non-grounded power extension cables, power surges, and missing safety grounds.

Outfit requirements

- Do not use worn or broken tools and testers.
- Regularly inspect and maintain your electrical hand tools for safe operational condition.

Important:

- Use only approved tools and test equipment. Some hand tools have handles covered with a soft material that does not insulate you when working with live electrical currents.
- Many customers have, near their equipment, rubber floor mats that contain small conductive fibers to decrease electrostatic discharges. Do not use this type of mat to protect yourself from electrical shock.

Operation requirements

- Disconnect all power before:
 - Performing a mechanical inspection
 - Working near power supplies
 - Removing or installing main units
- Do not service the following parts with the power on when they are removed from their normal operating places in a machine:
 - Power supply units
 - Pumps
 - Blowers and fans
 - Motor generators
 - Similar units as listed above

This practice ensures correct grounding of the units.
- Electrical grounding of the computer is required for operator safety and correct system function. Proper grounding of the electrical outlet can be verified by a certified electrician.
- Observe the special safety precautions when you work with very high voltages; Instructions for these precautions are in the safety sections of maintenance information. Use extreme care when measuring high voltages.
- Before you start to work on the machine, unplug the power cord. If you cannot unplug it, ask the customer to power-off the wall box that supplies power to the machine, and to lock the wall box in the off position.
- Never assume that power has been disconnected from a circuit. First, check that it has been powered off.
- Do not touch live electrical circuits with the reflective surface of a plastic dental mirror. The surface is conductive; such touching can cause personal injury and machine damage.
- If you need to work on a machine that has exposed electrical circuits, observe the following precautions:
 - Ensure that another person, familiar with the power-off controls, is near you.

Attention: Another person must be there to switch off the power, if necessary.

- Use only one hand when working with powered-on electrical equipment; keep the other hand in your pocket or behind your back.

Attention: An electrical shock can occur only when there is a complete circuit. By observing the above rule, you may prevent a current from passing through your body.

- When using testers, set the controls correctly and use the approved probe leads and accessories for that tester.
- Stand on suitable rubber mats (obtained locally, if necessary) to insulate you from grounds such as metal floor strips and machine frames.
- If an electrical accident occurs:
 - Use caution; do not become a victim yourself.
 - Switch off power.
 - Send another person to get medical aid.

Safety inspection guide

The purpose of this inspection guide is to assist you in identifying potentially unsafe conditions. As each machine was designed and built, required safety items were installed to protect users and service technicians from injury. This guide addresses only those items. You should use good judgment to identify potential safety hazards due to attachment of non-Lenovo features or options not covered by this inspection guide.

If any unsafe conditions are present, you must determine how serious the apparent hazard could be and whether you can continue without first correcting the problem.

Consider these conditions and the safety hazards they present:

- Electrical hazards, especially primary power (primary voltage on the frame can cause serious or fatal electrical shock)
- Explosive hazards, such as a damaged cathode ray tube (CRT) face or a bulging capacitor
- Mechanical hazards, such as loose or missing hardware

To determine whether there are any potentially unsafe conditions, use the following checklist at the beginning of every service task. Begin the checks with the power off, and the power cord disconnected.

Checklist:

1. Check exterior covers for damage (loose, broken, or sharp edges).
2. Power off the computer. Disconnect the power cord.
3. Check the power cord for:
 - a. A third-wire ground connector is in good condition. Use a meter to measure third-wire ground continuity for 0.1 ohm or less between the external ground pin and the frame ground.
 - b. The power cord should be the authorized type specified for your computer. Go to: <http://www.lenovo.com/serviceparts-lookup>
 - c. Insulation must not be frayed or worn.
4. Check for cracked or bulging batteries.
5. Remove the cover.
6. Check for any obvious non-Lenovo alterations. Use good judgment as to the safety of any non-Lenovo alterations.
7. Check inside the unit for any obvious unsafe conditions, such as metal filings, contamination, water or other liquids, or signs of fire or smoke damage.
8. Check for worn, frayed, or pinched cables.
9. Check that the power-supply cover fasteners (screws or rivets) have not been removed or tampered with.

Handling devices that are sensitive to electrostatic discharge

Any computer part containing transistors or integrated circuits (ICs) should be considered sensitive to electrostatic discharge (ESD). ESD damage can occur when there is a difference in charge between objects. Protect against ESD damage by equalizing the charge so that the machine, the part, the work mat, and the person handling the part are all at the same charge.

Notes:

1. Use product-specific ESD procedures when they exceed the requirements noted here.
2. Ensure that the ESD protective devices you use have been certified (ISO 9000) as fully effective.

When handling ESD-sensitive parts:

- Keep the parts in protective packages until they are inserted into the product.
- Avoid contact with other people.
- Wear a grounded wrist strap against your skin to eliminate static on your body.
- Prevent the part from touching your clothing. Most clothing is insulative and retains a charge even when you are wearing a wrist strap.

- Use a grounded work mat to provide a static-free work surface. The mat is especially useful when handling ESD-sensitive devices.
- Select a grounding system, such as those listed below, to provide protection that meets the specific service requirement.

Note: The use of a grounding system to guard against ESD damage is desirable but not necessary.

- Attach the ESD ground clip to any frame ground, ground braid, or green-wire ground.
- When working on a double-insulated or battery-operated system, use an ESD common ground or reference point. You can use coax or connector-outside shells on these systems.
- Use the round ground prong of the ac plug on ac-operated computers.

Important danger warning in multiple languages

The safety notices in this section are provided in the following languages:

- English
- Arabic
- Brazilian Portuguese
- French
- German
- Hebrew
- Japanese
- Korean
- Spanish
- Traditional Chinese

English



DANGER

Before the computer is powered on after FRU replacement, make sure that all screws, springs, and other small parts are in place and are not left loose inside the computer. Verify this by shaking the computer and listening for rattling sounds. Metallic parts or metal flakes can cause electrical short circuits.



DANGER

Some standby batteries contain a small amount of nickel and cadmium. Do not disassemble a standby battery, recharge it, throw it into fire or water, or short-circuit it. Dispose of the battery as required by local ordinances or regulations. Use only the battery in the appropriate parts listing. Use of an incorrect battery can result in ignition or explosion of the battery.



DANGER

The battery pack contains small amounts of nickel. Do not disassemble it, throw it into fire or water, or short-circuit it. Dispose of the battery pack as required by local ordinances or regulations. Use only the battery in the appropriate parts listing when replacing the battery pack. Use of an incorrect battery can result in ignition or explosion of the battery.



DANGER

The lithium battery can cause a fire, an explosion, or a severe burn. Do not recharge it, remove its polarized connector, disassemble it, heat it above 100°C (212°F), incinerate it, or expose its cell contents to water. Dispose of the battery as required by local ordinances or regulations. Use only the battery in the appropriate parts listing. Use of an incorrect battery can result in ignition or explosion of the battery.



DANGER

If the LCD breaks and the fluid from inside the LCD gets into your eyes or on your hands, immediately wash the affected areas with water for at least 15 minutes. Seek medical care if any symptoms from the fluid are present after washing.



DANGER

To avoid shock, do not remove the plastic cover that protects the lower part of the inverter card.



DANGER

Though the main batteries have low voltage, a short-circuited or grounded battery can produce enough current to burn personnel or combustible materials.



DANGER

Unless hot swap is allowed for the FRU being replaced, do as follows before removing it: power off the computer, unplug all power cords from electrical outlets, remove the battery pack, and disconnect any interconnecting cables.

Arabic



قبل إعادة تشغيل الحاسب بعد الانتهاء من استبدال FRU، تأكد من أنه قد تم إعادة كل من المسامير و السوست وكل الأجزاء الصغيرة الأخرى في أماكنهم ولم يتم فتحهم داخل الحاسب. ويمكن التحقق من ذلك عن طريق هز الحاسب والاستماع لأي صوت صاخب يصدر منه. قد تؤدي الأجزاء أو الرفائق المعدنية إلى حدوث دائرة قصر.



تحتوي بعض البطاريات الاحتياطية على كمية صغيرة من مادتي النيكل والكاديوم. لا تقم بفك أو إعادة شحن البطارية الاحتياطية ولا تقم أيضا بالقائها في النار أو الماء ولا تتسبب في احداث دائرة قصر بها. قم بالتخلص من البطارية كما هو موضح في القوانين المحلية. استخدم نوع البطارية المحدد والذي يوصى باستخدامه. حيث أنه قد يؤدي استخدام نوع بطارية غير صحيح الى اشتعالها أو انفجارها.



تحتوي حزمة البطارية على كمية صغيرة من مادة النيكل. لا تقم بفكها أو القاءها في النار أو الماء ولا تتسبب في احداث دائرة قصر بها. تخلص من حزمة البطارية وفقا لما هو موضح في القوانين المحلية. قم، عند استبدال حزمة البطارية، باستخدام الأنواع المحددة فقط والتي يوصى باستخدامها. حيث أنه قد يؤدي استخدام نوع بطارية غير صحيح الى اشتعالها أو انفجارها.



قد تتسبب بطارية الليثيوم في حدوث حريق أو انفجار أو حدوث حروق شديدة. لا تقم بإعادة شحن البطارية أو إزالة موصل الاستقطاب الخاص بها ولا تحاول أيضا فكها أو تسخينها لأكثر من ١٠٠ درجة مئوية (٢١٢ فهرنهايت) أو حرقها أو تعريض محتويات الخانة الخاصة بها للماء. قم بالتخلص من البطارية وفقا لما هو موضح في القوانين المحلية. استخدم نوع البطارية المحدد والذي يوصى باستخدامه. حيث أنه قد يؤدي استخدام نوع بطارية غير صحيح الى اشتعالها أو انفجارها.



إذا ما انكسرت شاشة LCD ولامس السائل الداخلي عينيك أو يديك، قم في الحال بغسلهما بالماء لمدة لا تقل عن ١٥ دقيقة. إذا ما وجدت أي أعراض بعد الغسل اطلب عندئذ المساعدة الطبية.



لتجنب التعرض لأي صدمات، لا تقم بإزالة الغطاء البلاستيكي الذي يحمي الجزء الأسفل من بطاقة العاكس.



على الرغم من أن البطاريات الرئيسية يكون لها جهد منخفض، إلا أنه قد تقوم البطاريات التي حدث قصور بها أو التي تم توصيلها أرضيا بإصدار تيار يكفي لحدوث حروق للأفراد أو تعرض المواد القابلة للاشتعال للحريق.



ما لم يتم السماح بالتبديل الفوري لأي FRU الجاري استبداله بدون ضرورة اغلاق النظام، قم بتنفيذ ما يلي قبل ازالته. قم بإيقاف تشغيل الحاسب ونزع كل أسلاك الطاقة من المخارج الكهربائية وقم أيضا بإزالة حزمة البطارية ثم قم بفصل أي كابلات متصلة.

Brazilian Portuguese



PERIGO

Antes de ligar o computador após a substituição da FRU, certifique-se de que todos os parafusos, molas e outras peças pequenas estejam no lugar e não estejam soltos dentro do computador. Verifique isso sacudindo o computador e procurando ouvir sons de peças soltas. Peças metálicas ou lascas de metal podem causar curto-circuito.



PERIGO

Algumas baterias reserva contêm uma pequena quantidade de níquel e cádmio. Não desmonte uma bateria reserva, recarregue-a, jogue-a no fogo ou na água, ou deixe-a entrar em curto-circuito. Descarte a bateria conforme requerido pelas leis ou regulamentos locais. Use somente a bateria nas partes listadas apropriadas. O uso de uma bateria incorreta pode resultar em combustão ou explosão da bateria.



PERIGO

O pacote da bateria contém uma pequena quantidade de níquel. Não o desmonte, jogue-o no fogo ou na água, ou deixe-o entrar em curto-circuito. Descarte o pacote da bateria conforme requerido pelas leis ou regulamentos locais. Use somente a bateria nas partes listadas apropriadas ao substituir o pacote da bateria. O uso de uma bateria incorreta pode resultar em combustão ou explosão da bateria.



PERIGO

A bateria de lítio pode causar incêndio, explosão ou graves queimaduras. Não a recarregue, remova seu conector polarizado, desmonte-a, aqueça-a acima de 100°C (212°F), incinere-a, ou exponha o conteúdo de sua célula à água. Descarte a bateria conforme requerido pelas leis ou regulamentos locais. Use somente a bateria nas partes listadas apropriadas. O uso de uma bateria incorreta pode resultar em combustão ou explosão da bateria.



PERIGO

Se o LCD quebrar e o fluido de dentro dele entrar em contato com seus olhos ou com suas mãos, lave as áreas afetadas imediatamente com água durante pelo menos 15 minutos. Procure cuidados médicos se algum sintoma causado pelo fluido surgir após a lavagem.



PERIGO

Para evitar choque elétrico, não remova a capa plástica que protege a parte inferior da placa inversora.



PERIGO

Embora as principais baterias possuam baixa voltagem, uma bateria em curto-circuito ou aterrada pode produzir corrente o bastante para queimar materiais de pessoal ou inflamáveis.



PERIGO

A menos que uma hot swap seja permitida para a FRU que está sendo substituída, faça o seguinte antes de removê-la: desligue o computador, desconecte todos os cabos de energia das tomadas, remova o pacote de baterias e desconecte quaisquer cabos de interconexão.

French



DANGER

Avant de remettre l'ordinateur sous tension après remplacement d'une unité en clientèle, vérifiez que tous les ressorts, vis et autres pièces sont bien en place et bien fixées. Pour ce faire, secouez l'unité et assurez-vous qu'aucun bruit suspect ne se produit. Des pièces métalliques ou des copeaux de métal pourraient causer un court-circuit.



DANGER

Certaines batteries de secours contiennent du nickel et du cadmium. Ne les démontez pas, ne les rechargez pas, ne les exposez ni au feu ni à l'eau. Ne les mettez pas en court-circuit. Pour les mettre au rebut, conformez-vous à la réglementation en vigueur. Lorsque vous remplacez la pile de sauvegarde ou celle de l'horloge temps réel, veillez à n'utiliser que les modèles cités dans la liste de pièces détachées adéquate. Une batterie ou une pile inappropriée risque de prendre feu ou d'exploser.



DANGER

La batterie contient du nickel. Ne la démontez pas, ne l'exposez ni au feu ni à l'eau. Ne la mettez pas en court-circuit. Pour la mettre au rebut, conformez-vous à la réglementation en vigueur. Lorsque vous remplacez la batterie, veillez à n'utiliser que les modèles cités dans la liste de pièces détachées adéquate. En effet, une batterie inappropriée risque de prendre feu ou d'exploser.



DANGER

La pile de sauvegarde contient du lithium. Elle présente des risques d'incendie, d'explosion ou de brûlures graves. Ne la rechargez pas, ne retirez pas son connecteur polarisé et ne la démontez pas. Ne l'exposez pas à une température supérieure à 100°C, ne la faites pas brûler et n'en exposez pas le contenu à l'eau. Mettez la pile au rebut conformément à la réglementation en vigueur. Une pile inappropriée risque de prendre feu ou d'exploser.



DANGER

Si le panneau d'affichage à cristaux liquides se brise et que vous recevez dans les yeux ou sur les mains une partie du fluide, rincez-les abondamment pendant au moins quinze minutes. Consultez un médecin si des symptômes persistent après le lavage.



DANGER

Afin d'éviter tout risque de choc électrique, ne retirez pas le cache en plastique protégeant la partie inférieure de la carte d'alimentation.



DANGER

Bien que le voltage des batteries principales soit peu élevé, le court-circuit ou la mise à la masse d'une batterie peut produire suffisamment de courant pour brûler des matériaux combustibles ou causer des brûlures corporelles graves.



DANGER

Si le remplacement à chaud n'est pas autorisé pour l'unité remplaçable sur site que vous remplacez, procédez comme suit avant de retirer l'unité : mettez l'ordinateur hors tension, débranchez tous les cordons d'alimentation des prises de courant, retirez le bloc de batterie et déconnectez tous les câbles d'interconnexion.

German



VORSICHT

Bevor nach einem FRU-Austausch der Computer wieder angeschlossen wird, muß sichergestellt werden, daß keine Schrauben, Federn oder andere Kleinteile fehlen oder im Gehäuse vergessen wurden. Der Computer muß geschüttelt und auf Klappergeräusche geprüft werden. Metallteile oder-splitter können Kurzschlüsse erzeugen.



VORSICHT

Die Bereitschaftsbatterie, die sich unter dem Diskettenlaufwerk befindet, kann geringe Mengen Nickel und Cadmium enthalten. Sie darf nur durch die Verkaufsstelle oder den IBM Kundendienst ausgetauscht werden. Sie darf nicht zerlegt, wiederaufgeladen, kurzgeschlossen, oder Feuer oder Wasser ausgesetzt werden. Die Batterie kann schwere Verbrennungen oder Verätzungen verursachen. Bei der Entsorgung die örtlichen Bestimmungen für Sondermüll beachten. Beim Ersetzen der Bereitschafts-oder Systembatterie nur Batterien des Typs verwenden, der in der Ersatzteilliste aufgeführt ist. Der Einsatz falscher Batterien kann zu Entzündung oder Explosion führen.



VORSICHT

Akkus enthalten geringe Mengen von Nickel. Sie dürfen nicht zerlegt, wiederaufgeladen, kurzgeschlossen, oder Feuer oder Wasser ausgesetzt werden. Bei der Entsorgung die örtlichen Bestimmungen für Sondermüll beachten. Beim Ersetzen der Batterie nur Batterien des Typs verwenden, der in der Ersatzteilliste aufgeführt ist. Der Einsatz falscher Batterien kann zu Entzündung oder Explosion führen.



VORSICHT

Die Systembatterie ist eine Lithiumbatterie. Sie kann sich entzünden, explodieren oder schwere Verbrennungen hervorrufen. Batterien dieses Typs dürfen nicht aufgeladen, zerlegt, über 100°C erhitzt oder verbrannt werden. Auch darf ihr Inhalt nicht mit Wasser in Verbindung gebracht oder der zur richtigen Polung angebrachte Verbindungsstecker entfernt werden. Bei der Entsorgung die örtlichen Bestimmungen für Sondermüll beachten. Beim Ersetzen der Batterie nur Batterien des Typs verwenden, der in der Ersatzteilliste aufgeführt ist. Der Einsatz falscher Batterien kann zu Entzündung oder Explosion führen.



VORSICHT

Die Leuchtstoffröhre im LCD-Bildschirm enthält Quecksilber. Bei der Entsorgung die örtlichen Bestimmungen für Sondermüll beachten. Der LCD-Bildschirm besteht aus Glas und kann zerbrechen, wenn er unsachgemäß behandelt wird oder der Computer auf den Boden fällt. Wenn der Bildschirm beschädigt ist und die darin befindliche Flüssigkeit in Kontakt mit Haut und Augen gerät, sollten die betroffenen Stellen mindestens 15 Minuten mit Wasser abgespült und bei Beschwerden anschließend ein Arzt aufgesucht werden.



VORSICHT

Aus Sicherheitsgründen die Kunststoffabdeckung, die den unteren Teil der Spannungswandlerplatine umgibt, nicht entfernen.



VORSICHT

Obwohl Hauptbatterien eine niedrige Spannung haben, können sie doch bei Kurzschluß oder Erdung genug Strom abgeben, um brennbare Materialien zu entzünden oder Verletzungen bei Personen hervorzurufen.



VORSICHT

Wenn ein Austausch der FRU bei laufendem Betrieb nicht erlaubt ist, gehen Sie beim Austausch der FRU wie folgt vor: Schalten Sie den Computer aus, ziehen Sie alle Netzkabel von den Netzsteckdosen ab, entfernen Sie den Akku und ziehen Sie alle miteinander verbundenen Kabel ab.

Hebrew



סכנה

לפני הפעלת המחשב לאחר החלפת FRU יש לוודא שכל הברגים, חקפצים, וחלקים קטנים אחרים נמצאים במקומם ואינם חופשיים לזוז בתוך המחשב. כדי לוודא זאת, יש לטלטל את המחשב ולחקש לבגליו קולות שקשוק. חלקי או שבבי מתכת עלולים לגרום לקצרים חשמליים.



סכנה

סוללות המתנה מסוימות מכילות כמות קטנה של ניקל וקדמיום. אין לפרק סוללת המתנה, לטעון אותה מחדש, להשליך אותה לאש או למים או לקצר אותה. יש לסלק את הסוללה כנדרש על ידי התקנות והחוקים המקומיים. יש להשתמש רק בסוללה המופיעה ברשימת החלקים המתאימה. שימוש בסוללה לא מתאימה עלול לגרום להצתה או התפוצצות של הסוללה.



סכנה

מארז הסוללה מכיל כמות קטנה של ניקל וקדמיום. אין לפרק את מארז הסוללה, להשליך אותו לאש או למים או לקצר אותו. יש לסלק את מארז הסוללה כנדרש על ידי התקנות והחוקים המקומיים. יש להשתמש רק בסוללה המופיעה ברשימת החלקים המתאימה בזמן החלפת מארז הסוללה. שימוש בסוללה לא מתאימה עלול לגרום להצתה או התפוצצות של הסוללה.



סכנה

סוללת הליתיום עלולה לגרום לשריפה, להתפוצצות או לכוויות קשות. אין לטעון אותה מחדש, לסלק את המחבר המקוטב שלה, לפרק אותה או לחמם אותה לטמפרטורה העולה על 100 מעלות צלזיוס. אין לשרוף את הסוללה ואין לחשוף את תוכן התא למים. יש לסלק את הסוללה כנדרש בתקנות ובחוקים המקומיים. יש להשתמש רק בסוללה המופיעה ברשימת החלקים המתאימים. שימוש בסוללה אחרת עלול לגרום לסכנת שריפה או התפוצצות.



סכנה

אם מסך הנביש חנוצלי (LCD) נשבר וחנוצל מתוך המסך בא במגע עם עיניים או ידיים, שטפו את האזורים הנגעיים מיד במים במשך 15 דקות לפחות. פנו לקבלת עזרה רפואית אם תסמינים הנובעים מחמגע עם חנוצל נמשכים לאחר חשטיפה.



סכנה

כדי למנוע התחשמלות, אין להסיר את מכסה הפלסטיק המגן על חלקו התחתון של הכרטיס ההפוך.



סכנה

אף שהסוללות הראשיות הן בעלות מתח נמוך, סוללה מקוצרת או מוארכת עלולה להפיק זרם מספיק לגרימת כוויות או להצתת חומרים דליקים.



סכנה

אלא אם כן מותרת יחלפה חמ"י של ה-FRU המוחלף, פעלו כדלחץ לפני חסרתו:
כבו את המחשב, נתקו את כל כבלי החשמל מחשקעים, הוציאו את מארז חסוללות ונתקו את כל חבילים
המחוברים.

Japanese



危険

FRUの交換後、ThinkPadの電源を入れる前に、ねじ、バネ、その他の小さな部品がすべて正しい位置にあり、またThinkPadの内部で緩んでいないことを確認してください。
これを確認するには、ThinkPadを振って、カチャカチャと音がしないか確かめま
す。金属部品や金属破片はショートの原因になることがあります。



危険

予備バッテリーの中には少量のニッケルとカドミウムが含まれているものがあり
ます。したがって、予備バッテリーの分解、再充電、火または水の中への投棄、
またはショートさせることは決して行わないでください。バッテリーを廃棄する
場合は地方自治体の条例に従ってください。適切なパーツ・リストにあるバッテ
リーだけを使用してください。誤ったバッテリーを使用すると、バッテリーが発
火したり、爆発したりすることがあります。



危険

バッテリー・パックには少量のニッケルが含まれています。バッテリー・パック
を分解したり、火または水の中に投げ込んだり、ショートさせないでください。
バッテリー・パックの廃棄にあたっては、地方自治体の条例または規則に従って
ください。バッテリー・パックを交換するときは、適切なパーツ・リストにある
バッテリーだけを使用してください。誤ったバッテリーを使用すると、バッテ
リーが発火したり、爆発したりすることがあります。



危険

リチウム・バッテリーは、火災、爆発、または重症のやけどを引き起こすことが
あります。バックアップ・バッテリーの充電、その極性コネクタの取り外し、
バッテリー本体の分解、
100 °C (212 °F) 以上への加熱、焼却、電池の中身を水に浸すことはしないでくださ
い。バッテリーを廃棄する場合は地方自治体の条例に従ってください。適切な
パーツ・リストにあるバッテリーだけを使用してください。誤ったバッテリーを
使用すると、バッテリーが発火したり、爆発したりすることがあります。



危険

LCD が破損し、LCD 中の液体が目に入ったり、手に触れたりした場合は、液
体が触れた部分を少なくとも 15 分間洗い流してください。洗い流した後に、液体
によって何らかの症状が現れた場合は、医師の治療を受けてください。



危険

感電を防ぐため、インバーター・カードの下部を保護しているプラスチック・カバーを外さないでください。



危険

メイン・バッテリーの電圧は低くても、ショートしたり、接地したバッテリーが、作業者にやけどを負わせたり、可燃物を燃やすだけの電流を発生させる場合があります。



危険

交換しようとしている FRU がホット・スワップに対応していない場合、それを取り外す前に、コンピューターの電源をオフにし、すべての電源コードをコンセントから抜き、バッテリー・パックを取り外して、相互接続しているケーブルをすべて切り離してください。

Korean



위험

FRU를 교체하고 나서 컴퓨터 전원을 켜기 전에 모든 나사, 스프링 및 기타 작은 부품들이 올바른 위치에 있는지, 컴퓨터 내부에 단단하게 연결되어 있는지 확인하십시오. 컴퓨터를 흔들어 달걀거리는 소리가 나지 않는지 확인하십시오. 금속 부품 또는 금속 조각은 누전을 일으킬 수 있습니다.



위험

일부 보조 배터리에는 소량의 니켈 및 카트륨이 포함되어 있습니다. 보조 배터리를 분해하거나, 다시 충전하거나, 불 또는 물에 던지거나, 단락시키지 마십시오. 배터리 팩을 폐기할 때에는 해당 지역의 법률 규정을 따르십시오. 배터리 팩을 교체할 때에는 올바른 배터리만 사용하십시오. 올바른지 않은 배터리를 사용하면 배터리가 발화되거나 폭발할 수 있습니다.



위험

배터리 팩에는 소량의 니켈이 포함되어 있습니다. 배터리 팩을 분해하거나, 불 또는 물에 던지거나, 단락시키지 마십시오. 배터리 팩을 폐기할 때에는 해당 지역의 법률 규정을 따르십시오. 배터리 팩을 교체할 때에는 올바른 배터리만 사용하십시오. 올바른지 않은 배터리를 사용하면 배터리가 발화되거나 폭발할 수 있습니다.



위험

리튬 배터리는 화재, 폭발 또는 심각한 화상을 일으킬 수 있습니다. 리튬 배터리를 다시 충전하거나, 극성 커넥터를 제거하거나, 분해하거나, 100C(212F) 이상으로 가열하거나, 소각하거나, 전지 내용물을 물에 노출시키지 마십시오. 배터리를 폐기할 때에는 해당 지역을 법률 규정을 따르십시오. 올바른 배터리만 사용하십시오. 올바른지 않은 배터리를 사용하면 배터리가 발화되거나 폭발할 수 있습니다.



위험

LCD가 파손되어 LCD 내부의 액체가 눈에 들어가거나 손에 묻으면 즉시 깨끗한 물로 15분 이상 닦아 내십시오. 씻은 후에 조금이라도 이상을 느끼면 즉시 병원에 가서 의사의 진찰을 받아야 합니다.



위험

전기적 위험을 방지하려면 인버터 카드의 아래 부분을 보호하는 플라스틱 덮개를 제거하지 마십시오.



위험

기본 배터리의 전압은 낮지만, 단락되거나 접지된 배터리는 화상을 입히기에 충분한 전류와 가연성 물질을 발생시킬 수 있습니다.



위험

FRU 교체 시 Hot Swap이 지원되지 않는 경우, FRU를 제거하기 전에 컴퓨터의 전원을 끄고, 전기 콘센트에서 전원 코드를 분리하고, 배터리를 제거한 후, 연결된 모든 케이블을 분리하십시오.

Spanish



PELIGRO

Antes de encender el sistema despues de sustituir una FRU, compruebe que todos los tornillos, muelles y demás piezas pequeñas se encuentran en su sitio y no se encuentran sueltas dentro del sistema. Compruébelo agitando el sistema y escuchando los posibles ruidos que provocarían. Las piezas metálicas pueden causar cortocircuitos eléctricos.



PELIGRO

Algunas baterías de reserva contienen una pequeña cantidad de níquel y cadmio. No las desmonte, ni recargue, ni las eche al fuego o al agua ni las cortocircuite. Deséchelas tal como dispone la normativa local. Utilice sólo baterías que se encuentren en la lista de piezas. La utilización de una batería no apropiada puede provocar la ignición o explosión de la misma.



PELIGRO

Las baterías contienen pequeñas cantidades de níquel. No las desmonte, ni recargue, ni las eche al fuego o al agua ni las cortocircuite. Deséchelas tal como dispone la normativa local. Utilice sólo baterías que se encuentren en la lista de piezas al sustituir la batería. La utilización de una batería no apropiada puede provocar la ignición o explosión de la misma.



PELIGRO

La batería de repuesto es una batería de litio y puede provocar incendios, explosiones o quemaduras graves. No la recargue, ni quite el conector polarizado, ni la desmonte, ni caliente por encima de los 100°C (212°F), ni la incinere ni exponga el contenido de sus celdas al agua. Deséchela tal como dispone la normativa local.



PELIGRO

Si la LCD se rompe y el fluido de su interior entra en contacto con sus ojos o sus manos, lave inmediatamente las áreas afectadas con agua durante 15 minutos como mínimo. Obtenga atención medica si se presenta algún síntoma del fluido despues de lavarse.



PELIGRO

Para evitar descargas, no quite la cubierta de plástico que rodea la parte baja de la tarjeta invertida.



PELIGRO

Aunque las baterías principales tienen un voltaje bajo, una batería cortocircuitada o con contacto a tierra puede producir la corriente suficiente como para quemar material combustible o provocar quemaduras en el personal.



PELIGRO

Salvo que se permita el intercambio en caliente para la unidad sustituible localmente, realice lo siguiente antes de extraerla: apague el sistema, desconecte todos los cables de alimentación de las tomas de alimentación eléctrica, extraiga la batería y desconecte los cables de interconexión.

Traditional Chinese



危險

完成 FRU 更換之後，在開啟電腦的電源之前，請確定所有螺絲、彈簧及其他小零件都已歸位，沒有遺留在電腦內部。
若要確認這一點，請搖晃電腦，聽聽看是否有卡嗒的聲響。
金屬零件或儀錶的火花會造成電線短路。



危險

部分備用電池含有微量的鎳和鎘。請勿拆開備用電池、再充電、丟入火或水中，或使其形成短路。請按照當地法令或規定來棄置電池。
僅限使用零件清單中的電池。使用不適當的電池會導致電池起火或爆炸。



危險

電池套件含有微量的鎳。請勿拆開電池套件、丟入火或水中，或使其形成短路。請按照當地法令或規定來棄置電池套件。

更換電池套件時，僅限使用零件清單中的電池。使用不適當的電池會導致電池起火或爆炸。



危險

鋰電池會導致起火、爆炸或嚴重燒傷。請勿再充電、拔除其電極接頭、拆開、加熱超過 **100°C (212°F)**、焚燒，或讓電池組成物浸到水。請按照當地法令或規定來棄置電池。

僅限使用零件清單中的電池。使用不適當的電池會導致電池起火或爆炸。



危險

如果 LCD 破裂導致 LCD 流出的液體沾到您的眼睛或手，請立即以清水沖洗沾染部位至少 15 分鐘。如果在清洗後出現該液體所造成的任何症狀，請就醫治療。



危險

為避免電擊，請勿拆下轉換卡下面的塑膠護蓋。



危險

雖然主電池的電壓很低，但短路或接地電池所產生的電流，仍足以使人燒傷或使可燃物質起火。



危險

除非 FRU 允許以熱抽換來替換，否則請依下列方式將其移除：將電腦關機，拔除插座上所有電源線，移除電池包，並拔開任何交互連接的線材。

Chapter 2. Diagnostics and troubleshooting

This chapter introduces several diagnostics applications to help you identify and solve the problems of your computer. If you still need help after running the applications, you can call Lenovo Customer Support Center.

Diagnostics applications

The following table lists diagnostics applications available on your computer, their running environments, and brief introductions to each application.

Table 1. Diagnostics applications

Diagnostics application	Running environment	Brief introduction
"Hardware scan in Vantage" on page 17*	Run in the operating system.	The Vantage application is preinstalled on the computer. Hardware scan in the Vantage application is an effective hardware testing tool to help you identify the hardware problems of your computer.
"UEFI diagnostics application" on page 18*	Run in the UEFI BIOS.	A UEFI diagnostics application is preinstalled on the computer. This application enables you to view system information and test some hardware components in your computer, especially when you cannot start up the operating system.
"Advanced diagnostics application (Windows version)" on page 18 "Advanced diagnostics application (bootable versions for Linux/UEFI)" on page 18	Run in the operating system or boot from USB (Need download).	Advanced diagnostics applications help you test a wider scope of hardware components in your computer that cannot be covered by hardware scan in the Vantage application or the UEFI diagnostics application.

* for selected models

Important: Be extremely careful during such writing operations as copying, saving, or formatting. Drives in the computer that you are servicing sequence might have been altered. If you select an incorrect drive, data or programs might be overwritten.

Hardware scan in Vantage

To run the hardware scan in Vantage, do the following:

- Step 1. Launch the Vantage app.
- Step 2. Click **Hardware scan** or **Support Services → Hardware scan**.
- Step 3. Choose one of the following ways to run the hardware scan:

Click **Refresh Modules** and check the list of hardware components currently available in the computer. Select **QUICK SCAN** to test all the hardware components detected.

Select **CUSTOMIZE** to choose one or several hardware components to be tested.

- Step 4. If any hardware failure is detected, the result varies depending on the warranty status and varies by country or region. Follow the on-screen instructions to resolve the issue.

UEFI diagnostics application

UEFI Diagnostics is consistently available as a boot option on Lenovo machines. To access the tool, follow these instructions:

- For ThinkPad, Thinkbook, and SMB systems, press the **F10** key during the boot process.
- For IdeaPad systems, access the **Novo button menu**, then select **Lenovo UEFI Diagnostics** from the menu. The application will start automatically.

The following table displays the items on the main screen of the UEFI diagnostics application. Depending on the model, the items might differ slightly.

Table 2. Items on the main screen of the UEFI diagnostics application

Category	Items
Tests	• Storage • Memory • CPU • Display • Motherboard • Touch
Tools	• System Information • Bad Block Recovery • Smart Information

Prepare a USB flash drive formatted in FAT32. After the test is executed, select **View Log → Save Log**. The test log is saved in the USB flash drive. You can view the log to find possible solutions or send the log to Lenovo for helps.

Advanced diagnostics application (Windows version)

To use the advanced diagnostics application (Windows version), do the following:

- Step 1. Go to <https://support.lenovo.com/solutions/ht506581>.
- Step 2. Select a Windows package that fits your scenario for download.
- Step 3. Double-click the downloaded file and complete the installation.
- Step 4. Launch the app and follow the on-screen instructions for diagnostics.

After the test is completed, select **Export Log** to save the diagnostic result. You can view the log to find possible solutions or send the log to Lenovo for helps.

Advanced diagnostics application (bootable versions for Linux/UEFI)

To use the advanced diagnostics application (bootable versions for Linux/UEFI), do the following:

- Step 1. Prepare a USB flash drive larger than 2 GB and make a backup of the content in the USB flash drive. (During the following diagnosing process, the content in the USB flash drive content will be erased.)

Note: During the following diagnostic process, the content on the USB flash drive will be erased.
- Step 2. Go to <https://support.lenovo.com/solutions/bootableusb>.
- Step 3. Follow the on-screen instructions to create a bootable USB and run the application from the bootable USB.

After the test is executed, select **View Log → Export Log**. The test log is saved in the USB flash drive. You can view the log to find possible solutions or send the log to Lenovo for help.

Call Lenovo

If you have tried to correct the problem yourself and still need help, you can call Lenovo Customer Support Center.

Before you contact Lenovo

Record product information and problem details before you contact Lenovo.

Product information	Problem symptoms and details
• Product name • Machine type and serial number	• What is the problem? Is it continuous or intermittent? • Any error message or error code? • What operating system are you using? Which version? • Which software applications were running at the time of the problem? • Can the problem be reproduced? If so, how?

Note: The product name and serial number can usually be found on the bottom of the computer, either printed on a label or etched on the cover.

Lenovo Customer Support Center

During the warranty period, you can call Lenovo Customer Support Center for help.

Telephone numbers

For a list of the Lenovo Support phone numbers for your country or region, go to <https://pcsupport.lenovo.com/supportphonenumberlist>.

Note: Phone numbers are subject to change without notice. If the number for your country or region is not provided, contact your Lenovo reseller or Lenovo marketing representative.

Services available during the warranty period

- Problem determination - Trained personnel are available to assist you with determining if you have a hardware problem and deciding what action is necessary to fix the problem.
- Lenovo hardware repair - If the problem is determined to be caused by Lenovo hardware under warranty, trained service personnel are available to provide the applicable level of service.
- Engineering change management - Occasionally, there might be changes that are required after a product has been sold. Lenovo or your reseller, if authorized by Lenovo, will make selected Engineering Changes (ECs) that apply to your hardware available.

Services not covered

- Replacement or use of parts not manufactured for or by Lenovo or non-warranted parts
- Identification of software problem sources
- Configuration of UEFI/BIOS as part of an installation or upgrade
- Changes, modifications, or upgrades to device drivers
- Installation and maintenance of network operating systems (NOS)
- Installation and maintenance of programs

For the terms and conditions of the Lenovo Limited Warranty that apply to your Lenovo hardware product, see "Warranty information" in the *Safety and Warranty Guide* that comes with your computer.

Nonwarranted items and activities

During the warranty period, the customer may be responsible for repair costs if the computer damage was caused by misuse, accident, modification, unsuitable physical or operating environment, or improper maintenance by the customer. Following is a list of some common items that are not covered under warranty and some symptoms that might indicate that the system was subjected to stress beyond normal use.

Items not covered by warranty

- LCD panel cracked from the application of excessive force or from being dropped
- Scratched (cosmetic) parts
- Distortion, deformation, or discoloration of the cosmetic parts
- Plastic parts, latches, pins, or connectors that have been cracked or broken by excessive force
- Damage caused by liquid spilled into the system
- Damage caused by the improper insertion of a personal-computer card (PC card) or the installation of an incompatible card
- Improper disc insertion or use of an external optical drive
- Fuses blown by attachment of a non-supported device
- Forgotten computer password (making the computer unusable)
- Sticky keys caused by spilling a liquid onto the keyboard
- Use of an incorrect ac power adapter on laptop products

Symptoms that might indicate damage caused by non-warranted activities

- Missing parts might be a symptom of improper service or modification.
- Check for obvious damage to a hard disk drive. If the spindle of a hard disk drive becomes noisy, the hard disk drive might have been dropped or subject to excessive force.

Chapter 3. Parts, screws, and tools

Parts

Before proceeding with part replacement, get to know part type definition, learn to look up a part on the Lenovo Support Web site, and gain an overview of all CRUs/FRUs in this computer through the exploded view.

Part type definition

Your computer contains the following types of “Customer Replaceable Unit” (CRU)s and “Field Replaceable Unit” (FRU)s:

- **Self-service CRUs:** Refer to parts that can be replaced easily by customer themselves or by trained service technicians at an additional cost.
- **Optional-service CRUs:** Refer to parts that can be replaced by customers with a greater skill level. Trained service technicians can also provide service to replace the parts under the type of warranty designated for the customer’s product.
- **FRUs:** Refer to parts that are more complicated to replace and it is recommended that these parts should be replaced by trained service technicians. If customers elect to replace the FRU by themselves, we recommend that you ensure the correct instructions are carefully followed.

Important notes:

- **CRU statement for customers:**
 - You can resolve some problems with your product by replacing a CRU. For self-service CRUs, installation is your responsibility. For optional-service CRUs, you can either install the CRU yourself or you can request that a Service Provider install the CRU according to the warranty service for your product.
 - If you intend on installing the CRU, Lenovo will ship the CRU to you. CRU information and replacement instructions are shipped with your product and are available from Lenovo at any time upon request.
 - You can find a list of CRUs for your product in this *Hardware Maintenance Manual*. To find this manual, go to <https://support.lenovo.com> and search by product.
- **CRU/FRU statement:**
 - **Replace a CRU/FRU only with another CRU/FRU of the correct model.** When you replace a CRU/FRU, make sure that the model of the machine and the CRU/FRU part number are correct.
 - **A CRU/FRU should not be replaced because of a single unreproducible failure.** Single failures can occur for a variety of reasons that have nothing to do with a hardware defect, such as cosmic radiation, electrostatic discharge, or software errors. Consider replacing a CRU/FRU only when a problem recurs. If you suspect that a CRU/FRU is defective, clear the error log and run the test again. If the error does not recur, do not replace the CRU/FRU.
 - **Be careful not to replace a nondefective CRU/FRU.**
 - When you return a CRU/FRU, you must include the following information in the parts exchange form or parts return form that you attach to it:
 1. Name and phone number of service technician
 2. Date of service
 3. Date on which the machine failed
 4. Date of purchase
 5. Failure symptoms, error codes appearing on the display, and beep symptoms

6. Procedure index and page number in which the failing CRU/FRU was detected
7. Failing CRU/FRU name and part number
8. Machine type, model number, and serial number
9. Customer's name and address

Look up a part


1. For more detailed CRU/FRU information, including part numbers, descriptions, and substitution part numbers, go to <https://support.lenovo.com/partslookup>.
2. Type the product name, the machine type or the serial number in the corresponding field to get a general CRU/FRU list.

Exploded view and part list (for 14-inch models)

By the exploded view and the part list, you can find the images, names, and types of all the CRU/FRUs of your computer.

Exploded view

Part list



Self-service CRUs:

- a** Power cord*
- b** ac power adapter*
- c** Screw kit

FRUs:

- 1** "Display cover" on page 60
- 2** "IR rubber" on page 56
- 3** "Microphone rubbers" on page 55
- 4** "Camera shutter" on page 57
- 5** "Camera board" on page 59
- 6** "Sensor board" on page 50
- 7** Stretch-release tapes (Right, left, top, and bottom)
- 8** "Display panel" on page 51
- 9** MB acetate tape
- 10** "Strip cover" on page 50
- 11** "I/O board" on page 46
- 12** "Upper case" on page 65
- 13** PMIC board*
- 14** PMIC cable*
- 15** "2242 trans cover" on page 37
- 16** I/O board cable
- 17** "M.2 solid-state drive" on page 36
- 18** Wi-Fi card mylar
- 19** "Wi-Fi card" on page 38
- 20** "Fan" on page 46
- 21** "Battery pack" on page 36
- 22** "Lower case" on page 31
- 23** "Speakers" on page 45
- 24** "Heat sink" on page 41
- 25** Memory shielding
- 26** System board
- 27** "Memory" on page 40
- 28** "Type-C bracket" on page 40
- 29** EDP cable
- 30** "Hinges" on page 55
- 31** "Camera cable" on page 58

* for selected models

Exploded view and part list (for 15-inch models)

By the exploded view and the part list, you can find the images, names, and types of all the CRU/FRUs of your computer.

Exploded view


Part list

Self-service CRUs:

- a** Power cord*
- b** ac power adapter*
- c** Screw kit

FRUs:

- 1** “Display cover” on page 97
- 2** “Camera shutter” on page 92
- 3** “IR rubber” on page 91
- 4** “Microphone rubbers” on page 91
- 5** “Sensor board” on page 87
- 6** Hinge plastics
- 7** “Hinges” on page 93
- 8** “Camera cable” on page 95
- 9** “Strip cover” on page 86
- 10** “Upper case” on page 103
- 11** PMIC cable*
- 12** PMIC board*
- 13** “I/O board” on page 99
- 14** System board
- 15** “Type-C bracket” on page 98
- 16** I/O board cable
- 17** “Heat sink” on page 79
- 18** “Fan” on page 78
- 19** Battery pack cable*
- 20** 84 Wh “Battery pack” on page 71*
- 21** 65 Wh “Battery pack” on page 71*
- 22** “Lower case” on page 66
- 23** “2242 trans cover” on page 74
- 24** “Speakers” on page 82
- 25** “Memory” on page 77
- 26** Memory shielding
- 27** “M.2 solid-state drive” on page 73
- 28** “Wi-Fi card” on page 75
- 29** Wi-Fi card mylar
- 30** MB acetate tape
- 31** EDP cable
- 32** “Display panel” on page 87
- 33** Stretch-release tapes (Right, left, top, and bottom)
- 34** “Camera board” on page 96




* for selected models

Screws

This section provides the screw list of this computer and the screw notices you need to know before hardware replacement.

Screw list

The following table includes screw specifications, torque information, and screw colors of this product.



The number after the letter L refers to the length of the screw shank measured from under the head to the tip of the screw. The number after the letter M refers to the width of the screw shank measured across the outermost points in a metric screw.

Table 3. Screw list of 14-inch models

Thread (mm)	Length (mm)	Torque (kgf.cm)	Color
M1.6	L1.6	1.25 ± 0.15	Black
M1.6	L3.0	1.25 ± 0.15	Silver
M2	L2.2	1.85 ± 0.15	Silver
M2	L2.3	1.85 ± 0.15	Black
M2	L3.5	1.85 ± 0.15	Black
M2	L4.5	1.85 ± 0.15	Depending on the product
M2.5	L5.5	3.0 ± 0.3	Black

Table 4. Screw list of 15-inch models

Thread (mm)	Length (mm)	Torque (kgf.cm)	Color
M1.6	L1.6	0.9 ± 0.1	Black
M1.6	L1.8	1.25 ± 0.15	Black
M1.6	L3.0	1.25 ± 0.15	Silver
M2	L2.2	1.85 ± 0.15	Silver
M2	L2.3	1.5 ± 0.1	Black
M2	L3.5	1.85 ± 0.15	Black
M2	L4.5	1.2 ± 0.1	Depending on the product
M2	L5.0	1.85 ± 0.15	Black
M2	L8.0	1.2 ± 0.1	Depending on the product

You can refer to the following table to choose a properly matched screwdriver.

Notes:

-  The Phillips head screw has a cross-shaped slot in the screw head.
-  The Torx head screw has a six-pointed star in the screw head.

Table 5. Choose a properly matched screwdriver

Screw head type	Thread (mm)	Screwdriver type
Phillips head	< M1.2	PH00
Phillips head	M1.6 — M2	PH0 or PH1
Phillips head	> M2	PH1
Torx head	M2	T5

Screw notices

Do the following when you service the computer:

- Carefully retain and reuse all screws.
- Keep the screw kit in your tool bag. For the part number of the screw kit, go to: <https://support.lenovo.com/partslookup>.
- Use the correct screw as shown in the CRU/FRU replacement procedures.
- Turn the screws in the direction as given by the arrow in the CRU/FRU replacement illustration.
- If you have a torque screwdriver, tighten all screws firmly to the torque specified in the screw information table for each step.
- Ensure torque screwdrivers are calibrated correctly following country specifications.


Loose screws can cause a reliability problem. In your computer, this problem is addressed with special nylon-coated screws that have the following characteristics:

- They maintain tight connections.
- They do not easily come loose, even with shock or vibration.
- They are harder to tighten.

Tighten screws as follows:


- **Plastic to plastic**

Turn an additional angle of 90 degrees after the screw head touches the surface of the plastic part.



- **Logic card to plastic**

Turn an additional angle of 180 degrees after the screw head touches the surface of the logic card.



Service tools

The following table lists all tools for servicing Lenovo products. Tools required to service a part are listed in the specific part disassembly topic. Prepare them before you service the product.

Table 6. Service tools

No.	Reference image	Tool name	Specification	Tool type
1		Screwdriver set	- PH0, PH00, PH1, PH2 - T5, T15, T20, T30 Note: Use a screwdriver with the shank length greater than 6 inches for Desktop, Workstation, and Smart device product.	Common tool
2		Pry tool	N/A	Common tool
3		Tweezers	- Conductive - Isolated	Common tool
4		Suction cup	N/A	Common tool
5		Hexagonal socket	- For VGA: H5 mm or H4.8 mm - For Tiny antenna: H8 mm	Common tool
6		Adjustable torque screwdriver	0.2 Nm to 4.0 Nm, Threadripper CPU, CAMM, etc	Common tool
7		ESD mat	N/A	Common tool

Table 6. Service tools (continued)



No.	Reference image	Tool name	Specification	Tool type
8		USB flash drive	For Golden Key, Chrome Reloads, AutoPilot, etc	Common tool
9		USB-C to USB-A converter	N/A	Common tool
10		Thermal pad	Variety of thickness, most common 0.5mm thickness pad under the component	Consumable tool
11		Thermal interface materials	N/A	Consumable tool
12		Acetate tape	N/A	Consumable tool
13		Polyimide tape	N/A	Consumable tool
14		Mylar tape	N/A	Consumable tool
15		Electrical tape	N/A	Consumable tool
16		Double-sided tape	N/A	Consumable tool

Table 6. Service tools (continued)

No.	Reference image	Tool name	Specification	Tool type
17		Conductive tape	N/A	Consumable tool
18		Eraser	N/A	Consumable tool
19		Cleaning wipes	N/A	Consumable tool
20		Touchpad jig (this might come with touchpad)	N/A	Consumable tool
21		Heat gun	N/A	Special tool
22		Brown brush	25 mm to 35 mm wide	Special tool
23		Contact cleaner spray	WD-40 Contact cleaner for battery connector	Special tool
24		Hexagonal socket	H17 mm	Special tool

Chapter 4. Hardware replacement (for 14-inch models)

This chapter provides instructions on how to remove and install the hardware components of your computer.

General guidelines



Before removing any FRU or CRU, shut down the computer, unplug all power cords from electrical outlets, and wait about ten minutes to let the computer cool down.

When removing or replacing a CRU/FRU, ensure that you observe the following general guidelines:

1. Before replacing any CRU/FRU, ensure that you have read [Generic Safety and Compliance Notices](#).
2. Begin by removing any CRUs/FRUs that have to be removed before replacing the failing CRU/FRU. Any such CRUs/FRUs are listed at the beginning of each CRU/FRU replacement procedure. Remove them in the order in which they are listed.
3. Follow the correct sequence in the steps for removing a CRU/FRU, as shown in the illustrations by the numbers in square callouts.
4. When removing a CRU/FRU, move it in the direction as shown by the arrow in the illustration.

Attention:

- After replacing a CRU/FRU, do not turn on the computer until you have ensured that all screws, springs, and other small parts are in place and none are loose inside the computer. Verify this by shaking the computer gently and listening for rattling sounds. Metallic parts or metal flakes can cause electrical short circuits.
- The system board is sensitive to and can be damaged by ESD. Before touching it, establish personal grounding by touching a ground point with one hand or by using an ESD strap (P/N 6405959).

Lower case

Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 31.

Step 1. Place the computer upside down on a flat surface.

Step 2. Remove four or five screws. Then, pry up the latches and remove the lower case.




Figure 1. Remove four screws and the lower case (for selected models)

Table 7. Four screws used to secure the lower case (for selected models)

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2	4.5	1.85 ± 0.15	4




Figure 2. Remove five screws and the lower case (for selected models)

Table 8. Five screws used to secure the lower case (for selected models)

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2	4.5	1.85 ± 0.15	5

Step 3. Install the lower case in reverse order.

Label locations

When replacing the lower case or the upper case, reapply all labels that come with the replacement case. If some original labels are not included with the replacement case, peel them off from the original case and paste them on the replacement case.

Label locations on the upper case (with a palmrest label)




Figure 3. Label layout on the upper case (with a palmrest label)

Labels attached to the upper case are country/region specific. Make sure to apply the appropriate labels to the replacement upper case.

Table 9. All upper case labels (with a palmrest label)

Label	Label description	Applied country/region	Label dimensions
1	Palmrest label	All	18 mm × 75 mm
2	QR label	Non-EAA countries or regions	17 mm × 26.1 mm
3	AMD RADEON label	All	19.53 mm × 16.51 mm
	GEFORCE RTX label		18 mm × 18 mm
4	Intel label	All	18 mm × 22.25 mm
	AMD RYZEN label		19.53 mm × 16.51 mm

Label locations on the upper case (no palmrest label)




Figure 4. Label layout on the upper case (no palmrest label)

Labels attached to the upper case are country/region specific. Make sure to apply the appropriate labels to the replacement upper case.

Table 10. All upper case labels (no palmrest label)

Label	Label description	Applied country/region	Label dimensions
1	AMD RADEON label	All	19.53 mm × 16.51 mm
	GEFORCE RTX label		18 mm × 18 mm
2	Intel label	All	18 mm × 22.25 mm
	AMD RYZEN label		19.53 mm × 16.51 mm
3	QR label	Non-EAA countries or regions	17 mm × 26.1 mm

Label locations on the back side of the lower case




Figure 5. Label layout on the back side of the lower case

Table 11. All lower case labels (for green or gray cases)

Label	Label description	Applied country/region	Label dimensions
1	Laser etched rating label (for AMD models)	All	100 mm × 30 mm
	POD rating label		
2	Country/region label	Belarus (Belarus label)	40 mm × 8 mm
		Brazil (WL&BT label)	16.5 mm × 15 mm
		Canada (USA warning label)	120 mm × 20 mm
		Israel, USA, Canada, Taiwan, Argentina (WL label)	32 mm × 10 mm
		Japan (WL&BT label)	52 mm × 10 mm
		Korea (KR KCC label)	50 mm × 43 mm
		Malaysia, Indonesia (WL label)	15 mm × 10 mm
		Malaysia (Malaysia MCMC label)	8 mm × 8 mm
		South Africa (WL label)	20 mm × 10 mm
		Taiwan (TW Caution label)	70 mm × 10 mm
		Vietnam (Energy label)	10 mm × 9 mm
3	CO2 offset label	All	18 mm × 18 mm
4	OS label	All	16.1 mm × 22.5 mm
5	QR label	EAA countries or regions	17 mm × 26.1 mm
6	Transparent raised label	EAA countries or regions	17 mm × 17 mm

Note: Depending on the country/region where the computer is purchased, the upper case and the lower case may include one or more of the above listed labels. For the laser etched label, print the label and apply it to the replacement case according to the label location illustrated above. The artworks for the laser etched labels are country/region specific and can be found in Appendix A “Artworks for laser etched labels (IdeaPad 5 2-in-1 14AGP11)” on page 104 and Appendix B “Artworks for laser etched labels (IdeaPad 5 2-in-1 14AHP11)” on page 107.

Battery pack

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 31.
- Make sure the following FRUs (or CRUs) have been removed.

“Lower case” on page 31

Step 1. Disconnect the battery pack cable from the system board.

Attention: Use your fingernails to pull the connector to unplug it. Do not pull the cable.

Step 2. Remove two screws. Then, remove the battery pack.




Figure 6. Remove the battery pack

Table 12. Screws used to secure the 84 Wh battery pack

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2	3.5	1.85 ± 0.15	2

Step 3. Install the battery pack in reverse order.

M.2 solid-state drive

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 31.
- Make sure the following FRUs (or CRUs) have been removed.

“Lower case” on page 31

Step 1. Disconnect the battery pack cable from the system board. Remove one screw. Then, remove the solid-state drive by pulling it away from the slot.

Attention: Use your fingernail to pull the connector to unplug it. Do not pull the cable.




Figure 7. Remove the solid-state drive

Table 13. Screws used to secure the solid-state drive

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2	3.5	1.85 ± 0.15	1

Note: The product supports up to two solid-state drives. Remove both, if necessary.

Step 2. Install the M.2 solid-state drive in reverse order.

2242 trans cover

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 31.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Lower case” on page 31

Step 1. Remove one screw. Then, pry up the 2242 trans cover.




Figure 8. Remove the 2242 trans cover

Table 14. Screws used to secure the 2242 trans cover

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2	3.5	1.85 ± 0.15	1

Step 2. Install the 2242 trans cover in reverse order.

Wi-Fi card

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 31.
- Make sure the following FRUs (or CRUs) have been removed.

“Lower case” on page 66

Step 1. Disconnect the battery pack cable from the system board. Then, remove the Wi-Fi card mylar.

Attention: Use your fingernails to pull the connector to unplug it. Do not pull the cable.




Figure 9. Remove the Wi-Fi card mylar

- Step 2. Detach the main and auxiliary antenna cable connectors. Remove one screw. Then, remove the Wi-Fi card by pulling it away from the slot.




Figure 10. Remove the Wi-Fi card

Table 15. Screw used to secure the Wi-Fi card

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2	3.5	1.85 ± 0.15	1

- Step 3. Install the Wi-Fi card in reverse order.

Type-C bracket

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 31.
- Make sure the following FRUs (or CRUs) have been removed.

“Lower case” on page 31

Step 1. Disconnect the battery pack cable from the system board.

Attention: Use your fingernails to pull the connector to unplug it. Do not pull the cable.

Step 2. Remove three screws. Then, remove the Type-C bracket.




Figure 11. Remove the Type-C bracket

Table 16. Screws used to secure the Type-C bracket

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M1.6	3	1.85 ± 0.15	3

Step 3. Install the Type-C bracket in reverse order.

Memory

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 31.
- Make sure the following FRUs (or CRUs) have been removed.

“Lower case” on page 31

Step 1. Disconnect the battery pack cable from the system board. Peel off the tapes. Then, remove the memory shielding.

Attention: Use your fingernails to pull the connector to unplug it. Do not pull the cable.




Figure 12. Remove the memory shielding

Step 2. Remove the memory module.




Figure 13. Remove the memory module

Step 3. Install the memory module and the memory shielding in reverse order.

Heat sink

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 31.
- Make sure the following FRUs (or CRUs) have been removed.

“Lower case” on page 31

Step 1. Disconnect the battery pack cable from the system board.

Attention: Use your fingernails to pull the connector to unplug it. Do not pull the cable.

Step 2. Peel off the tape. Remove three or four screws in the alphabetical order. Then, remove the heat sink.




Figure 14. Remove the heat sink (for AMD models)

Table 17. Screw used to secure the heat sink (for AMD models)

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2	2.2	1.85 ± 0.15	3




Figure 15. Remove the heat sink (for Intel models)

Table 18. Screw used to secure the heat sink (for Intel models)

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2	2.2	1.85 ± 0.15	4

Step 3. Install the heat sink in reverse order.

Handling thermal interface materials

Thermal interface materials are typically applied between a heat sink and a CPU (and/or GPU) die to enhance the heat transfer capability of the heat sink. If thermal interface materials are exposed during computer servicing, such as when replacing the heat sink or system board, it is important to handle the thermal interface materials properly.

- You need to completely remove the old thermal interface materials from the CPU and/or GPU die.
- You need to apply new thermal interface materials onto the heat sink according to the type, quantity, and application areas specified in this publication.

Related topics

“Heat sink” on page 41

“System board (with I/O board cable, PMIC cable, and PMIC board)” on page 61

Type, quantity, and areas of thermal interface materials application on the heat sink

The table and figure below provide information on the type and quantity of thermal interface materials, as well as the specific areas on the heat sink where these materials should be applied.

Models	Area	Type	Quantity
AMD models	a	PTM7958sp	0.15 g–0.2 g, 17.96 mm × 13.97 mm × 0.2 mm
Intel models	a	PTM7958sp	0.2 g–0.25 g, 20.0 mm × 13.5 mm × 0.2 mm




Figure 16. Areas on the heat sink where thermal interface materials should be applied (for AMD models)



Figure 17. Areas on the heat sink where thermal interface materials should be applied (for Intel models)

Areas on the system board where thermal interface materials are applied

The following figure shows the areas on the system board where thermal interface materials are applied.




Figure 18. Areas on the system board where thermal interface materials are applied (for AMD models)




Figure 19. Areas on the system board where thermal interface materials are applied (for Intel models)

Speakers

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 31.
- Make sure the following FRUs (or CRUs) have been removed.

“Lower case” on page 31

“Battery pack” on page 36

Step 1. Disconnect the speakers from the system board. Release the left speaker cable from the guide. Remove five screws. Then, remove the speakers from the upper case.




Figure 20. Remove the speakers

Table 19. Screws used to secure the hinge

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M1.6	1.6	1.25 ± 0.15	5

Step 2. Install the speakers in reverse order.

Fan

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 31.
- Make sure the following FRUs (or CRUs) have been removed.

“Lower case” on page 31

“Battery pack” on page 36

Step 1. Disconnect the fan cable from the system board. Release the speaker cable and the antennas from the cable guide. Remove two screws. Then, remove the fan.




Figure 21. Remove the fan

Table 20. Screws used to secure the fan

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2	3.5	1.85 ± 0.15	2

Step 2. Install the fan in reverse order.

I/O board

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 31.
- Make sure the following FRUs (or CRUs) have been removed.

- “Lower case” on page 31
- “Fan” on page 46
- “Heat sink” on page 41
- “Display module” on page 47

Step 1. Disconnect the I/O board cable from the I/O board. Remove one screw. Then, remove the I/O board.




Figure 22. Remove the I/O board

Table 21. Screws used to secure the I/O board

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2	3.5	1.85 ± 0.15	1

Step 2. Install the I/O board in reverse order.

Display module

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 31.
- Make sure the following FRUs (or CRUs) have been removed.

- “Lower case” on page 31
- “Heat sink” on page 41

Step 1. Peel off the MB acetate tape.




Figure 23. Peel off the MB acetate tape

Step 2. Disconnect the EDP cable and the camera cable from the system board.




Figure 24. Disconnect cables

Step 3. Remove seven screws.




Figure 25. Remove seven screws

Table 22. Screws used to secure the hinge

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2.5	5.5	3.0 ± 0.3	7

Step 4. Open the display module until it reaches an angle more than 90 degrees relative to the base. Then, remove the display module.




Figure 26. Remove the display module

Step 5. Install the display module in reverse order.

Panel Self Test

When you turn on the computer and the panel goes black, run panel Self Test to help you determine whether the panel functions normally.

To run panel Self Test:

Ensure that the computer is connected to ac power. Then, press the power button for about seven seconds to turn off the computer.

Press Fn, left Ctrl, and the power button at the same time. If the computer displays five solid colors in sequence across the entire screen, it indicates that the panel functions normally.

The test lasts for about 20 seconds and then exits automatically. You also can press the power button to exit the test.

Disassemble the display module

The display module as a whole is not a FRU. Instead, it contains FRUs as its components. Before disassembling the display module, make sure it has been detached from the upper case.

Strip cover

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Display module” on page 47

Step 1. Remove the strip cover.




Figure 27. Remove the strip cover

Step 2. Install the strip cover in reverse order.

Sensor board

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.

- Make sure the following FRUs (or CRUs) have been removed.

“Display module” on page 47

“Strip cover” on page 50

Step 1. Disconnect the sensor board connector. Then, pry up the sensor board.




Figure 28. Remove the sensor board

Step 2. Install the sensor board in reverse order.

Display panel

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Display module” on page 47
 - “Strip cover” on page 50

Step 1. Place the display module on a hard surface with the screen facing upward and the hinge side facing you.

Step 2. Disconnect the touch board connector and the sensor board connector. Remove two screws. Then, pry up the sensor board.




Figure 29. Disconnect the touch board connector and the sensor board connector, remove two screws, and pry up the touch board

Table 23. Screws used to secure the display panel

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2	2.3	1.85 ± 0.15	2

- Step 3. Use a pair of tweezers to take out the tabs of four stretch-release tapes: Pull the tab for the left stretch-release tape downward to detach it. Next, locate the tab for the right tape and pull it downward to detach it. After that, locate the second tab from the left and pull it downward to detach the top stretch-release tape. Locate the third tab from the left and pull it downward to detach the bottom stretch-release tape.
- The display panel is secured to the display cover using four stretch-release tapes: two are positioned on the sides, one at the top, and one at the bottom. The graphic below illustrates the locations of these tapes beneath the screen. For the left and right tapes, the entire tape is adhesive and stretchable. For the top and bottom tapes, the downward-folded section is non-adhesive and non-stretchable.

Attention: Stretch-release tapes lose their adhesive properties when stretched. To effectively detach a stretch-release tape, it is essential to follow a pull-shift-pull pattern. Begin by gripping the tab and pulling the tape downward approximately three to four centimeters. Next, shift your hand to grip the tape as high as possible, and pull again for another three to four centimeters. Continue this pattern until the tape is completely removed.





Figure 30. Take out the stretch-release tapes

Step 4. Carefully lift the display panel.



Step 5. Turn over the display panel. Peel off the tape. Then, remove the EDP cable from the display panel.




Figure 31. Remove the EDP cable

Install the display panel

Step 1. Peel off the release liner from one side of the stretch-release tape and adhere it to a specified location as illustrated.

- For the left or the right tape: Directly adhere it to the specified location on the left or right side.
- For the top or the bottom tape: Adhere the adhesive and stretchable half horizontally to the specified location at the top or the bottom of the display cover, and then fold the non-adhesive, non-stretchable half downward at a 90-degree angle.




Figure 32. The locations of the stretch-release tapes

Step 2. Peel off a section of the liner that is approximately 6 centimeters long and fold it outwards so that the end of the liner extends beyond the bottom edge of the display cover.

- Step 3. Repeat the operation for other stretch-release tapes.
- Step 4. Gradually lower panel on the display cover until the panel makes firm contact with the edges.
- Step 5. Pull the liners of the tapes downward to detach them.
- Step 6. Gently slide your fingers over the panel where the stretch-release tapes are attached underneath to ensure the panel is securely fastened to the tapes.

Hinges

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Display module” on page 47
 - “Strip cover” on page 50
 - “Display panel” on page 51

Step 1. Remove six screws. Then, remove the hinges.




Figure 33. Remove the hinges

Table 24. Screws used to secure the hinges

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2.0	2.3	1.85 ± 0.15	6

Step 2. Install the hinges in reverse order.

Microphone rubbers

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Display module” on page 47

“Strip cover” on page 50

“Display panel” on page 51

Step 1. Remove the microphone rubbers.




Figure 34. Remove the microphone rubbers

Step 2. Install the microphone rubbers in reverse order.

IR rubber

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.

“Display module” on page 47

“Strip cover” on page 50

“Display panel” on page 51

Step 1. Remove the IR rubber.




Figure 35. Remove the IR rubber

Step 2. Install the IR rubber in reverse order.

Camera shutter

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Display module” on page 47
 - “Strip cover” on page 50
 - “Display panel” on page 51

Step 1. Remove the camera shutter.




Figure 36. Remove the camera shutter

Step 2. Install the camera shutter in reverse order.

Camera cable

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Display module” on page 47
 - “Strip cover” on page 50
 - “Display panel” on page 51

Step 1. Disconnect the camera cable. Then, remove the cable from the camera board and the display cover.




Figure 37. Remove the camera cable

Step 2. Install the camera cable in reverse order.

Camera board

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Display module” on page 47
 - “Strip cover” on page 50
 - “Display panel” on page 51
 - “Microphone rubbers” on page 55
 - “IR rubber” on page 56
 - “Camera shutter” on page 57

Step 1. Disconnect the camera cable from the camera board. Then, remove the camera board.




Figure 38. Remove the camera board

Step 2. Install the camera board in reverse order.

Display cover

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Display module” on page 47
 - “Strip cover” on page 50
 - “Sensor board” on page 50
 - “Display panel” on page 51
 - “Hinges” on page 55
 - “Microphone rubbers” on page 55
 - “IR rubber” on page 56
 - “Camera shutter” on page 57
 - “Camera cable” on page 58
 - “Camera board” on page 59

The display module is now completely detached. The following FRUs are either exposed or have been detached after completing this disassembly procedure.

FRU	Components and miscellaneous parts
Camera board	N/A
Camera cable	N/A
Camera shutter	N/A
Display cover	Four stretch-release tapes: Left, right, top, and bottom

FRU	Components and miscellaneous parts
Display panel	Four stretch-release tapes: Left, right, top, and bottom
EDP cable	N/A
Hinges	Two hinges: Right and left
IR rubber	N/A
Microphone rubbers	Two rubbers: Right and left
Stretch-release tape	Four stretch-release tapes: Right, left, top, and bottom
Sensor board	N/A
Strip cover	N/A

System board (with I/O board cable, PMIC cable, and PMIC board)

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Lower case” on page 31
 - “Battery pack” on page 36
 - “M.2 solid-state drive” on page 36
 - “2242 trans cover” on page 37
 - “Wi-Fi card” on page 38
 - “Type-C bracket” on page 40
 - “Memory” on page 40
 - “Heat sink” on page 41
 - “Fan” on page 46
 - “Display module” on page 47

Step 1. Peel off the MB acetate tape.




Figure 39. Peel off the MB acetate tape

Step 2. Disconnect the speakers, the keyboard backlight cable, the keyboard cable, the touchpad cable, the I/O board cable, the EDP cable, and the camera cable from the system board.




Figure 40. Disconnect the cables

Step 3. Peel off the I/O board cable. Remove three screws. Then, remove the system board.




Figure 41. Remove three screws and remove the system board

Table 25. Screws used to secure the system board

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2	3.5	1.85 ± 0.15	3

Step 4. Turn over the system board. Then, disconnect the I/O board cable from the system board.




Figure 42. Disconnect the I/O board cable from the system board

Step 5. For models with an OLED display panel, follow these steps to remove the PMIC cable and the PMIC board from the system board:

1. Peel off the MB acetate tape.




Figure 43. Peel off the MB acetate tape covering the PMIC board and the PMIC cable

2. Disconnect the PMIC cable from the PMIC board and the system board. Then, remove the PMIC board.




Figure 44. Disconnect the PMIC cable and then remove the PMIC board

Step 6. Install the system board, the I/O board cable, the PMIC cable, and the PMIC board in reverse order.

Write key product information to a replacement system board

Some key product information and settings are stored in the ROMs of the PC's system board. The information and settings are essential for using and servicing a Lenovo PC. After replacing a system board for a Lenovo PC, you need to use a Lenovo-provided software tool to write key information—including machine type model (MTM), serial number (SN), and product name—as well as settings such as keyboard language to the replacement system board.

For service technicians, go to <https://support.lenovo.com/us/en/solutions/ht102004> for detailed instructions on how to create and use a Golden Key U1 tool or a normal BIOS tool.

For users, follow the following steps:

Attention: Take extra caution when entering the MTM and SN and when selecting the product name and keyboard language. Carefully verify these details before committing the writing action. Once recorded on the

system board, they cannot be altered. Consult Lenovo service if you are uncertain about the MTM, SN, and product name for your PC.

- Step 1. Connect the ac power adapter and turn on the computer.
- Step 2. Download the tool package and double-click the WinMBDWizard.exe file to run the tool. To download the tool, go to <https://support.lenovo.com/solutions/HT516532>.
- Step 3. Follow the on-screen instructions to input the MTM and SN, select the product name and keyboard language of the computer.
- Step 4. Click **Start Update** to update the product information.
- Step 5. Click **Yes** in the confirmation window to continue the update.
- Step 6. Click **Finish** to close the tool.
- Step 7. Click **Yes** in the confirmation window to restart the computer and apply the configuration on the system board.

Note: Do not turn off the computer or disconnect the computer from ac power during the whole process.

Upper case

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Lower case” on page 31
 - “Battery pack” on page 36
 - “M.2 solid-state drive” on page 36
 - “2242 trans cover” on page 37
 - “Wi-Fi card” on page 38
 - “Type-C bracket” on page 40
 - “Memory” on page 40
 - “Heat sink” on page 41
 - “Speakers” on page 45
 - “Fan” on page 46
 - “I/O board” on page 46
 - “Display module” on page 47
 - “System board (with I/O board cable, PMIC cable, and PMIC board)” on page 61

Chapter 5. Hardware replacement (for 15-inch models)

This chapter provides instructions on how to remove and install the hardware components of your computer.

General guidelines



Before removing any FRU or CRU, shut down the computer, unplug all power cords from electrical outlets, and wait about ten minutes to let the computer cool down.

When removing or replacing a CRU/FRU, ensure that you observe the following general guidelines:

1. Before replacing any CRU/FRU, ensure that you have read [Generic Safety and Compliance Notices](#).
2. Begin by removing any CRUs/FRUs that have to be removed before replacing the failing CRU/FRU. Any such CRUs/FRUs are listed at the beginning of each CRU/FRU replacement procedure. Remove them in the order in which they are listed.
3. Follow the correct sequence in the steps for removing a CRU/FRU, as shown in the illustrations by the numbers in square callouts.
4. When removing a CRU/FRU, move it in the direction as shown by the arrow in the illustration.

Attention:

- After replacing a CRU/FRU, do not turn on the computer until you have ensured that all screws, springs, and other small parts are in place and none are loose inside the computer. Verify this by shaking the computer gently and listening for rattling sounds. Metallic parts or metal flakes can cause electrical short circuits.
- The system board is sensitive to and can be damaged by ESD. Before touching it, establish personal grounding by touching a ground point with one hand or by using an ESD strap (P/N 6405959).

Lower case

Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.

Step 1. Place the computer upside down on a flat surface.

Step 2. Remove six screws. Then, pry up the latches and remove the lower case.




Figure 45. Remove six screws and the lower case

Table 26. Screws used to secure the lower case

Label	Thread	Length (mm)	Torque (kgf.cm)	Quantity
1	M2	8.0	1.2 ± 0.1	2
2	M2	4.5	1.2 ± 0.1	4

Step 3. Install the lower case in reverse order.

Label locations

When replacing the lower case or the upper case, reapply all labels that come with the replacement case. If some original labels are not included with the replacement case, peel them off from the original case and paste them on the replacement case.

Label locations on the upper case (with a palmrest label)




Figure 46. Label layout on the upper case (with a palmrest label)

Labels attached to the upper case are country/region specific. Make sure to apply the appropriate labels to the replacement upper case.

Table 27. All upper case labels (with a palmrest label)

Label	Label description	Applied country/region	Label dimensions
1	Palmrest label	All	18 mm × 75 mm
2	QR label	Non-EAA countries or regions	17 mm × 26.1 mm
3	AMD RADEON label	All	19.53 mm × 16.51 mm
4	Intel label	All	18 mm × 22.25 mm
	AMD RYZEN label		19.53 mm × 16.51 mm

Label locations on the upper case (no palmrest label)




Figure 47. Label layout on the upper case (no palmrest label)

Labels attached to the upper case are country/region specific. Make sure to apply the appropriate labels to the replacement upper case.

Table 28. All upper case labels (no palmrest label)

Label	Label description	Applied country/region	Label dimensions
1	AMD RADEON label	All	19.53 mm × 16.51 mm
2	Intel label	All	18 mm × 22.25 mm
	AMD RYZEN label		19.53 mm × 16.51 mm
3	QR label	Non-EAA countries or regions	17 mm × 26.1 mm

Label locations on the back side of the lower case (for non-EAA countries or regions)




Figure 48. Label layout on the back side of the lower case (for non-EAA countries or regions)

Label layout on the back side of the lower case (for EAA countries or regions)




Table 29. All lower case labels (for non-EAA countries or regions)

Label	Label description	Applied country/region	Label dimensions
1	Laser etched rating label	All	100 mm × 30 mm
	POD rating label		
2	Country/region label	Belarus (Belarus label)	40 mm × 8 mm
		Brazil (WL&BT label)	16.5 mm × 15 mm

Table 29. All lower case labels (for non-EAA countries or regions) (continued)

Label	Label description	Applied country/region	Label dimensions
		Canada (USA warning label)	120 mm × 20 mm
		Israel, USA, Canada, Taiwan, Argentina (WL label)	32 mm × 10 mm
		Japan (WL&BT label)	52 mm × 10 mm
		Korea (KR KCC label)	50 mm × 43 mm
		Malaysia, Indonesia (WL label)	15 mm × 10 mm
		Malaysia (Malaysia MCMC label)	8 mm × 8 mm
		South Africa (WL label)	20 mm × 10 mm
		Taiwan (TW Caution label)	70 mm × 10 mm
		Vietnam (Energy label)	10 mm × 9 mm
3	CO2 offset label	All	18 mm × 18 mm
4	OS label	All	16.1 mm × 22.5 mm
5	QR label	EAA countries or regions	17 mm × 26.1 mm
6	Transparent raised label	EAA countries or regions	17 mm × 17 mm

Note: Depending on the country/region where the computer is purchased, the upper case and the lower case may include one or more of the above listed labels. For the laser etched label, print the label and apply it to the replacement case according to the label location illustrated above. The artworks for the laser etched labels are country/region specific and can be found in Appendix C “Artworks for laser etched labels (IdeaPad 5 2-in-1 15AGP11)” on page 110, Appendix D “Artworks for laser etched labels (IdeaPad 5 2-in-1 15AHP11)” on page 114, and Appendix E “Artworks for laser etched labels (IdeaPad 5 2-in-1 15IPH11)” on page 117.

Battery pack

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.
“Lower case” on page 66

Step 1. Disconnect the battery pack cable from the system board.

Attention: Use your fingernails to pull the connector to unplug it. Do not pull the cable.

Step 2. Remove two screws. Then, remove the battery pack.




Figure 49. Remove the battery pack (for the 60 Wh battery pack)




Figure 50. Remove the battery pack (for the 84 Wh battery pack)

Table 30. Screws used to secure the battery pack

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2	3.5	1.85 ± 0.15	2

Step 3. For the 84 Wh battery pack, remove the battery pack cable, if necessary.




Figure 51. Remove the battery pack cable of the 84 Wh battery pack

Step 4. Install the battery pack and the battery pack cable in reverse order.

M.2 solid-state drive

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Lower case” on page 66

Step 1. Disconnect the battery pack cable from the system board. Then, remove one screw and remove the solid-state drive by pulling it away from the slot.

Attention: Use your fingernail to pull the connector to unplug it. Do not pull the cable.




Figure 52. Remove the solid-state drive

Table 31. Screws used to secure the primary solid-state drive

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2	3.5	1.85 ± 0.15	1

Note: The product supports up to two solid-state drives. Remove both, if necessary.

Step 2. Install the M.2 solid-state drive in reverse order.

2242 trans cover

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.

“Lower case” on page 66

Step 1. Remove one screw. Then, pry up the 2242 trans cover.




Figure 53. Remove the 2242 trans cover

Table 32. Screws used to secure the 2242 trans cover

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2	3.5	1.85 ± 0.15	1

Step 2. Install the 2242 trans cover in reverse order.

Wi-Fi card

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.
“Lower case” on page 31

Step 1. Disconnect the battery pack cable from the system board. Then, remove the Wi-Fi card mylar.

Attention: Use your fingernails to pull the connector to unplug it. Do not pull the cable.




Figure 54. Remove the Wi-Fi card mylar

Step 2. Detach the main and auxiliary antenna cable connectors. Remove one screw. Then, remove the Wi-Fi card by pulling it away from the slot.




Figure 55. Remove the Wi-Fi card

Table 33. Screw used to secure the Wi-Fi card

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2	3.5	1.85 ± 0.15	1

Step 3. Install the Wi-Fi card in reverse order.

Memory

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.

“Lower case” on page 66

Step 1. Disconnect the battery pack cable from the system board. Peel off the tapes. Then, remove the memory shielding.

Attention: Use your fingernails to pull the connector to unplug it. Do not pull the cable.




Figure 56. Remove the memory shielding

Step 2. Remove the memory module.




Figure 57. Remove the memory module

Step 3. Install the memory module and the memory shielding in reverse order.

Fan

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Lower case” on page 66

Step 1. Disconnect the battery pack cable from the system board.

Attention: Use your fingernails to pull the connector to unplug it. Do not pull the cable.

Step 2. Release the speaker cable from the cable guide. Disconnect the fan cable from the system board. Remove two screws. Then, remove the fan.




Figure 58. Remove the fan

Table 34. Screws used to secure the fan

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2	3.5	1.85 ± 0.15	2

Step 3. Install the fan in reverse order.

Heat sink

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.

“Lower case” on page 66

Step 1. Disconnect the battery pack cable from the system board.

Attention: Use your fingernails to pull the connector to unplug it. Do not pull the cable.

Step 2. Peel off the tape. Remove three or four screws in the alphabetical order. Then, remove the heat sink.




Figure 59. Remove the heat sink (for AMD models)

Table 35. Screw used to secure the heat sink (for AMD models)

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2	2.2	1.85 ± 0.15	3




Figure 60. Remove the heat sink (for Intel models)

Table 36. Screw used to secure the heat sink (for Intel models)

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2	2.2	1.85 ± 0.15	4

Step 3. Install the heat sink in reverse order.

Handling thermal interface materials

Thermal interface materials are typically applied between a heat sink and a CPU (and/or GPU) die to enhance the heat transfer capability of the heat sink. If thermal interface materials are exposed during computer servicing, such as when replacing the heat sink or system board, it is important to handle the thermal interface materials properly.

- You need to completely remove the old thermal interface materials from the CPU and/or GPU die.
- You need to apply new thermal interface materials onto the heat sink according to the type, quantity, and application areas specified in this publication.

Related topics

“Heat sink” on page 41

“System board (with I/O board cable, PMIC cable, and PMIC board)” on page 61

Type, quantity, and areas of thermal interface materials application on the heat sink

The table and figure below provide information on the type and quantity of thermal interface materials, as well as the specific areas on the heat sink where these materials should be applied.

Models	Area	Type	Quantity
AMD models	a	PTM7958sp	0.15 g–0.2 g, 17.96 mm × 13.97 mm × 0.2 mm
Intel models	a	PTM7958sp	0.2 g–0.25 g, 20.0 mm × 13.5 mm × 0.2 mm




Figure 61. Areas on the heat sink where thermal interface materials should be applied (for AMD models)




Figure 62. Areas on the heat sink where thermal interface materials should be applied (for Intel models)

Areas on the system board where thermal interface materials are applied

The following figure shows the areas on the system board where thermal interface materials are applied.




Figure 63. Areas on the system board where thermal interface materials are applied (for AMD models)




Figure 64. Areas on the system board where thermal interface materials are applied (for Intel models)

Speakers

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Lower case” on page 66
 - “Heat sink” on page 79

Step 1. Peel off the MB acetate tape.




Figure 65. Peel off the MB acetate tape

Step 2. Disconnect the speakers from the system board. Release the left speaker cable from the guide. Remove four screws. Then, remove the speakers from the upper case.




Figure 66. Remove the speakers

Table 37. Screws used to secure the hinge

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M1.6	1.6	0.9 ± 0.1	4

Step 3. Install the speakers in reverse order.

Display module

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.

“Lower case” on page 66

“Heat sink” on page 79

Step 1. Disconnect the speaker near the memory module from the system board.

Note: For details about how to disconnect the speaker, see “Speakers” on page 82.

Step 2. Disconnect the EDP cable and the camera cable from the system board.




Figure 67. Disconnect cables

Step 3. Remove six screws.




Figure 68. Remove six screws

Table 38. Screws used to secure the hinge

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2	5.0	1.85 ± 0.15	6

- Step 4. Open the display module until it reaches an angle more than 90 degrees relative to the base and then remove the display module.




Figure 69. Remove the display module

- Step 5. Install the display module in reverse order.



Panel Self Test

When you turn on the computer and the panel goes black, run panel Self Test to help you determine whether the panel functions normally.

To run panel Self Test:

Ensure that the computer is connected to ac power. Then, press the power button for about seven seconds to turn off the computer.

Press Fn, left Ctrl, and the power button at the same time. If the computer displays five solid colors in sequence across the entire screen, it indicates that the panel functions normally.

The test lasts for about 20 seconds and then exits automatically. You also can press the power button to exit the test.

Disassemble the display module

The display module as a whole is not a FRU. Instead, it contains FRUs as its components. Before disassembling the display module, make sure it has been detached from the upper case.

Strip cover

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.

“Display module” on page 84

Step 1. Remove the strip cover.




Figure 70. Remove the strip cover

Step 2. Install the strip cover in reverse order.

Sensor board

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Display module” on page 84
 - “Strip cover” on page 86

Step 1. Remove the sensor board.




Figure 71. Remove the sensor board

Step 2. Install the sensor board in reverse order.

Display panel

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Display module” on page 84
 - “Strip cover” on page 86

Step 1. Place the display module on a hard surface with the screen facing upward and the hinge side facing you.

Step 2. Disconnect the touch board connector and the sensor board connector. Remove 2 screws. Then, pry up the touch board.




Figure 72. Disconnect the touch board connector and the sensor board connector, remove two screws, and pry up the touch board


Table 39. Screws used to secure the display panel

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M1.6	1.8	1.25 ± 0.15	2


Step 3. Use a pair of tweezers to pull the tabs of five stretch-release tapes to detach the tapes. Follow this order:

1. Pull the tab for the left stretch-release tape downward to detach it.
2. Pull the tab for the right tape and pull it downward to detach it.
3. Locate the second tab from the left and pull it downward to detach the top stretch-release tape.
4. Locate the second tab from the right and pull it downward to detach the other top stretch-release tape.
5. Locate the third tab from the left and pull it downward to detach the bottom stretch-release tape.

Note: The display panel is secured to the display cover using five stretch-release tapes: two are positioned on the sides, two at the top, and one at the bottom. The graphic below illustrates the locations of these tapes beneath the screen. For the left and right tapes, the entire tape is adhesive and stretchable. For the top and bottom tapes, the downward-folded section is non-adhesive and non-stretchable.



Step 4. Carefully lift the display panel.



Step 5. Turn over the display panel. Then, disconnect the EDP cable from the display panel.




Figure 73. Disconnect the EDP cable

Note: To remove the EDP cable, see “EDP cable” on page 94.

Install the display panel

Step 1. Peel off the release liner from one side of the stretch-release tape and adhere it to a specified location as illustrated.

- For the left or the right tape: Directly adhere it to the specified location on the left or right side.
- For the top or the bottom tape: Adhere the adhesive and stretchable half horizontally to the specified location at the top of the display cover, and then fold the non-adhesive, non-stretchable half downward at a 90-degree angle.




Figure 74. The locations of the stretch-release tapes

- Step 2. Peel off a section of the liner that is approximately 6 centimeters long and fold it outwards so that the end of the liner extends beyond the bottom edge of the display cover.
- Step 3. Repeat the operation for other stretch-release tapes.
- Step 4. Gradually lower panel on the display cover until the panel makes firm contact with the edges.
- Step 5. Pull the liners of the tapes downward to detach them.
- Step 6. Gently slide your fingers over the panel where the stretch-release tapes are attached underneath to ensure the panel is securely fastened to the tapes.

Microphone rubbers

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Display module” on page 84
 - “Strip cover” on page 86
 - “Display panel” on page 87

- Step 1. Remove the microphone rubbers.




Figure 75. Remove the microphone rubbers

- Step 2. Install the microphone rubbers in reverse order.

IR rubber

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Display module” on page 84
 - “Strip cover” on page 86
 - “Display panel” on page 87

Step 1. Remove the IR rubber.




Figure 76. Remove the IR rubber

Step 2. Install the IR rubber in reverse order.

Camera shutter

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Display module” on page 84
 - “Strip cover” on page 86
 - “Display panel” on page 87

Step 1. Remove the camera shutter.




Figure 77. Remove the camera shutter

Step 2. Install the camera shutter in reverse order.

Hinges

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Display module” on page 84
 - “Strip cover” on page 86
 - “Display panel” on page 87

Step 1. Remove eight screws. Then, remove the hinges.




Figure 78. Remove the hinges

Table 40. Screws used to secure the hinges

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2	2.3	1.5 ± 0.1	8

Step 2. Remove the EDP cable and the camera cable.

Note: For details about how to remove the EDP cable and the camera cable, see “EDP cable” on page 94 and “Camera cable” on page 95.

Step 3. Install the hinges in reverse order.

EDP cable

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.

“Display module” on page 84


“Strip cover” on page 86

“Display panel” on page 87

Step 1. Remove the left hinge.

Note: For details about how to remove the hinge, see “Hinges” on page 93.

Step 2. Hold the EDP cable and pull it outward to remove the cable together with the hinge plastic.



Step 3. Install the EDP cable in reverse order.

Camera cable

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Display module” on page 84
 - “Strip cover” on page 86
 - “Display panel” on page 87

Step 1. Disconnect the camera cable from the camera board. Then, peel off the cable from the display cover.




Figure 79. Remove the camera cable

Step 2. Remove the right hinge.

Note: For details about how to remove the hinges, see “Hinges” on page 93.

Step 3. Hold the camera cable and pull it outward to remove the cable together with the hinge plastic.



Step 4. Install the camera cable in reverse order.

Camera board

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Display module” on page 84
 - “Strip cover” on page 86
 - “Display panel” on page 87
 - “Microphone rubbers” on page 91
 - “IR rubber” on page 91
 - “Camera shutter” on page 92

Step 1. Disconnect the camera cable from the camera board. Then, remove the camera board.




Figure 80. Remove the camera board

Step 2. Install the camera board in reverse order.

Display cover

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Display module” on page 84
 - “Strip cover” on page 86
 - “Sensor board” on page 87
 - “Display panel” on page 87
 - “Microphone rubbers” on page 91
 - “IR rubber” on page 91
 - “Camera shutter” on page 92
 - “Hinges” on page 93
 - “EDP cable” on page 94
 - “Camera cable” on page 95
 - “Camera board” on page 96

The display module is now completely detached. The following FRUs are either exposed or have been detached after completing this disassembly procedure.

FRU	Components and miscellaneous parts
Camera board	N/A
Camera cable	N/A
Camera shutter	N/A
Display cover	Five stretch-release tapes: Left × 1, right × 1, top × 2, and bottom × 1

FRU	Components and miscellaneous parts
Display panel	Five stretch-release tapes: Left × 1, right × 1, top × 2, and bottom × 1
EDP cable	N/A
Hinges	Two hinges: Right and left
Hinge plastics	Two plastics: Right and left
IR rubber	N/A
Microphone rubbers	Two rubbers: Right and left
Stretch-release tape	Five stretch-release tapes: Left × 1, right × 1, top × 2, and bottom × 1
Sensor board	N/A
Strip cover	N/A

Type-C bracket

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Lower case” on page 66
 - “Heat sink” on page 79
 - “Display module” on page 84

Step 1. Remove two screws. Then, remove the Type-C bracket.




Figure 81. Remove the Type-C bracket

Table 41. Screws used to secure the Type-C bracket

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M1.6	3	1.25 ± 0.15	2

Step 2. Install the Type-C bracket in reverse order.

I/O board

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.

“Lower case” on page 66

“Heat sink” on page 79

“Display module” on page 84

Step 1. Disconnect the I/O board cable from the I/O board. Remove one screw. Then, remove the I/O board.




Figure 82. Remove the I/O board

Table 42. Screws used to secure the I/O board

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2	3.5	1.85 ± 0.15	1

Step 2. Install the I/O board in reverse order.

System board (with I/O board cable, PMIC cable, and PMIC board)

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.

“Lower case” on page 66
“Battery pack” on page 71
“M.2 solid-state drive” on page 73
“2242 trans cover” on page 74
“Wi-Fi card” on page 75
“Memory” on page 77
“Fan” on page 78
“Heat sink” on page 79
“Display module” on page 84
“Type-C bracket” on page 98

Step 1. Disconnect the keyboard backlight cable, the keyboard cable, the touchpad cable, the I/O board cable, and the speaker cable near the I/O board from the system board.




Figure 83. Disconnect the cables

Step 2. Peel off the I/O board cable. Remove three screws. Then, remove the system board.




Figure 84. Remove three screws and remove the system board

Table 43. Screws used to secure the system board

Thread	Length (mm)	Torque (kgf.cm)	Quantity
M2	3.5	1.85 ± 0.15	3

Step 3. Turn over the system board. Then, disconnect the I/O board cable from the system board.




Figure 85. Disconnect the I/O board cable from the system board

Step 4. For models with an OLED display panel, follow these steps to remove the PMIC cable and the PMIC board from the system board:

1. Peel off the MB acetate tape.




Figure 86. Peel off the MB acetate tape covering the PMIC board and the PMIC cable

2. Disconnect the PMIC cable from the PMIC board and the system board. Then, remove the PMIC board.




Figure 87. Disconnect the PMIC cable and then remove the PMIC board

Step 5. Install the system board, the I/O board cable, the PMIC cable, and the PMIC board in reverse order.

Write key product information to a replacement system board

Some key product information and settings are stored in the ROMs of the PC's system board. The information and settings are essential for using and servicing a Lenovo PC. After replacing a system board for a Lenovo PC, you need to use a Lenovo-provided software tool to write key information—including machine type model (MTM), serial number (SN), and product name—as well as settings such as keyboard language to the replacement system board.

For service technicians, go to <https://support.lenovo.com/us/en/solutions/ht102004> for detailed instructions on how to create and use a Golden Key U1 tool or a normal BIOS tool.

For users, follow the following steps:

Attention: Take extra caution when entering the MTM and SN and when selecting the product name and keyboard language. Carefully verify these details before committing the writing action. Once recorded on the

system board, they cannot be altered. Consult Lenovo service if you are uncertain about the MTM, SN, and product name for your PC.

- Step 1. Connect the ac power adapter and turn on the computer.
- Step 2. Download the tool package and double-click the WinMBDWizard.exe file to run the tool. To download the tool, go to <https://support.lenovo.com/solutions/HT516532>.
- Step 3. Follow the on-screen instructions to input the MTM and SN, select the product name and keyboard language of the computer.
- Step 4. Click **Start Update** to update the product information.
- Step 5. Click **Yes** in the confirmation window to continue the update.
- Step 6. Click **Finish** to close the tool.
- Step 7. Click **Yes** in the confirmation window to restart the computer and apply the configuration on the system board.

Note: Do not turn off the computer or disconnect the computer from ac power during the whole process.

Upper case

- Before you start, ensure that you have read Chapter 1 “Safety requirements for hardware maintenance” on page 1 and “General guidelines” on page 66.
- Make sure the following FRUs (or CRUs) have been removed.
 - “Lower case” on page 66
 - “Battery pack” on page 71
 - “M.2 solid-state drive” on page 73
 - “Wi-Fi card” on page 75
 - “Memory” on page 77
 - “Fan” on page 78
 - “Heat sink” on page 79
 - “Speakers” on page 82
 - “Display module” on page 84
 - “Type-C bracket” on page 98
 - “I/O board” on page 99
 - “System board (with I/O board cable, PMIC cable, and PMIC board)” on page 99

Appendix A. Artworks for laser etched labels (IdeaPad 5 2-in-1 14AGP11)

Argentina



Figure 88. Artworks for the laser etched label used in Argentina

Brazil




Figure 89. Artworks for the laser etched label used in Brazil

India




Figure 90. Artworks for the laser etched label used in India

Japan




Figure 91. Artworks for the laser etched label used in Japan

Malaysia



Figure 92. Artworks for the laser etched label used in Malaysia

Morocco Group and Indonesia



Figure 93. Artworks for the laser etched label used in Morocco Group and Indonesia

South Africa



Figure 94. Artworks for the laser etched label used in South Africa

Taiwan




Figure 95. Artworks for the laser etched label used in Taiwan

USCA




Figure 96. Artworks for the laser etched label used in USCA

Vietnam




Figure 97. Artworks for the laser etched label used in Vietnam

Worldwide countries or regions



Figure 98. Artworks for the laser etched label used in worldwide countries or regions

Appendix B. Artworks for laser etched labels (IdeaPad 5 2-in-1 14AHP11)

Argentina



Figure 99. Artworks for the laser etched label used in Argentina

Brazil




Figure 100. Artworks for the laser etched label used in Brazil

India




Figure 101. Artworks for the laser etched label used in India (IdeaPad 5 2-in-1 14AHP11 1)

Japan



Figure 102. Artworks for the laser etched label used in Japan

Malaysia




Figure 103. Artworks for the laser etched label used in Malaysia

Morocco Group and Indonesia




Figure 104. Artworks for the laser etched label used in Morocco Group and Indonesia

South Africa




Figure 105. Artworks for the laser etched label used in South Africa

Taiwan




Figure 106. Artworks for the laser etched label used in Taiwan

USCA




Figure 107. Artworks for the laser etched label used in USCA

Vietnam



Figure 108. Artworks for the laser etched label used in Vietnam

Worldwide countries or regions




Figure 109. Artworks for the laser etched label used in worldwide countries or regions

Appendix C. Artworks for laser etched labels (IdeaPad 5 2-in-1 15AGP11)

Argentina




Figure 110. Artworks for the laser etched label used in Argentina

Brazil




Figure 111. Artworks for the laser etched label used in Brazil

India




Figure 112. Artworks for the laser etched label used in India (IdeaPad 5 2-in-1 15AGP11 1)




Figure 113. Artworks for the laser etched label used in India (IdeaPad 5 2-in-1 15AGP11 2)

Japan




Figure 114. Artworks for the laser etched label used in Japan

Korea




Figure 115. Artworks for the laser etched label used in Korea

Malaysia




Figure 116. Artworks for the laser etched label used in Malaysia

Morocco Group and Indonesia



Figure 117. Artworks for the laser etched label used in Morocco Group and Indonesia

South Africa



Figure 118. Artworks for the laser etched label used in South Africa

Taiwan




Figure 119. Artworks for the laser etched label used in Taiwan

USCA




Figure 120. Artworks for the laser etched label used in USCA

Vietnam




Figure 121. Artworks for the laser etched label used in Vietnam

Worldwide countries and regions



Figure 122. Artworks for the laser etched label used in worldwide countries and regions

Appendix D. Artworks for laser etched labels (IdeaPad 5 2-in-1 15AHP11)

Argentina




Figure 123. Artworks for the laser etched label used in Argentina

Brazil




Figure 124. Artworks for the laser etched label used in Brazil

India




Figure 125. Artworks for the laser etched label used in India (IdeaPad 5 2-in-1 15AHP11 1)




Figure 126. Artworks for the laser etched label used in India (IdeaPad 5 2-in-1 15AHP11 2)

Japan




Figure 127. Artworks for the laser etched label used in Japan

Malaysia




Figure 128. Artworks for the laser etched label used in Malaysia

Morocco Group and Indonesia




Figure 129. Artworks for the laser etched label used in Morocco Group and Indonesia

South Africa




Figure 130. Artworks for the laser etched label used in South Africa

Taiwan




Figure 131. Artworks for the laser etched label used in Taiwan

USCA




Figure 132. Artworks for the laser etched label used in USCA

Vietnam



Figure 133. Artworks for the laser etched label used in Vietnam

Worldwide countries and regions



Figure 134. Artworks for the laser etched label used in worldwide countries and regions

Appendix E. Artworks for laser etched labels (IdeaPad 5 2-in-1 15IPH11)

Argentina



Figure 135. Artworks for the laser etched label used in Argentina

Brazil




Figure 136. Artworks for the laser etched label used in Brazil

India




Figure 137. Artworks for the laser etched label used in India (IdeaPad 5 2-in-1 15IPH11 1)




Figure 138. Artworks for the laser etched label used in India (IdeaPad 5 2-in-1 15IPH11 2)

Japan




Figure 139. Artworks for the laser etched label used in Japan

Korea



Figure 140. Artworks for the laser etched label used in Korea

Malaysia



Figure 141. Artworks for the laser etched label used in Malaysia

Morocco Group and Indonesia




Figure 142. Artworks for the laser etched label used in Morocco Group and Indonesia

South Africa



Figure 143. Artworks for the laser etched label used in South Africa

Taiwan



Figure 144. Artworks for the laser etched label used in Taiwan

USCA




Figure 145. Artworks for the laser etched label used in USCA

Vietnam



Figure 146. Artworks for the laser etched label used in Vietnam

Worldwide countries and regions



Figure 147. Artworks for the laser etched label used in worldwide countries and regions

Appendix F. Important notice for Quebec consumers

In regard to section 79.18 of Quebec's Regulation respecting the application of the Consumer Protection Act, Lenovo in no way guarantees the availability of (a) replacement parts; (b) repair services; and (c) information necessary to maintain or repair the goods. For up-to-date information on the technical support and parts available for your purchase, please consult <https://support.lenovo.com/ca/en>.

En ce qui concerne l'article 79.18 du Règlement d'application de la Loi sur la protection du consommateur du Québec, Lenovo ne garantit en aucune façon la disponibilité des éléments suivants : (a) les pièces de rechange ; (b) les services de réparation ; et (c) les renseignements nécessaires à l'entretien à la réparation du bien. Pour obtenir des renseignements à jour sur le soutien technique et les pièces disponibles pour votre achat, veuillez consulter <https://support.lenovo.com/ca/fr>.

Appendix G. Self-help resources

Use the following self-help resources to learn more about the computer and troubleshoot problems.

Resources	How to access?
Troubleshooting and frequently asked questions	• https://www.lenovo.com/tips • https://forums.lenovo.com
Accessibility information	https://www.lenovo.com/accessibility
Reset or restore Windows	• Use Lenovo recovery options. 1. Go to https://support.lenovo.com/HowToCreateLenovoRecovery. 2. Follow the on-screen instructions. • Use Windows recovery options. 1. Go to https://pcsupport.lenovo.com. 2. Detect your computer or manually select your computer model. 3. Click Troubleshoot & Diagnose → Custom Troubleshooting → Operating System Diagnostics and then follow the on-screen instructions.
Use Lenovo Vantage or Lenovo Baiying to: • Download and install the latest drivers and firmware. • Configure hardware settings. • Diagnose computer hardware problems. • Check the computer warranty status.	Use Windows Search.
Product documentation: • Generic Safety and Compliance Notices • <i>Safety and Warranty Guide</i> • <i>Setup Guide</i> • <i>User Guide</i> • <i>This Hardware Maintenance Manual</i> • <i>Regulatory Notice</i>	Go to Lenovo Documentation Center and search by product.

Resources	How to access?
Lenovo Support Web site with the latest support information on the following: • Drivers and software • Diagnostic solutions • Product and service warranty • Product and parts details • Knowledge base and frequently asked questions	Visit https://support.lenovo.com.
Windows help information	• Use Get Help or Tips. • Use Windows Search. • Microsoft Support Web site: https://support.microsoft.com

Trademarks

LENOVO and the LENOVO logo are trademarks of Lenovo.

All other trademarks are the property of their respective owners. © 2025 Lenovo.

Lenovo