**IPC K240L** 



The **IPC K240L** is the perfect rack for a low-priced server system. The excellent quality of the materials combined with superb workmanship establishes the basis for a very variable case.

The **IPC K240L** offers the possibility to mount an ATX power supply with 80mm fan as well as four 3.5", two 2.5" HDDs and one 5.25" external drive.

Furthermore the **IPC IPC K240L** provides two 80mm fans and perforated slot brackets for excellent cooling.

Both serial USB 3.0 front connectors round off the whole package.





## **Specifications**

Mainboard	Mini ITX, µATX
	Max. Mainboard size WxD: 244mm x 244mm, 9.6" x 9.6"
Drive Bays	5.25" external: 0
	3.5" external: 0
	3.5" internal: 4*
	2.5" internal: 2*
Front Connectors	USB 3.0: 2
Cooling System	Front: 2x 80mm
	(serial, molex) Rear 2x 60mm
	(optional)
Controls	Power-Button
	Reset-Button
LED	Power
	HDD-activity
Power Supply	ATX-PSU (80mm fan)
Material	1.0-1.2mm Steel
Maximum CPU cooler height	60mm
Maximum graphics card length	244mm*
Packing Units	Shipping Unit: 1 Piece
	Pallet: 24 Pieces
Guarantee and Warranty	Case 24 Months Warranty
Article Number	88887331
EAN-Code	4260455646383
Scope of Delivery	Screw Set
	Wall Mount set
	4 Stand
Features	Serial 2x 80mm fan
	Possibility to mount an ATX-PSU (80mm fan)
	Removable HDD-cages
	Slot brackets perforated
	*can vary by using several mounting options

<b>Dimensions and Weight</b>					
		Cage	Case	Package	
	Height	89mm	89mm	170mm	
	Width	430mm	482mm	520mm	
	Depth	400mm	433mm	535mm	
Weight (net): 5,35kg Weight (gross): 6,72kg					

Certification:

CE

## Power supply

Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	
P8 12V 8Pin	-	
PCI-Express 6+2Pin		ИĻ
PCI-Express Chin		
IDE 4Pin		-
S-ATA		-
Floppy	-	-
RPM sensor cable	-	-
Fan control	-	-
Fan 120mm	-	-