NCN106A

MCB 1P 10kA/15kA C-6A 1M



Architecture

Neutral position	without neutral
Number of poles	1 P
Type of pole	1 P
Fixing mode	Din-Rail
Curve	C

Main electrical features

Rated operational voltage Ue	230 / 400 V
Rated current	6 A
Type of supply voltage	AC

Voltage

Rated insulation voltage	500 V
Rated impulse withstand voltage	6000 V

Electric current

Rated service breaking capacity Ics AC according IEC 60898-1	7.5 kA

Electric current / temperature	
Rating current 30°C	6 A
Rating current 30°C according to IEC 60947-2	6.73 A
Dimensions	
Depth of installed product	70 mm
Height of installed product	83 mm
Width of installed product	17.5 mm
Power	
Total power loss under IN	1.33 W
Endurance	
Electric endurance in number of cycles	4000
Number of mechanical operations	20000
Capacity	
Number of modules	1
Installation, mounting	
Tightening torque	2,8Nm
Equipment	
Can be accessorized	Yes
Standards	
Standard text	EN 60898-1 ; IEC 60947-2
European directive WEEE	concerned
Safety	
Protection index IP	IP20
Use conditions	
Storage temperature	-25/80 °C
temperatur	
Operating temperature	-25/70 °C