



18V Combi Drill Brushless LXT DHP490RT1J

Model DHP490 is a Combi Drill powered by an 18V LXT Li-ion battery.



Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 500 / 1900 min ⁻¹
Max. fastening torque Hard/Soft	50 / 27 Nm
Torque setting	20
Max Torque	65 Nm
Impacts per Minute (IPM)	0 - 7500 / 28500 min ⁻¹
Max. Drilling Diameter in Wood	38 mm
Drilling Capacity Wood (Auger Bit)	38 mm
Drilling Capacity Wood (Self-feed bit)	38 mm
Max. Drilling Diameter in Masonry	13 mm
Max. Drilling Diameter in Steel	13 mm
Drilling Capacity Flat bit	40 mm
Drilling Capacity Hole Saw	51 mm
Driving Shank	1/2"-20UNF "

EAN 0197050009951

Link to product - www.makitauk.com

User benefits

- Keyless chuck for easy bit installation and removal
- Mechanical 2-speed gearing; High speed mode for speedy drilling in light duty applications; Low speed mode for heavy duty applications requiring high torque
- Built-in LED light with pre-glow and afterglow functions illuminates the work area
- Variable speed trigger allows operator to adjust speed based on materials or application
- eXtreme Protection Technology (XPT) is engineered for improved dust and water resistance for operation in harsh conditions
- Battery protection circuit protects against overloading, over-discharging and over-heating



Related products

■ Standard AC

821550-0

Makpac case (2)



■ Standard MA

BL1850B

Battery LXT® 5,0 Ah



DC18RC

Battery Charger LXT®



■ Other

User manual

Parts drawing