

ThinkStation P330 Tower 30C5002VGE

Region WE	Cable Lock Cable Lock
Country Germany	System Management Intel AMT 12
Machine Type 30C5	Optional Front Ports None
TopSeller TopSeller	Optional Rear Ports None
Processor Xeon E-2124G 4C/4T/3.4GHz/8MB/71W/DDR4-2666	Power Supply Fixed 250W Platinum
Memory 1x 8GB UDIMM DDR4-2666 ECC	Keyboard USB Full
Processor Graphics Intel UHD Graphics P630	Mouse USB Optical
Discrete Graphics Card 1x Quadro P620 2GB	Floor Stand for SFF None
Monitor Cable None	Operating System Windows 10 Pro 64 for Workstations
Disks 1x 1TB HDD 7.2K 3.5" SATA6Gbps	Warranty 3-year, Onsite
Flex Bay None	Global No
Optical 9.0mm DVD±RW	End of Support 2024/08/27
Optane Memory None	Ann Date (mm/yy) 2018/07/27
M.2 Drives None	
WLAN + Bluetooth None	
Media Reader SD Reader	
Available Networking Ports 1x GbE	
Chassis Intrusion Switch None	

Note:

Country Code "US" is for United States, "++" is for EMEA countries (e.g. AD - Saudi, Arabia, AT - Austria, BM - Bulgaria, etc.), "xx" is for EAST countries (e.g. BM - Bulgaria, CX - Hungary, CY - Cyprus, etc.), and "***" is for MEA countries (e.g. AD - Saudi, Arabia, ED - Egypt, EQ - Sweden, etc.). Please be aware that the EMEA/ EAST/MEA models listed above might not be available in all countries



This publication was developed for products and services offered in the United States and E.M.E.A countries. Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area. Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.



<http://psref.lenovo.com>

Visit psref website for the latest version of Product Specifications Reference.

© Lenovo, 2018. All rights reserved.



Components	Specification																																																																								
Machine Type	MT 30C5 for Transactional model and MT 30C6 for Relationship model. For configuration of all 30C5 EMEA and US models, please visit: http://psref.lenovo.com/Product/ThinkStation/ThinkStation_P330_Tower																																																																								
Form factor	18L Tower																																																																								
Dimensions	Height: 376 mm (14.8 in). Width: 165 mm (6.5 in). Depth: 328 mm (12.9 in)																																																																								
Weight	Maximum configuration: 23.4 lb (10.6kg)																																																																								
Processor	Up to one Intel Xeon E family processor, up to 95W, up to 6 cores at 3.8GHz, up to 12MB cache, up to DDR4-2666 memory speed. Or up to one 8th Intel Core family processor, i7, i5, or i3, up to 95W, up to 6 cores at 3.7GHz, up to 12MB cache, up to DDR4-2666 memory speed. Or up to one Intel Pentium Gold G5400 via Special Bids, 54W, 2 cores at 3.7GHz, 4MB cache, DDR4-2400 memory speed																																																																								
Chipset	Intel C246 Chipset																																																																								
Memory	4 DIMM sockets. DDR4-2666. UDIMM. ECC and non-ECC are supported, but memory types cannot be intermixed																																																																								
Memory capacity	Up to 64GB with 4x 16GB, both ECC and non-ECC																																																																								
Memory protection	ECC with ECC UDIMM. Core i7 and i5 processors cannot support ECC UDIMM																																																																								
Expansion slots	Three PCIe 3.0 slots as following:																																																																								
	Slot 1 PCIe 3.0 x16, full height, half length, links to CPU																																																																								
	Slot 2 PCIe 3.0 x1, full height, full length, links to PCH																																																																								
	Slot 3 PCIe 3.0 x16 (negotiable link width x4), full height, half length, links to PCH																																																																								
Graphics - Processor graphics	Integrated Intel UHD Graphics P630 in -G suffix Xeon processors, or Intel UHD Graphics 630 in Core i7, i5, or i3 processors, or Intel UHD Graphics 610 in Pentium Gold G5400. Works along with discrete graphics to support multi-display, enables three display connectors (2x DP, 1x HDMI. HDMI is optional) on rear																																																																								
Graphics - Discrete graphics card	Up to two PCIe 3.0 x16 slots for discrete graphics card (Slot 1 and 3). Supports the following graphics adapters:																																																																								
	<table><tr><th>Adapter</th><th>Cores</th><th>Memory</th><th>Power</th><th>Connectors</th><th>Max qty</th></tr><tr><td>NVS 810</td><td>1024</td><td>4GB DDR3</td><td>68W</td><td>8x miniDP</td><td>1</td></tr><tr><td>Quadro P400</td><td>256</td><td>2GB GDDR5</td><td>30W</td><td>3x miniDP</td><td>2</td></tr><tr><td>Quadro P620</td><td>512</td><td>2GB GDDR5</td><td>40W</td><td>4x miniDP</td><td>2</td></tr><tr><td>Quadro P1000</td><td>640</td><td>4GB GDDR5</td><td>47W</td><td>4x miniDP</td><td>2</td></tr><tr><td>Quadro P2000</td><td>1024</td><td>5GB GDDR5</td><td>75W</td><td>4x DP</td><td>2</td></tr><tr><td>Quadro P4000</td><td>1792</td><td>8GB GDDR5</td><td>105W</td><td>4x DP</td><td>1</td></tr><tr><td>Geforce GTX 1060</td><td>1280</td><td>6GB GDDR5</td><td>120W</td><td>DVI-D DL, HDMI, 3x DP</td><td>1</td></tr><tr><td>Geforce GTX 1070</td><td>1920</td><td>8GB GDDR5</td><td>150W</td><td>DVI-D DL, HDMI, 3x DP</td><td>1</td></tr><tr><td>Geforce GTX 1080</td><td>2560</td><td>8GB GDDR5X</td><td>180W</td><td>DVI-D DL, HDMI, 3x DP</td><td>1</td></tr><tr><td>Radeon Pro WX 3100</td><td>512</td><td>4GB GDDR5</td><td>50W</td><td>DP, 2x miniDP</td><td>2</td></tr><tr><td>Radeon Pro WX 4100</td><td>1024</td><td>4GB GDDR5</td><td>50W</td><td>4x miniDP</td><td>2</td></tr></table>	Adapter	Cores	Memory	Power	Connectors	Max qty	NVS 810	1024	4GB DDR3	68W	8x miniDP	1	Quadro P400	256	2GB GDDR5	30W	3x miniDP	2	Quadro P620	512	2GB GDDR5	40W	4x miniDP	2	Quadro P1000	640	4GB GDDR5	47W	4x miniDP	2	Quadro P2000	1024	5GB GDDR5	75W	4x DP	2	Quadro P4000	1792	8GB GDDR5	105W	4x DP	1	Geforce GTX 1060	1280	6GB GDDR5	120W	DVI-D DL, HDMI, 3x DP	1	Geforce GTX 1070	1920	8GB GDDR5	150W	DVI-D DL, HDMI, 3x DP	1	Geforce GTX 1080	2560	8GB GDDR5X	180W	DVI-D DL, HDMI, 3x DP	1	Radeon Pro WX 3100	512	4GB GDDR5	50W	DP, 2x miniDP	2	Radeon Pro WX 4100	1024	4GB GDDR5	50W	4x miniDP	2
	Adapter	Cores	Memory	Power	Connectors	Max qty																																																																			
	NVS 810	1024	4GB DDR3	68W	8x miniDP	1																																																																			
	Quadro P400	256	2GB GDDR5	30W	3x miniDP	2																																																																			
	Quadro P620	512	2GB GDDR5	40W	4x miniDP	2																																																																			
	Quadro P1000	640	4GB GDDR5	47W	4x miniDP	2																																																																			
	Quadro P2000	1024	5GB GDDR5	75W	4x DP	2																																																																			
	Quadro P4000	1792	8GB GDDR5	105W	4x DP	1																																																																			
	Geforce GTX 1060	1280	6GB GDDR5	120W	DVI-D DL, HDMI, 3x DP	1																																																																			
	Geforce GTX 1070	1920	8GB GDDR5	150W	DVI-D DL, HDMI, 3x DP	1																																																																			
	Geforce GTX 1080	2560	8GB GDDR5X	180W	DVI-D DL, HDMI, 3x DP	1																																																																			
	Radeon Pro WX 3100	512	4GB GDDR5	50W	DP, 2x miniDP	2																																																																			
	Radeon Pro WX 4100	1024	4GB GDDR5	50W	4x miniDP	2																																																																			
<i>Notes:</i> 1. Quadro P4000, 2x Quadro P2000, Geforce GTX1060/1070/1080 needs 400W PSU. 2. Geforce GTX 1060/1070/1080 are dual-slot width. 3. Geforce GTX 1060/1070/1080 and Radeon Pro WX 3100/4100 are SBO.																																																																									
Storage controllers	Integrated Intel SATA AHCI/RAID controller in chipset, 6Gbps SATA, RAID 0/1/10/5. Four onboard SATA ports for max 4 SATA HDD/SSD/ODD																																																																								
Internal storage bay	Up to five bays with four disk bays plus one slim optical bay, supports up to 3x 3.5" HDD plus 1x 2.5" SSD, or 4x 2.5" SSD																																																																								
	Bay 1 Primary disk bay, 3.5" or 2.5"																																																																								
	Bay 2 2.5" SATA bay, cannot be available when 2nd Quadro P2000 is used																																																																								
	Bay 3 Secondary disk bay, 3.5" or 2.5"																																																																								
	Bay 4 5.25" Flex bay, supports one of the following: - Flex module for optional front eSATA/Thunderbolt/IEEE1394 3rd disk bay, 3.5" or 2.5", removable, via Front Access Storage Enclosure, using SATA 4 connector as eSATA mode 3rd disk bay, 3.5" or 2.5", via 5.25" to 3.5" HDD Kit - M.2 drive, via Front removable M.2 enclosure, also occupies slot 1 or 3																																																																								
	Bay 5 9mm Slim ODD bay																																																																								
Disks	3.5" HDD supports up to 4TB each, 6Gbps SATA, 7.2K 2.5" HDD supports up to 1TB each, 6Gbps SATA																																																																								

Components	Specification
M.2 slot for SSD	Up to 3x M.2 SSD with one dedicated onboard M.2 slot plus two PCIe to M.2 adapters. PCIe to M.2 adapter uses slot 1 or 3. Supports RAID 0/1 with PCH, When used as RAID, M.2 SSD should be installed in onboard M.2 slot and slot 3.
M.2 SSD	Up to one Optane memory per system; Optane memory must work with a HDD or SSD; Optane memory cannot supported on Pentium G5400 models
M.2 slot for Wi-Fi and Bluetooth	M.2 SSD supports up to 1TB each, PCIe 3.0 x4, NVMe, Opal. Optane memory supports 32GB, PCIe 3.0 x2, NVMe, 3D Xpoint
Media reader	One dedicated onboard M.2 slot for optional Intel Wireless-AC 9560, 2x2, 2.4GHz/5GHz (160MHz channels), 802.11ac, Bluetooth 5, up to 1.73Gbps
Network interfaces	Optional SD card reader on most models
Security features	One onboard GbE port via integrated gigabit ethernet Intel i219LM, supports Wake-on-LAN. Optional PCIe ethernet adapters are available
Systems management	Power-on and admin password. Trusted Platform Module, TCG 2.0 compliant. Optional chassis intrusion switch, cable lock, Kensington lock, and pad lock
Base warranty	Intel Active Management Technology 12 on Xeon models, Intel Standard Manageability on other models
HD Audio	US models comes with 3-year limited onsite service with 9x5/NBD. 1 or 3-year limited onsite service with 9x5/NBD in EMEA or other GEOs
Front ports	Intel HD Audio interface with Realtek ALC233 Codec
Rear ports	2x USB 3.1 Gen 1 Type A. 2x USB 3.1 Gen 2 Type A. 1x USB 3.1 Gen 1 Type-C. 1x Mic-in. 1x Combo jack
Optional front ports (on flex module)	2x USB 3.1 Gen 1 Type A. 2x USB 2.0 Type-A. 1x RJ-45. 1x COM. 2x DP. <i>Notes: DP needs Core, Pentium, or -G suffix Xeon processor</i>
Optional rear ports	2x Thunderbolt (USB Type-C), one of two ports supports video-out. 1x eSATA. 1x IEEE1394
Temperature	2x USB 3.1 Type-C. 1x COM. PS/2. 1x Parallel. 1x Thunderbolt. 1x IEEE1394. 1x HDMI. <i>Notes: HDMI needs Core, Pentium, or -G suffix Xeon processor</i>
Altitude	Operating: 41 °F to 104 °F (10 °C to 35 °C) Non operating (no package): 14 °F to 140 °F (-10 °C to 60 °C) Non operating (with package): -40 °F to 140 °F (-40 °C to 60 °C)
Humidity	Operating: -15.2 m (-50 ft) to 3048 m (10 000 ft). Storage: -15.2 m (-50 ft) to 10, 668 m (35 000 ft)
Environmental certification	Operating: 30%~90%, non-condensing Storage (with package): 20%~90%, non-condensing
Power supply	RoHS-compliant. GREENGUARD. EPEAT Gold rating and ENERGY STAR 7 qualified
ISV certifications	Supports one 250W or 400W power supply, 100V - 240V, 92% PSU. Climate Savers Computing Platinum and 80 PLUS Platinum qualified. 400W PSU supports one 6+2-pin aux power connector.
	Please visit www.thinkworkstations.com/isv-certifications/



ThinkStation P330 Tower

