



Make It Yours.

ELITE 350 230V - V4

MPE-3501-ACABN

POWER UP



FEATURES

Active PFC + Forward Topology Design : Constructed with protective measures normally found in high-end power supplies to increase safety and current stability.

High Temperature Resistance : Capable of operating at 40°C under full load allowing a longer lifespan in warmer environments.

Peak Power Tolerance : Can reliably push an additional 50W at peak power load for up to 10 seconds.

80 PLUS White EU 230V Efficiency : Maintains an average efficiency of 85% at typical load.

Durable, Reliable, and Safe : Will perform consistently in whatever environment whether it's high altitudes or ultra humid settings.

3 Year Warranty : This unit comes with a standard limited manufacturing warranty of 3 years from the date of purchase.

PACKAGE INFORMATION

Cable Type	EAN	UPC
US	4719512097113	884102069413
UK	4719512097120	884102069420
EU	4719512097137	884102069437
ST	4719512097144	884102069444
AU	4719512097151	884102069451
BR	4719512097168	884102069468
KR	4719512097175	884102069475
TW	4719512097182	884102069482
JP	4719512097199	884102069499
IN	4719512097205	884102069505
WO	4719512097212	884102069512

Nett Weight	0.002 kg / 0.004 lb
Gross Weight	0.002 kg / 0.004 lb
Package Dimensions	213 x 195 x 96mm (8.39 x 7.68 x 3.78")
Carton Dimensions	500 x 228 x 215mm (19.69 x 8.98 x 8.46")
Unit / Carton	5 pcs
Carton / Pallet	50 pcs

The Elite - v4 power supply unit is a dependable choice for entry level users and system integrators. The quiet 120mm fan, Active PFC, and 3 year warranty deliver a PSU that provides function and resilience you can count on. It's the perfect option for entry level users and work horse systems being housed in extreme conditions. This power supply has been engineered for reliability with a focus on reducing random shutdowns in conditions where power sources are inconsistent and unstable. The Elite - v4 is a complete solution, offering performance and stability at an affordable price.

SPECIFICATIONS

Product Name	Elite 350 230V - v4	
Item Code	MPE-3501-ACABN	
ATX Version	ATX 12V Ver. 2.41	
PFC	Active PFC	
Input Voltage	200 - 240V	
Input Current	4A	
Input Frequency	50 - 60Hz	
Dimensions (L x W x H)	140 x 150 x 86mm	
Fan Size	120mm	
Fan Bearing	Sleeve Bearing	
Efficiency	85% @ Typical Load	
80 PLUS Rating	80 PLUS White EU 230V	
ErP 2014 Lot 3	Yes	
Operating Temperature	40°C	
Power Good Signal	100 - 500 ms	
Hold Up Time	>14ms at 100% load	
MTBF	>100,000 hours	
Protections	OVP / OPP / OTP / SCP / UVP	
Regulatory	TUV / cTUVus / CE / BSMI / FCC / EAC / RCM / KCC / CCC / CB	
Connectors	ATX 24 Pin	x1
	EPS 4+4 Pin	x1
	SATA	x3
	Peripheral 4 Pin	x2
	PCI-e 6+2 Pin	x1

AC INPUT	200 - 240V~ 4A 50 - 60Hz				
DC OUTPUT	+3.3V	+5V	+12V	-12V	+5Vstb
	12A	12A	26A	0.3A	3A
TOTAL POWER	80W		350W	3.6W	15W
	350W				