



47466084



**SCHUKO socket outlet with hinged cover Labelling field, enhanced contact protection, Mounting orientation variable in 45° steps, Berker Q.1/Q.3/Q.7/Q.9**

#### Technical features

#### Architecture

Design according to DIN 49440

#### Main electrical features

Nominal voltage	250 V
Rated current	16 A
Rated voltage	250 V AC

#### Cover, door

- with hinged cover that falls back
- Central cover plate

#### Materials

RAL colour	RAL 9006 - White aluminium
Colour of design line	aluminium
Colour	aluminium optics
Colour	aluminium
Material / workmanship	lacquered
Material	thermoplastic
Surface appearance	velvety

#### Dimensions

Insertion depth	32 mm
-----------------	-------

#### Installation, mounting

- mounting orientation of insert selectable in 45° steps
- with spreader claws

#### Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1

- with plug-in terminals

#### Use

- Labelling field
- enhanced contact protection
- Mounting orientation variable in 45° steps

#### Safety

Protection index IP	IP20
IK protection code against mechanical impacts	02
Enhanced contact protection (child protection)	according to IEC 60884-1
Enhanced contact protection (child protection)	according to VDE 0620-1

- Enhanced contact protection

---

**Identification**

---

Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.3, Berker Q.1

---

**Instructions**

- 
- Specially suited to combinations of several socket outlets if right angle plugs are used. 1140.

Labelling field height designed for 6 mm P-touch strips.

---