



MPG A1000G PCIE5

- Supports Nvidia® GeForce RTX™ 40 Series graphics cards
- Full modular design
- Flat cables
- 80 Plus Gold certified for high efficiency
- 100% all Japanese 105°C capacitor
- Active PFC design
- Industrial level protection with OVP,OCP,OPP,OTP, SCP,UVP
- LLC Half Bridge Topology with DC-DC module design

SPECIFICATIONS

Efficiency Rating	80 PLUS Gold (up to 90%)
Modular	Yes (fully modular)
Fan Size	135 mm
Fan Bearing	Fluid Dynamic Bearing
Dimensions (DxWxH)	150 x 150 x 86 mm
PFC Type	Active PFC
Input Voltage Range	100~240 VAC
Power Watt	1000W
Power Excursion	2000W (*up to 200% of the PSU's rated power for 100µs)
Input Frequency Range	50~60 Hz
Protection	OCP / OVP / OPP / OTP / SCP / UVP
ATX (24 pin)	1
EPS (4+4 pin)	2
PCI-E 5.0 (16 pin)	1 (600W)
PCI-E (6+2 pin)	6
SATA (15 pin)	12
MOLEX (4 pin)	4
FDD (4 pin)	1

MPG A1000G PCIE5

AC INPUT		100-240~, 13A, 50-60Hz			
DC OUTPUT	+5V	+3.3V	+12V	+12V	+5Vsb
	22A	22A	83.5A	0.3A	3A
TOTAL POWER	120W		1000W	3.6W	15W
	1000W				



POWER-SUPPLY
MPG A1000G PCIE5

CONNECTOR						
ATX	EPS	PCI-E 5.0	PCI-E	SATA	Molex	FDD
1	2	1	6	12	4	1