

# MOVE-10PMK2

Order No.: 1000226

## PRODUCTINFOS

**Professional PA speaker system, 350 W, 8 Ω**

- Compact professional full range bass-reflex system
- Cabinet made of birch plywood
- 25 cm (10", FaitalPro 10PR300) bass speaker
- 25 mm (1", 44 mm voice coil, Celestion CDX1-1747) horn tweeter, can be turned by 90°
- Switchable between passive operation and bi-amp active operation
- Neutral sound tuning
- 'Catch & Carry' carrying handle
- M8 threaded inserts for suspended installation
- 2 x NEUTRIK SPEAKON terminal, in/out
- Stand sleeve, robust front grille
- Ball-proof acc. to DIN 18032, Part 3

## TECHNICAL SPECIFICATIONS

| **MOVE-10PMK2** | |
|---|---|
| Active/passive | passive |

**MOVE-10PMK2**

| | |
|---|---|
| Transmission technology | cable |
| Total power rating | 700 W |
| Power rating (RMS) | 350 W |
| Impedance | 8 Ω |
| Frequency range | 55-20,000 Hz |
| System | 2-way bass-reflex |
| Bass speaker | 25 cm (10", FaitalPro 10PR300) |
| Tweeter | dyn. 25 mm<br>mid-high range speaker<br>(1", 44 mm voice coil, Celestion CDX1-1747 ) |
| Number of speakers | 2 |
| Speaker size | 25 cm (10") |
| SPL | 96 dB/W/m |
| Max. rated SPL | 121 dB |
| Beam angle | H: 80°/V: 40°, horn can be turned by 90° |
| Radiation angle, horizontal | 80° |
| Radiation angle, vertical | 40° |
| Housing material | birch plywood |
| Colour | black |
| Admiss. ambient temp. | 0-40 °C |
| Dimensions | 320 x 545 x 350 mm |
| Width | 320 mm |
| Height | 545 mm |
| Depth | 350 mm |
| Weight | 13.9 kg |
| Inputs | 1 x NEUTRIK SPEAKON |
| Outputs | 1 x NEUTRIK SPEAKON par. out |
| Accessories | MOVE-10/BAG |
| Packing dimensions (W x H x L) | 0.32 x 0.545 x 0.35 m |
| Gross weight | 14.48 kg |
| Net weight | 13.9 kg |