

19" Wall Housing Foldable, Depth 600 mm, RAL9005



Abbildung zeigt
Farbvariante RAL 7035
(lichtgrau)

Picture shows
colour variant RAL 7035
(lightgrey)



Description

19" Wall housing 1-part, type Flat Pack
Steel sheet housing screwable, not pre-assembled
Front door fully made of certified safety glass, thickness 4 mm, smoked, tempered, smoothed, antistatic
Front door lockable, Door opening angle 120°
Door stop easy changeable (right/left)
Sidewalls not detachable
Roof prepared for mounting of 2 x single fans
Roof and bottom with cable entry 145 x 70 mm
Inside 2 x 19" profile rails, depth-dajustable, with lateral opening for cable routing
Paint finish RAL7035 light grey / RAL9005 (jet black) / RAL9010 (pure white)
Width 535 mm, depth 450 / 600 mm
Max. load 50 kg (static, equally distributed)
Protection degree IP20
Incl. key
Delivery unassembled in 1 carton with handle

General data

Mounting level	Front and rear
Type of profile rail	L-shaped
Type of ventilation	Passive
Modular spacing	482.6 mm (19 inch)
With roof plate	True

This datasheet was created automatically on 16-08-2022 . Technical changes reserved.

19" Wall Housing Foldable, Depth 600 mm, RAL9005

General data

With earthing	False
With front door	True
With sidewall	True
Demountable	True
Model	With permanent frame
Material	steel
Surface finishing	powder coating
Degree of protection (IP)	IP20
Number of doors	1
Number of cartons	1

Available variants

Article no.	Title	Number of height units	Width	Height	Depth	Max. Load	RAL-number	Colour	Degree of protection (NEMA)
WGF-1904TS.60	19" 06U Wall Housing Foldable, Depth 600 mm, 1-Part, Flat Pack, RAL9005	4	542 mm	237 mm	600 mm	50 kg	9005	black	1
WGF-1906TS.60	19" 04U Wall Housing Foldable, Depth 600 mm, 1-Part, Flat Pack, RAL9005	6	542 mm	326 mm	600 mm	50 kg	9005	black	1
WGF-1909TS.60	19" 09U Wall Housing Foldable, Depth 600 mm, 1-Part, Flat Pack, RAL9005	9	542 mm	458 mm	600 mm	50 kg	9005	black	1
WGF-1912TS.60	19" 15U Wall Housing Foldable, Depth 600 mm, 1-Part, Flat Pack, RAL9005	12	542 mm	592 mm	600 mm	50 kg	9005	black	1
WGF-1915TS.60	19" 12U Wall Housing Foldable, Depth 600 mm, 1-Part, Flat Pack, RAL9005	15	542 mm	726 mm	600 mm	50 kg	9005	black	1
Article no.	Title	Number of height units	Width	Height	Depth	Max. Load	RAL-number	Colour	Degree of protection (NEMA)
WGB-1906TS.45	19" 06U Wall Housing Basic, Depth 450 mm, 1-Part, Flat Pack, RAL9005								

This datasheet was created automatically on 16-08-2022 . Technical changes reserved.



19" Wall Housing Foldable, Depth 600 mm, RAL9005

WGB-1909TS.45	19" 09U Wall Housing Basic, Depth 450 mm, 1-Part, Flat Pack, RAL9005								
WGB-1912TS.45	19" 12U Wall Housing Basic, Depth 450 mm, 1-Part, Flat Pack, RAL9005								
WGB-1915TS.45	19" 15U Wall Housing Basic, Depth 450 mm, 1-Part, Flat Pack, RAL9005								

accessory

WGB-PRO06	19" Mounting Rails for Wall Housing BASIC
EK631DE.3	19" 1U Socket Strip 7 x CEE 7/3 with Surge Protection
EK631DE.2	19" 1U Socket Strip 8 x CEE 7/3 with Switch
EK631DE.1	19" 1U Socket Strip 9 x CEE 7/3 without Switch
EK504.2V2	Power Cable CEE7/7 90° - C13 180°, Black

spare part

WGB-TUR06	Front Door for Wall Housing BASIC
-----------	-----------------------------------