

DATASHEET

305039/ 304978

Brandson DC Tower Fan

TECHNICAL INFORMATION

BASIC INFORMATION

Dimensions	• Height: Approx. 86 cm • Diameter: Device Ø18 cm • Air outlet: 47 cm (Height) x Width (7cm) • Blade: Ø 9 cm x 47 cm Height
Weight	• 2,8 kg (Tower fan) • 37 g (Remote control)
Cable length	170 cm
Material	ABS
Colours	305039 (white) / 304978 (black)
Scope of delivery	• Brandson DC Tower Fan • IR Remote Control • User Manual

DETAILED DESCRIPTION

Voltage supply	220-240V ~ 50Hz
Consumption	Max. 30 W
Air outlet	2934 m³/h
Stand-by consumption	0.48 W
Plug type	EURO plug type C CEE 7/16
Operating noise	• Max. 38 dBA in level 1 • Up to approx. 48 dBA in level 9
Speed levels	Low / Medium / High
Operating modes	Speed / OSC / Timer
Oscillation mode	Switchable 60° oscillation
Timer mode	Integrated auto power off/timer function (from 0 – 9 hours)
Acoustic signal	Buzzer beep when pressing the buttons
Safety class	II
GS mark	✓



DATENBLATT

305039/ 304978

Brandson DC Turm-Ventilator

TECHNISCHE INFORMATIONEN

BASIS-INFORMATIONEN

Abmessungen	• Höhe: ca. 86 cm • Durchmesser: Ø 18 cm • Luftauslass: 47 cm (Höhe) x Breite (7cm) • Rotorblatt: Ø 9 cm x 47 cm Höhe
Gewicht	• 2,92 kg (Ventilator) • 36 g (Fernbedienung)
Kabellänge	170 cm
Material	ABS
Farben	305039 (weiß) / 304978 (schwarz)
Lieferumfang	• Brandson DC Turmventilator • IR-Fernbedienung • Bedienungsanleitung

DETAILLIERTE SPEZIFIKATIONEN

Spannungsversorgung	220-240V ~ 50Hz
Luftdurchlass	2934 m³/h
Leistungsaufnahme	Max. 30 W
Stand-By-Verbrauch	0,48 W
Steckertyp	EURO-Stecker Typ C CEE 7/16
Betriebsgeräusch	• Max. ca. 38 dBA in der Stufe 1 • Bis zu ca. 48 dBA in der Stufe 9
Geschwindigkeitsstufen	Low / Medium / High
Betriebs-Modi	Speed / OSC / TIMER
Oszillation-Modus	Zuschaltbare 60° Oszillation
Timer-Modus	Integrierte Auto Power Off / Timerfunktion (von 0 – 9 Stunden)
Signalton	Summer-Signalton bei Betätigen der Tasten
Schutzklasse	II
GS-Siegel	✓

