

6130763512



**Change-over switch insert with rocker surface-mounted/flush-mounted Berker W.1, polar white matt**

Technical features

**Architecture**

| | |
|---|---|
| Type of control unit | single rocker |

**Main electrical features**

| | |
|---|---|
| Nominal voltage | 250 V |
| Rated voltage | 250 V AC |

**Electric current**

| | |
|---|---|
| Switching current | 10 AX |

**Materials**

| | |
|---|---|
| RAL colour | RAL 9010 - Pure white |
| Colour of design line | polar white |
| Colour | white |
| Material | thermoplastic |
| Surface appearance | matt |

**Dimensions**

| | |
|---|---|
| Depth | 42 mm |
| Height | 70 mm |
| Width | 70 mm |

**Installation, mounting**

- for screw fastening

**Connection**

| | |
|---|---|
| Type of connection | Quickconnect |

- with plug-in terminals

**Safety**

| | |
|---|---|
| Protection index IP | IP55 |

**Use conditions**

| | |
|---|---|
| Operating temperature | -40 … 30 °C |
| Storage/transport temperature | -50 … 50 °C |

**Identification**

| | |
|---|---|
| Application, usage | Surface-mounted wet-room installation |
| Main design line | Berker W.1 |

**Instructions**

- Pins of quick-release lock made of ZAMAK
- Inserts will only reach the degree of protection IP55 if mounted with a housing surface mounted or frame for flush-mounted installation.