



ALPHA 160, wall-mounted cabinet, IP44, Protection class 2, H: 500 mm, W: 300 mm, T: 140 mm, RAL 9016

| Model                                                |                      |                           |
|------------------------------------------------------|----------------------|---------------------------|
| product brand name                                   | ALPHA 160            |                           |
| product designation                                  | Wall-mounted cabinet |                           |
| design of the product                                | Surface mounting     |                           |
| surface processing                                   | powder-coated        |                           |
| Protection class                                     |                      |                           |
| protection class IP                                  | IP43                 |                           |
| operating resource protection class                  | Safety class 2       |                           |
| suitability for interaction / lightning protection   | Yes                  |                           |
| suitability for use / for outside use                | No                   |                           |
| Appearance                                           |                      |                           |
| RAL color number                                     | 9016                 |                           |
| product component                                    |                      |                           |
| • cable entry                                        |                      |                           |
| • mounting plate                                     | No                   |                           |
| product extension / optional / side-by-side mounting | No                   |                           |
| Mechanical Design                                    |                      |                           |
| height                                               | 500 mm               |                           |
| width                                                | 300 mm               |                           |
| depth                                                | 140 mm               |                           |
| installation depth                                   | 140 mm               |                           |
| net weight                                           | 4.8 kg               |                           |
| material / of the enclosure                          | Steel                |                           |
| General Product Approval                             |                      | Declaration of Conformity |
|                                                      |                      | Test Certificates         |

[Miscellaneous](#)



EG-Konf.

[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)

| Test Certificates | other |
|-------------------|-------|
|-------------------|-------|

[Miscellaneous](#)

[Miscellaneous](#)

## Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8GK1032-1KK11>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8GK1032-1KK11>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=8GK1032-1KK11](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8GK1032-1KK11)

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

