



SPECIFICATIONS

PANEL SIZE	26.5"
PANEL RESOLUTION	2560 x 1440 (WQHD)
REFRESH RATE	144Hz
RESPONSE TIME	0.03ms (GtG)
PANEL TYPE	QD-OLED
BRIGHTNESS (NITS)	SDR: 200 HDR: 400
VIEWING ANGLE	178°(H) / 178°(V)
ASPECT RATIO	16:9
CURVATURE	Flat
CONTRAST RATIO	1500000 : 1
DCR	N/A
Signal Frequency	96~232 KHz(H) / 48~144 Hz(V)
ADOBE RGB / DCI-P3 / SRGB	98% / 99.07% / 138.39% (CIE1976)
ACTIVE DISPLAY AREA (MM)	590.42(H) x 333.72(V)
PIXEL PITCH (H X V)	0.2292(H) x 0.2292(V)
SURFACE TREATMENT	Anti-Glare Low Reflection
DISPLAY COLORS	1.07B
COLOR BIT	10 bits
HDR SUPPORT	HDR Ready
VIDEO PORTS	2x HDMI™ 2.0b (WQHD@144Hz) 1x DisplayPort 1.4a 1x Type-C (DP alt.) w/ 15W PD
Audio Interface	1x Headphone-out
KENSINGTON LOCK	Yes
SPEAKER	2x 2.5W
VESA MOUNTING	100 x 100 mm
POWER TYPE	Internal Power Board
POWER INPUT	100~240V, 50/60Hz
DYNAMIC REFRESH RATE TECHNOLOGY	NVIDIA G-SYNC Compatible AMD FreeSync™
ADJUSTMENT (TILT)	-5° ~ 20°
ADJUSTMENT (SWIVEL)	-30° ~ 30°
ADJUSTMENT (PIVOT)	-90° ~ 90°
ADJUSTMENT (HEIGHT)	0 ~ 150 mm
Dimension with Stand (W x D x H)	611.1 x 200.6 x 560.3 mm (24.06 x 7.90 x 22.06 inch)
Dimension without Stand (W x D x H)	611.1 x 73.0 x 356.3 mm (24.06 x 2.87 x 14.03 inch)

FEATURES



QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming.



OLED Care 2.0

MSI has developed a more advanced version to provide several care services and significantly reduce the chances of OLED screen aging.



Type-C Display & Power Delivery

Built-in an USB Type-C connection allows you to effortlessly connect to and charge your devices.



VisiClarity

VisiClarity masterfully integrates Anti-Glare Low Reflection technology to eliminate distracting light, providing a window of pure, undisturbed depth.



EyesErgo

An eye care solution designed with ergonomics in mind.



Less Blue Light PRO

Use a hardware solution to reduce the light emission in the blue-violet region of the blue light spectrum (wavelength 415 to 455 nm).



0.03ms Fast Response Time

Eliminate screen tearing and choppy frame rates with 0.03ms GtG response time.



PIP/PBP Technology

Display and view dual contents simultaneously with multi-screen functionality.

CARTON DIMENSION (W X D X H)	770 x 142 x 478 mm (30.31 x 5.59 x 18.82 inch)
WEIGHT (NW / GW)	6 kg (13.23 lbs) / 9 kg (19.84 lbs)
ACCESSORIES	1x DisplayPort Cable (1.4a), 1x Power Cord, 1x Quick Guide, 4x VESA Wall Mount Screw, 1x VESA Plate, 4x VESA Plate Screw, VESA Adapter Kit, 1x Cable Clip, 1x Fiber Cloth, Color Report
Note	HDMI™: 2560 x 1440 (Up to 144Hz) DisplayPort: 2560 x 1440 (Up to 144Hz) Type-C: 2560 x 1440 (Up to 144Hz) Support: HDMI™ CEC/ MSI Power Link, OLED Care 2.0, FW Update, PIP/PBP, Delta-E (ΔE) ≤ 2; Non-Support: KVM 1.0

CONNECTIONS



- 1. Headphone-out
- 2. 2x HDMI™ 2.0b (WQHD@144Hz)
- 3. 1x DisplayPort 1.4a
- 4. 1x Type-C (DP alt.) w/ 15W PD
- 5. Kensington Lock
- 6. AC-in