



S12-100-230V

Technical data page 18-7.

S12-100-/200-/110-

1- and 2-pole 16 A/250 V AC

Modular devices for DIN 60715 TH35 rail mounting with manual control and switch position indicator.
1 module = 18 mm wide, 55 mm deep.
100% time on. Control power demand 5–6 W only.
Contacts 1 NO, 2 NO, 1 NO + 1 NC.
Contact gap 3 mm. Spacing of control connections/contact > 6 mm.
Devices for 25 A XS12, page 18-5.
Retrofittable auxiliary contact KM12, page 18-3.
The pin-compatible ES12DX-UC, ES12-200-UC and ES12-110-UC electronic impulse switches can also be used.
Their universal control voltage UC covers the voltage ranges of 8 to 253 V AC at 50-60 Hz and 10 to 230 V DC.

S12-100-12V	1 NO 16 A	EAN 4010312100455	**25,50 €/pc.**
S12-100-230V	1 NO 16 A	EAN 4010312100479	**25,50 €/pc.**
S12-100-8V, 24V, 12V DC, 24V DC	1 NO 16 A		**27,50 €/pc.**
S12-200-12V	2 NO 16 A	EAN 4010312100530	**31,90 €/pc.**
S12-200-230V	2 NO 16 A	EAN 4010312100554	**32,50 €/pc.**
S12-200-8V, 24V, 12V DC, 24V DC	2 NO 16 A		**34,10 €/pc.**
S12-110-12V	1 NO + 1 NC 16 A	EAN 4010312100493	**31,90 €/pc.**
S12-110-230V	1 NO + 1 NC 16 A	EAN 4010312100516	**32,50 €/pc.**
S12-110-8V, 24V, 12V DC, 24V DC	1 NO + 1 NC 16 A		**34,10 €/pc.**