



## ColorEdge CS2740

The ColorEdge CS2740 is the first CS series monitor to implement 4K UHD resolution (3840 x 2160). The remarkable detail on this 27" monitor ensures high resolution photos and other content are displayed crisply. This makes the monitor versatile for photos, video editing, design and other types of creative work up to 4K, all while meeting the varying needs and budget of all EIZO users.


**Size:** 27.0" (68.5 cm)

**Resolution:** 3840 x 2160 (16:9 aspect ratio)

**Pixel Density:** 164 ppi

**Colour:** USB Type-C, DisplayPort, HDMI: 1.07 billion from a palette of 278 trillion. DVI: 16.77 million from a palette of 278 trillion


**Warranty:** Five Year On-site



5 | Year on site Warranty  
★★★★★

# ColorEdge CS2740

Dimensions (Unit: mm)



## Panel

**Type:** IPS

**Backlight:** Wide-Gamut LED

**Size:** 27.0" / 68.5 cm

**Native Resolution:**  
3840 × 2160 (16:9 aspect ratio)

**Viewable Image Size (H x V):** 596.2 × 335.3 mm

**Pixel Pitch:** 0.155 × 0.155 mm

**Pixel Density:** 164 ppi

**Greyscale Tones:** USB Type-C, DisplayPort, HDMI: 1,024 tones (a palette of 65 thousand tones) DVI: 256 tones (a palette of 65 thousand tones)

**Display Colours:** USB Type-C, DisplayPort, HDMI: 1.07 billion from a palette of 278 trillion. DVI: 16.77 million from a palette of 278 trillion

**Viewing Angles (H / V, Typical):** 178°, 178°

**Brightness (Typical):** 350 cd/m<sup>2</sup>

**Recommended Brightness for Calibration:**  
120 cd/m<sup>2</sup> or less

**Contrast Ratio (Typical):** 1000:1

**Response Time (Typical):** 10 ms (grey-to-grey)

**Wide Gamut Coverage (Typical):**  
Adobe RGB: 99%

## Video Signals

**Input Terminals:** USB Type-C (DisplayPort Alt Mode, HDCP 1.3), DisplayPort (HDCP 1.3), HDMI (Deep Colour, HDCP 1.4), DVI-D (HCP 1.4)

**Digital Scanning Frequency (H / V):**  
USB Type-C, DisplayPort, DVI: 26 - 89 kHz, 23 - 61 Hz (VGA Text: 69 - 71 Hz)  
HDMI: 15 - 89 kHz, 23 - 61 Hz

## USB

**Function:** 2 ports for monitor control  
3-port USB hub

**Standard:** USB 3.1

## Power

**Power Requirements:**  
AC 100 - 240 V, 50 / 60 Hz

**Maximum Power Consumption:** 168 W

**Typical Power Consumption:** 36 W

**Power Save Mode:** 1 W or less

**Standby Mode:** 1 W or less

## Features & Functions

**Digital Uniformity Equaliser:** Yes

**Preset Modes:** Colour Mode  
(User, Adobe RGB, sRGB, Calibration)

## Physical Specification

**Dimensions (Landscape, W x H x D):**  
638 x 404.1 - 559.1 x 265 mm

**Dimensions (Portrait, W x H x D):**  
378.2 x 649 - 689 x 265 mm

**Dimensions (Without Stand, W x H x D):**  
638 x 378.2 x 75 mm

**Net Weight:** 10.3 kg / 22.7 lbs

**Net Weight (Without Stand):** 6.7 kg / 14.7 lbs

**Height Adjustment Range:** 155 mm

**Tilt:** 35° Up, 5° Down

**Pivot:** 90°

**Swivel:** 344°

**Hole Spacing (VESA Standard):**  
100 x 100 mm

## Environmental Requirements

**Temperature:** 0 - 35°C

**Humidity (R.H., non condensing):** 20 - 80 %

## Certifications & Standards

(Please contact EIZO for the latest information)  
CB, CE, TUV/GS, cTUVus, FCC-B, Canadian ICES-003-B, VCCI-B, TUV/Ergonomics, RCM, RoHS, WEEE, EAC, Energy Labelling of televisions.

## Included Cables

DisplayPort (2m), HDMI (2m)  
AC power cord, USB TYPE C (2m)

## Warranty

Five years on-site<sup>1,2</sup>

<sup>1</sup> Usage time is limited to 30,000 hours.

<sup>2</sup> Free from bright sub-pixels for 6 months for the date of purchase. With current LCD technology, a panel may contain a limited number of missing or flickering pixels.

## EIZO Limited

1 Queens Square, Ascot Business Park, Lyndhurst Road, Ascot, Berkshire, SL5 9FE. UK

## Website:

[www.EIZOcolour.com](http://www.EIZOcolour.com)

## Telephone:

+44 (0) 1344-317-480