

EUROLITE LED FE-1750 Hybrid Laserflower

4in1 LED effect spotlight with derby, washlight, laser (2M) and strobe

Art. No.: 51741083

GTIN: 4026397642773



List price: 272.51 €

incl. 19% VAT.

Features:

- 2 laser diodes project hundreds of red and green laser beams
- Dimmer electronic; color blend stepless
- Laser; UV effect; multi beam effect; flower effect; strobe effect
- 7 integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; Light Captain; Colorchief
- With a beam angle of 25°
- With mounting bracket
- Monochrome 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer; small rental
- Application possibility: Suspended; on stand
- laser**
- Laser class 2M
 does not require additional protective measures or appointment of a laser safety officer
- spotlight**
- 8 powerful LEDs 4 W high-power 4in1 QCL RGB/UV (homogenous color mix)
 spots controlled separately
- light effect**
- 6 powerful LEDs 0,2 W SMD 5050 cold white (CW)
 lighting effects controlled separately
- strobes**

Logistic

EAN / GTIN: 4026397642773

Weight: 5,15 kg

Length: 0.35 m

Width: 0.34 m

Height: 0.28 m

- 12 powerful LEDs 3 W high-power 6in1 HCL RGBWA/UV
 lighting effects controlled separately

Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x remote control

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	60 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Fuse:	5 x 20 mm, T 0,5 A fuse replaceable
Lamp type:	LED lamp
DMX channels:	4; 13
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; Light Captain; Colorchief
Beam angle:	25°
Beam angle (1/2 peak):	25°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	Monochrome 4 digit 7-segment LED display
Dimensions:	Width: 31,5 cm Depth: 19 cm Height: 33 cm
Weight:	4,60 kg
Noise classification:	Class 2 (slight noise)
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Light effect	
LED type:	6 x 0,2 W SMD 5050 cold white (CW)
Strobes	
LED type:	12 x 3 W high-power 6in1 HCL RGBWA/UV
Flash rate:	0 - 20 Hz
Laser	
Laser class:	2M
Laser color:	R/G

Laser module:	Red (R) 100 mW 650nm Green (G) 50 mW 532nm
Spotlight	
LED type:	8 x 4 W high-power 4in1 QCL RGB/UV (homogenous color mix)