


41496086

SCHUKO socket outlet with labelling field, enhanced contact protection, Screw-in lift terminals, Berker Q.1/Q.3/Q.7/Q.9, anthracite velvety, lacquered

Technical features

Architecture

Design	according to DIN 49440

Main electrical features

Nominal voltage	250 V
Rated current	16 A
Rated voltage	250 V AC

Cover, door

- Central cover plate

Materials

RAL colour	RAL 7021 - Black grey
Colour of design line	anthracite
Colour	anthracite charcoal grey
Colour	anthracite
Material / workmanship	lacquered
Material	duroplastic
Surface appearance	velvety

Dimensions

Insertion depth	32 mm

Installation, mounting

- with spreader claws

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1

- with screw-in lift terminals

Use

- with labelling field
- enhanced contact protection
- Screw-in lift terminals

Safety

Protection index IP	IP20
IK protection code against mecanical impacts	02
Enhanced contact protection (child protection)	according to IEC 60884-1
Enhanced contact protection (child protection)	according to VDE 0620-1

- Enhanced contact protection

Identification

Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.3, Berker Q.1

Instructions

- Labelling field height arranged for P-touch strips 6 mm.