

DIGITUS 4 Port Fast Ethernet Network Switch, Industrial, Unmanaged, 1 SFP Uplink

DN-651130

EAN 4016032485490



Industrial 4+1 Port Fast Ethernet Switch Unmanaged, 4 RJ45 Ports 10/100 Mbps

DN-651130 is a Industrial Fast-Ethernet-Switch with 4-Port 10/100Mbps RJ45 +1 Port 100Mbps base-FX. The industrial graded switch has the operating temperature of -40°C ~ 80°C, has the super firmness can adapt to all kinds of harsh environment, can also be conveniently placed in the compact space of the control box. The installation characteristics of the guide rail, wide temperature operation, IP40 protection class housing and LED indicator light make the DN-651130 a plug and play industrial grade device, providing a reliable and convenient solution for users to network their Ethernet devices.

DN-651130 is a industrial graded 4+1 -Port Ethernet Switch, provides non-blocking wire-speed performance in harsh industrial environment.

- 4-port 10/100Base-Tx RJ45 with autonegotiation and auto-MDI/MDI-X function
- 1-port 100Base-Fx interface SFP
- 12V to 48V DC, redundant power input
- -40°C to 80°C operating temperature
- IP40 aluminum housing
- Supports 6KV DC Ethernet ESD protection
- Supports 6KV DC EFT protection for power line
- Free Fall, Shock and Vibration Stability
- DIN-rail Installation
- Performance Specification: Bandwidth: 1.6Gbps, Packet Buffer Memory: 1Mbit, Packet Forwarding Rate: 1.2Mpps, MAC Address Table: 2K
- Flow Control: Back pressure for half duplex, IEEE 802.3x pause frame for full duplex
- LED Indicator: Power: Red, Fiber: Link 2(Green), Ethernet: Yellow

- Power Input: 12 to 48V DC redundant power
- Power Consumption: < 3 watts
- Network Protocols: IEEE802.3 10BASE-T; IEEE802.3i 10Base-T; IEEE802.3u; 100Base-TX/FX;
- Industry Standard: FCC CFR47 Part 15, EN55022/CISPR22, Class A, IEC61000-4-2 (ESD): ±8kV (contact), ±12kV (air), IEC61000-4-3 (RS): 10V/m (80~1000MHz), IEC61000-4-4 (EFT): Power Port: ±4kV; Data Port: ±2kV, IEC61000-4-5 (Surge): Power Port: ±2kV/DM, ±4kV/CM; Data Port: ±2kV, IEC61000-4-6 (CS): 3V (10kHz-150kHz); 10V (150kHz-80MHz), IEC61000-4-16 (Common mode conduction): 30V (cont.), 300V (1s)
- Dimensions (W x D x H): 118 x 92.4 x 40 mm
- Weight: Product Weight: 0.48KG
- Working Environment: working temperature: -40°C~80°C; Storage temperature: -40°C~80°C
- Relative Humidity: 5%~95 % (no condensation)
- Relative Humidity: 5%~95 % (no condensation)
- Relative humidity: 5% to max. 95% (non-condensing)
- Number of ports: 4
- Ethernet speed: Fast Ethernet
- Industrial usage: yes
- Installation type: DIN rail
- Managed: no
- Number of ports (Uplink): 1
- Outdoorsuitable: no
- PoE (Power over Ethernet): no
- Protection against vandalism: no
- Uplink port connection: SFP
- VLAN: no

Package contents

- 4+1 Port-Ethernet-Switch
- Manual

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	24	13.00	22.50	39.00	46.50	40,803.80
Packaging Unit Inside	1	0.54	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.54	5.40	13.50	16.50	1,202.85
Net single without Packaging	1	0.46	3.40	8.60	12.80	0.00

More images:

