

Motion detector

IS 360-3

EAN 4007841006525



Functional description

The infrared ceiling sensor that satisfies all demands and is really simple to install. Simply genius: Sophisticated technology that is installed and configured in just a few steps thanks to a clever installation concept. Thanks to its three pyro sensors, the infrared surface-mounted sensor has an impressive 360° angle of coverage and a range of up to 12 metres. The detection zone can be set to any requirement by fitting shrouds. The IS 360-3 is available in black and white.

Technical specifications

Model	Movement sensor
Sensor type	Passive infrared
Accessories	incl. faceplate
Detection angle	360° with 90° angle of aperture
Reach	12 m max.
Application	indoors and outdoors
Installation	Ceiling
Dimensions(w x h x d):	57 x Ø 121 mm
Voltage	220 - 240 V, 50/60 Hz
Output	max. 2000 W, max. 8 fluorescent lamps / LED lamps C < 176 µF
Capability of masking out individual segments	Yes
Adjustment range	± 10° precision adjustment of lens
Teach-function for response value luminosity	No
Time setting	5 sec. - 15 min.
Manual override	selectable, 4h
Degree of protection (IP)	IP54
Protection class	II
Temperature	-20-50 °C
Housing	UV-resistant plastic
Version	Black