

AGV 17-125 XE | 1750 W angle grinder with AVS



- Powerful, 1750 W PROTECTOR-MOTOR with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool.
- Constant power electronics with soft start for smooth start up.
- Line lock out function to prevent automatic start up after power breakdown.
- Thermal overload protection to prevent overheating.
- Safety clutch to protect the user from kickback injuries.
- FIXTEC™ nut for tool-free disc change.
- Burst resistant and tool-free safety guard for best user protection and fast adjustment.

	AGV 17-125 XE
Anti-kickback protection	Yes
AVS Anti-Vibration System	Yes
Brake	No
Disc diameter (mm)	125
Line lock out function	Yes
Max. cutting depth (mm)	33
No load speed (rpm)	2600 - 11,000
Power input (W)	1750
Sound power level (dB(A))	97.5
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	86.5
Sound pressure level uncertainty (dB(A))	3
Spindle size	M 14
Standard equipment	Quick release safety guard, AVS side handle, FIXTEC flange nut, flange nut, 4 m cable
Supplied in	No kitbox or bag supplied
Switch type	Trigger lock-on switch
Variable speed	Yes
Vibration grinding (m/s ²)	9.4
Vibration grinding uncertainty (m/s ²)	1.5
Vibration sanding (m/s ²)	3
Vibration sanding uncertainty (m/s ²)	1.5
Weight (kg)	2.8