

Product data sheet

Standard automatic switch 1.1 m - IP 44



Reference number

A 17180 WU SW

Standard automatic switch 1.1 m

for LB Management inserts "light" ref.-no.: 1701 SE, 1704 ESE, 1702 SE, 1710 DE, 1711 DE, 1713 DSTE, 1723 NE, 1708 IE
IP 44 suitable only for indoor installation

Intended use

- Automatic switching of lighting depending on the thermal movement and ambient brightness
- Operation with flush-mounted insert for switching or dimming or satellite insert 3-wire of the LB Management
- Wall installation on flush-mounted insert

Product characteristics

- Extension of the detection area in combination with 3-wire satellite insert
- Operation with 2-wire or 3-wire satellite insert, rotary satellite insert or push-button
- Selectable brightness threshold
- Selectable sensitivity
- Fixed run-on time
- Switch on with last saved brightness or saved switch-on brightness, with dimming insert
- Switch-on brightness can be saved permanently via satellite unit, with dimmer insert
- Dimming light via satellite unit, with dimmer insert
- Screen for limiting the detection area

Technical data

Ambient temperature:	-20 ... +45 °C
Storage/transport temperature:	-25 ... +70 °C
Brightness setting:	approx. 5 ... 1,000 lx (and daytime operation)
Sensitivity:	25, 50, 75, 100 %
Shut-off delay:	approx. 2 min
Mounting height:	1.10 m
Detection angle:	180°
Detection range	
Sensitivity 25 %:	max. 8 m
Sensitivity 50 %:	max. 13 m
Sensitivity 75 %:	max. 26 m
Sensitivity 100 %:	max. 32 m

Thermoplastic (breakproof) high-gloss

Colour:
black

Material:
thermoplastic

IP Protection level IP 44 is ensured with sealing gasket ref.-no. 551 WU and "IP 44 frame" of the respective design range.