

## Rack PDU, Basic, Zero U, 10A,230V, (15)C13 AP9568

Call for More Information 0800 2799254



- Reliable rack power distribution
- Includes: Installation Guide, Rack Mounting Brackets, Toolless Mounting Kit

### Output

Nominal Output Voltage	208V, 230V
Maximum Total Current Draw	10
Output Connections	(15) IEC 320 C13

### Input

Nominal Input Voltage	120V, 200V, 208V, 230V, 240V
Input frequency	50/60 Hz
Input Connections	IEC-320 C14
Cord Length	1.98meters
Acceptable Input Voltage	100-240VAC
Number of Power Cords	1
Load Capacity	2300VA
Maximum Input Current	10A

### Physical

Maximum Height	610MM, 61.0CM
Maximum Width	44MM, 4.4CM
Maximum Depth	44MM, 4.4CM
Net Weight	2.0KG
Shipping weight	2.73KG
Shipping Height	648MM, 64.8CM
Shipping Width	178MM, 17.8CM

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

## Technical Specifications

Rack PDU, Basic, Zero U, 10A,230V, (15)C13 | AP9568 | Downloaded on 08/11/2020 (EST)

Physical	
Shipping Depth	152MM, 15.2CM
Color	Black

Environmental	
Operating Temperature	0 - 45 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000meters

Conformance	
Approvals	cUL Listed, CE, GOST, Queensland Australia, UL Listed, VDE
Standard warranty	2 years repair or replace

Sustainable Offer Status	
RoHS	Compliant
REACH	REACH: Contains No SVHCs

**Disclaimer:** Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.