



WALL-04T/WS

Order No.: 0163570

PRODUCTINFOS

Pair of 2-way PA speaker systems

- 100 V wall speaker with plastic cabinet in white
- 4 power taps as well as switchable to 8 Ω operation
- 10 cm (4") bass-midrange speaker and 12 mm ($\frac{1}{2}$ ") dome tweeter
- High sound quality and speech intelligibility
- Mounting bracket for pivoting and tilting
- Connecting terminal with cover

TECHNICAL SPECIFICATIONS

WALL-04T/WS

Active/passive	passive
Transmission technology	100 V
Total power rating	60 W
Power rating (RMS)	16/8/4/2 W (100 V) 30 W (8 Ω)

WALL-04T/WS

Impedance	8 Ω
Frequency range	90-20,000 Hz
System	2-way
Bass speaker	10 cm (4") bass-midrange speaker
Tweeter	12 mm (½") dome tweeter
Number of speakers	2
Speaker size	4"
SPL	87 dB/W/m
Max. rated SPL	100 dB
Housing material	plastic
Colour	white
Mounting device	mounting bracket
Protection class	IP65
Admiss. ambient temp.	0-40 °C
Dimensions	130 x 197 x 164 mm (with bracket)
Width	130 mm
Height	197 mm
Depth	164 mm
Weight	1.8 kg
Inputs	spring-load. speaker term.
Other features	for pivoting and tilting
Packing dimensions (W x H x L)	0.155 x 0.22 x 0.33 m
Gross weight	3.82 kg
Net weight	3.51 kg