

A D A P T E R

Type C Series

Model : FSP060-D1AR4



Specification

- Compliance with newest USB 3.1 PD device
- 1 inch height design
- 5 different output voltage auto select
- Includes ground wire for safety
- High power output density for up to 6 w/in3
- Full protections OCP,OVP, SCP,OPP,OTP

Rating Information

	Default Output	Second Output	Third Output	Fourth Output	Fifth Output	Regulation
Output Rating	5V / 3A	9V / 3A	12V / 3A	15V / 3A	20V / 3A	± 5%

EAN / UPC Code

Model	EAN Code	UPC Code
FSP060-D1AR4	471322452154 6	84568501006 3

Specifications Information

Specification	NB C 60
Model	FSP060-D1AR4
Tips Type	Type C
PFC	Active PFC > 0.9
Input Voltage	100-240Vac
Input Current	2.0A
Input Frequency	50-60Hz
Output Power Capacity	60W
Output Current	5V / 3A 9V / 3A 12V / 3A 15V / 3A 20V / 3A
Efficiency	> 88%@20V output [115V] DOE Level VI [230V] Erp Tier 2
Protection	SCP / OVP / OPP / OTP /OCP
Safety	CB/CE/FCC/TUV/UL
Weight	232g
Dimension(L X W X H)	92 X 77.3 X 25.5 mm

Packing Information

Shipping Dimension	Master Package	Master Carton Dimension	Pallet Quantity
202X115X62 mm	20pcs	457X395X284 mm	700pcs