



PROJECTOR

LSD300W-ST

Key Features

- Advanced 3rd-gen LED tech with a 60,000-hour lifespan for low maintenance and reliable performance
- 0.49 short throw & 360° projection ensure glare-free visuals and flexible installation anywhere
- IP5X-sealed DLP engine ensures a dustproof, filter-free system for consistent color performance
- LAN control for easy remote and centralized management
- User-friendly setup with instant on/off, H/V keystone correction, and 4-corner adjustment



Product Description

The LSD300W-ST is a short-throw LED projector from ViewSonic, designed specifically for education environments. It delivers 3,300 ANSI Lumens of brightness and WXGA resolution, making it ideal for small to medium-sized classrooms. With a 0.49 short-throw ratio, it projects a 100" image from just 1.06 meters, ensuring clear visuals with minimal glare and shadows. Powered by third-generation LED technology, this lamp-free projector offers a 60,000-hour lifespan, helping reduce maintenance costs and eliminate the use of mercury-based lamps. Its sealed DLP engine ensures dustproof, filter-free operation with long-lasting color performance. Designed for intuitive operation, the LSD300W-ST features instant power on/off, horizontal/vertical keystone correction, 4-corner adjustment, and 360° projection, making it suitable for versatile installations—including floor projection in education settings. A built-in LAN control interface streamlines centralized device management and supports integration with Crestron, Extron, and ATEN systems.

- | | |
|------------------|-----------------------------|
| 1. LED Indicator | 8. Audio In |
| 2. Keypad | 9. HDMI |
| 3. Power | 10. USB-A(SV/1.5A, Service) |
| 4. Focus Ring | 11. Computer In |
| 5. Front IR | 12. Monitor Out |
| 6. Lens | 13. RS232 |
| 7. Audio Out | 14. RJ45 (LAN Control) |

Visit Us

www.viewsonic.com

SPECIFICATION

Projection System:	0.65" WXGA
Native Resolution:	1280x800
Brightness:	3300 (ANSI Lumens)
Brightness (Center Lumens):	3700
Contrast Ratio:	3000000:1
Display Color:	1.07 Billion Colors
Light Source Type:	LED
Light Source Life (hours) with Normal Mode:	60000
Lens:	F=2.6, f=6.9mm
Projection Offset:	110%+/-5%
Throw Ratio:	0.49
Optical Zoom:	Fixed
Digital Zoom:	0.8x-2.0x
Image Size:	60"-300"
Throw Distance:	0.63-1.58m (87"@0.92m)
Keystone:	H: +/-40° , V: +/-40°
Audible Noise (Normal):	32dB
Audible Noise (Eco):	27dB
Input Lag:	16ms
Resolution Support:	VGA(640 x 480) to FullHD(1920 x 1080)
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Horizontal Frequency:	15K-102KHz
Vertical Scan Rate:	23-120Hz
Interactive Camera:	Optional (vTouch-10s)

INPUT

Computer in (share with component):	1
HDMI:	1 (HDMI 1.4, HDCP 1.4)
Audio-in (3.5mm):	1

OUTPUT

Monitor out:	1
Audio-out (3.5mm):	1
Speaker:	2W
USB Type A (Power):	1 (5V/2A)

CONTROL

RS232 (DB 9-pin male):	1
RJ45 (LAN control):	1
USB Type A (Services):	1 (share with USB A Output)

OTHERS

Power Supply Voltage:	100-240V+/- 10%, 50/60Hz (AC in)
Power Consumption:	Normal: 229W Standby: <0.5W
Operating Temperature:	0~40°C
Carton:	Brown
Net Weight:	2.85kg
Gross Weight:	3.80kg
Dimensions (WxDxH) with Adjustment Foot:	294x237x115mm
Packing Dimensions:	365x300x188mm
OSD Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, Hindi, Arabic, Vietnamese, Greek, Hungarian. Total 24 languages
User Guide Language:	English, S-Chinese, T-Chinese, Indonesian, Finish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, total 20 languages

STANDARD ACCESSORY

Power Cord:	1
VGA Cable:	1
Remote Control:	1
QSG:	Yes
Lens Cover:	Yes
Warranty Card:	Yes (CN Only)

OPTIONAL ACCESSORY

Wall/Ceiling Mount:	PJ-WMK-305 PJ-WMK-007
Carry Bag:	PJ-CASE-008