

Manual

Hot-Swap frames

ST-2513

ST-2523

ST-3515

ST-3525

ST-7227U

ST-8213U

For your safety, please read this manual carefully before installation or using. Keep this safety instructions and forward it when you forward the product.

Depending model one or two 2,5" or 3,5" harddisks can be mounted:

Model	Space Mounting options
ST-2513	3,5" bay 1x 2,5" HDD/ SSD
ST-2523	3,5" bay 2x 2,5" HDD/ SSD
ST-3515	5,25" bay 1x 3,5" HDD/ SSD
ST-3525	2x 5,25" bay 2x 3,5" + 1x 2,5" HDD/ SSD
ST-7227U	3,5" bay 1x 2,5" HDD/ SSD
ST-8213PCI	PCI slot 1x 2,5" HDD/ SSD

Intended use

This product is only for indoor use and for mounting of hard disks inside computer cases. Don't use or store this product close to water or in humid rooms.

Danger and protection

Don't apply external force to the device. Don't use the device with wet hands (can cause damages).

In spite of a special process of production and careful controls some edges could be not polished. Please take care of that to avoid injuries.

Maintenance

The device needs generally no maintenance. In case of dust or dirt take it up with a vacuum cleaner.

Disposal

In case of disposal your power supply, please dispose it by using the official way. In case of questions for that, contact your municipality or local dealer.

Dispose cardboard and plastics from package according your local law.

Warranty terms

Inter-Tech grants 12 months warranty by proper use up from the date of purchase. In case of warranty please contact your local dealer or the dealer from which you bought the product. Please look also at our complete warranty terms on our website www.inter-tech.de – Information – Warranty Terms.

Preparation

Take out the product and check the package content for completeness or damages. In case of missing parts or external damages, please contact your local dealer for replacement. Please keep the original package for shipping in case of warranty case.

Installation

ST-2513:

Put the device into a free external 3,5" bay. Position it at the front panel and fix it with screws.

Set a SATA data cable between device and Mainboard and a SATA power cable from your power supply to the device. The device is now ready to use.

ST-2523:

Put the device into a free external 3,5" bay. Position it at the front panel and fix it with screws.

Set two SATA data cables between device and Mainboard and two SATA power cables from your power supply to the device. The device is now ready to use.

ST-3515:

Put the device into a free external 5,25" bay. Position it at the front panel and fix it with screws.

Set a SATA data cable between device and Mainboard and a SATA power cable from your power supply to the device. The device is now ready to use.

ST-3525:

Put the device into two free external 5,25" bays. Position it at the front panel and fix it with screws.

Set three SATA data cables between device and Mainboard and two SATA power cable from your power supply to the device. The device is now ready to use.

ST-7227U:

Put the device into a free external 5,25" bay. Position it at the front panel and fix it with screws.

Set two SATA data cables between device and Mainboard and two SATA power cables from your power supply to the device. Put the USB cable into a free USB 3.0 port onto your Mainboard. The device is now ready to use.

ST-8213PCI:

Put the device into a free PCI slot of the case.

Probably you have to remove the slot bracket first. In case the bracket is stamped be careful breaking it out to avoid injuries.

Fix the device at the case. Set a SATA data cable between device and Mainboard and a SATA power cable from your power supply to the device. The device is now ready to use.

Use

Open the door of the device using the included key. Put a hard disk into the device and close the door slowly.

To take out the hard disk open the door like above till you can pick it with your fingers.

Contact

Inter-Tech Elektronik Handels GmbH
Hainhäuser Weg 93
D-30855 Langenhagen
Germany

Web: www.inter-tech.de

Email: vertrieb@inter-tech.de