


47512045



SCHUKO socket outlet with hinged cover enhanced contact protection, Berker R.1/R.3/R.8, black glossy

Technical features

Architecture

Design according to DIN 49440

Main electrical features

Nominal voltage	250 V
Rated current	16 A
Rated voltage	250 V AC

Cover, door

- with self-closing hinged covers
- Central cover plate

Materials

RAL colour	RAL 9005 - Jet black
Colour of design line	black
Colour of labelling	217,217,217
Colour	deep black
Colour	black
Material	thermoplastic
Material for printing	PC-PMA black
Surface appearance	glossy

Installation, mounting

- with spreader claws

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1
- with plug-in terminals	

Settings

Shading parameter	R1_czarny
Laser parameter	R1_schwarz

Equipment

Type of configuration	Laserdruck
-----------------------	------------

Use

- enhanced contact protection

Safety

Protection index IP	IP20
IK protection code against mechanical impacts	05
Enhanced contact protection (child protection)	according to IEC 60884-1
Enhanced contact protection (child protection)	according to VDE 0620-1

- Enhanced contact protection

Identification

Application, usage	Flush-mounted wet-room installation
Main design line	Berker R.1/R.3/R.8
Secondary design line(s)	Berker R.3, Berker R.1

Instructions

-
- these marked articles (see symbol) are only suitable for the water-protected flush-mounted installation IP44 in conjunction with the corresponding seal, frame and contact protection box (imprint "IP44").
-