

DIGITUS mini GBIC (SFP) Module, 10Gbps, 0.3km, with DDM Feature

DN-81200**EAN 4016032324133****10G SFP+ Module, Multimode, DDM LC Duplex Connector, 850nm, up to 300m**

The DIGITUS® mini GBIC (SFP) transceiver modules offer highest quality and reliability. Whether from switch to switch, converter to switch, converter to converter or any else application: The wide product range of DIGITUS® modules makes possible a flexible usage of the fiber technology. The conformity to the MSA (Multi Source Agreement) standard ensures a compatibility to third party manufacturers.

The plug and play fiber connection

- Mini GBIC SFP (Small Form Factor Pluggable) module
- Compatible with the following manufacturers: Allied Telesis, Allnet, CISCO, D-Link, Edimax, Hirschmann, Intellinet, KTI Networks, Level One, Netgear, PLANET, Tenda, TP-Link, TRENDnet, ZyXEL, ZTE
- Supports DDM (Digital Diagnostic Monitoring)
- High quality and excellent reliability
- 10 Gbps Maximum Data Rate
- Compliant to IEEE802.3ae 10 Gigabit Standard
- Class 1 laser product compliant with EN 60825-1
- Easy plug-and-play installation
- MSA (Multi Source Agreement) compliant

- Hot pluggable
- Connector: 1x LC Duplex
- Wavelength: 850nm
- Transmission Power: Minimum -5 dBm, Maximum -1 dBm
- Empfangssensitivität: Minimum -11,5 dBm
- For a distance of up to 0.3km
- Safe fast-locking mechanism
- 3.3V power supply
- Operating temperature: 0 °C ~ 70 °C
- USB-C Products: no
- Broadcasting Mode: Unidirectional
- Manufacturer compatibility: Cisco
- Connector: LC
- DDM Support: yes
- Distance (km): 0.3
- Mode: Multimode
- Ethernet speed: 10 Gigabit
- Wavelength: 850 nm

Package contents

- SFP module

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	20	0.80	41.00	26.00	16.00	17,056.00
Packaging Unit Inside	1	0.04	3.00	11.50	9.00	310.50
Packaging Unit Single	1	0.04	3.00	11.50	9.00	310.50
Net single without Packaging	1	0.02	3.00	11.50	9.00	310.50

More images:



SFP Modules							
Part Number	Speed	Distance	Connector	Wavelength	Operating Temperature	Industrial Version	
Fast Ethernet							
DS-4100	10/100 Mbps	2 km	LC Duplex	1310nm	0 to 70 °C	✓	
DS-4102	10/100 Mbps	20 km	LC Duplex	1550nm	0 to 70 °C	✓	
DS-4103	10/100 Mbps	20 km	LC Duplex	1310nm	0 to 70 °C	✓	
Gigabit							
DS-4104	1 Gbps	20 km	LC Duplex	1310nm	0 to 70 °C	✓	
DS-4105	1 Gbps	20 km	LC Duplex	1550nm	0 to 70 °C	✓	
DS-4106	1 Gbps	20 km	LC Duplex	1310nm	0 to 70 °C	✓	
DS-4107	1 Gbps	20 km	LC Duplex	1550nm	0 to 70 °C	✓	
DS-4108	1 Gbps	20 km	LC Duplex	1310nm	0 to 70 °C	✓	
DS-4109	1 Gbps	20 km	LC Duplex	1550nm	0 to 70 °C	✓	
10G							
DS-4110	10 Gbps	20 km	LC Duplex	1310nm	0 to 70 °C	✓	
DS-4111	10 Gbps	20 km	LC Duplex	1550nm	0 to 70 °C	✓	
Fast Ethernet							
DS-4112	10/100 Mbps	20 km	LC Duplex	1310nm	-40 to +85 °C	✓	
DS-4113	10/100 Mbps	20 km	LC Duplex	1550nm	-40 to +85 °C	✓	
DS-4114	10/100 Mbps	20 km	LC Duplex	1310nm	-40 to +85 °C	✓	
DS-4115	10/100 Mbps	20 km	LC Duplex	1550nm	-40 to +85 °C	✓	
DS-4116	1 Gbps	20 km	LC Duplex	1310nm	-40 to +85 °C	✓	
DS-4117	1 Gbps	20 km	LC Duplex	1550nm	-40 to +85 °C	✓	
DS-4118	1 Gbps	20 km	LC Duplex	1310nm	-40 to +85 °C	✓	
DS-4119	1 Gbps	20 km	LC Duplex	1550nm	-40 to +85 °C	✓	