


47468982



SCHUKO socket outlet with hinged cover Labelling field, enhanced contact protection, Mounting orientation variable in 45° steps, Berker S.1, white glossy

Technical features

Architecture

Design according to DIN 49440

Main electrical features

Nominal voltage	250 V
Rated current	16 A
Rated voltage	250 V AC

Cover, door

- when opening hinged cover, it can be arrested in end position
- Central cover plate

Materials

RAL colour	RAL 1013 - Oyster white
Colour of design line	white
Colour	white
Colour	white
Material	thermoplastic
Surface appearance	glossy

Dimensions

Insertion depth	32 mm
-----------------	-------

Installation, mounting

- mounting orientation of insert selectable in 45° steps
- with spreader claws

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1
- with plug-in terminals	

Use

- Labelling field
- enhanced contact protection
- Mounting orientation variable in 45° steps

Safety

Protection index IP	IP20
IK protection code against mechanical impacts	05
Enhanced contact protection (child protection)	according to IEC 60884-1
Enhanced contact protection (child protection)	according to VDE 0620-1
- Enhanced contact protection	

Identification

Main design line

Berker S.1

Instructions

-
- Specially suited to combinations of several socket outlets if right angle plugs are used. 1140.

Labelling field height designed for 6 mm P-touch strips.
