



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	User manual
Number of tare power	7 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	WS

Physical

Cable length	1.83 m
Colour	Black
Depth	36.5 cm
Height	12 cm
Mounting preference	No preference
Net weight	4 kg
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes
Width	13 cm

Input

Network frequency	47...63 Hz
Plug standard	CEI 23-16 Italian
Maximum input current	6 A

Switching current capacity	10 A
Input voltage	230 V

Output

Rated power in W	400 W
Maximum configurable power in W	400 W
Output frequency	47...63 Hz sync to mains 50/60 Hz +/- 1 Hz unsynchronised
Outputvoltage_other	220 V
UPS type	Standby
Wave type	Stepped approximation to a sinewave
Nb of power socket outlets	6 Schuko CEE 7 2 Schuko CEE 7 surge
Curve equation	Efficiency
Curve fixed loss	0.0062
Curve load maximum	100 %
Curve load minimum	1 %
Curve proportional loss	0
Curve square loss	0.02
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit of data measured in accordance with the ENERGY STAR Test Method for Uninterruptible Power Supplies. All measurements taken in normal mode(s), at typical environmental conditions, with 230V/50Hz electrical input and balanced resistive load (PF = 1.0) output.
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Efficiency	80 % (full load)
Graph display	1
Graph start point	40
Output voltage	230 V
Maximum configurable power in VA	650 VA
Rated power in VA	650 VA
Transfer time	6 ms typical : 10 ms maximum

Conformance

Product certifications	CE EAC
Equipment protection policy	Lifetime : 100000 euros

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...90 %
Operating altitude	0...3000 ft
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...4572.00 m
Acoustic level	45 dBA
Show note OP temperature	No

Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	16 h
Liquid value	0
Battery voltage	12 V
Battery capacity	7.0 Ah
Battery curve	C
Battery charger power	5 W rated
Battery power in VAH	75 VAh runtime
Battery life	2...5 year(s)
Extended runtime	0

Communications & Management

Control panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	310 J
Data line protection	RJ45 analog phone line for phone/fax/modem/DSL RJ45 network line - 10/100 base-T Ethernet

Packing Units

Package 1 Weight	4.5 kg
Package 1 Height	19 cm
Package 1 width	18.6 cm
Package 1 Length	44.1 cm
SCC14	10731304347221
Package 2 Weight	14.50 kg
Package 2 Height	203.20 mm
Package 2 width	457.20 mm
Package 2 Length	558.80 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product

Contractual warranty

Warranty	2 years repair or replace, 3 years repair or replace for European Union countries
----------	---