
Product information

WISI DD 15 HP

Broadband modem sockets, Data loop through socket with highpass filter



KLASSE A CLASS

Description

TV connection with IEC technology. Multimedia with F-connector or WICLIC for cable modem. HF output high-pass filtered. Cover plate and connector cable see accessories

WISI Communications GmbH & Co. KG
Wilhelm-Sihn-Str. 5-7
75223 Niefern-Oeschelbronn, Germany
Phone: +49 7233 66-280, Fax: -350
E-Mail: export@wisi.de

Technical Modifications reserved. WISI cannot be held liable for any printing error. 4. September 2017, 4:00 nachm.

WISI DD 15 HP

Technical data	
Inputs	
Frequency range	5...862 MHz
Outputs	
Frequency range TV	85...862 MHz
Frequency range FM	87...862 MHz
Frequency range DATA	5...862 MHz
Frequency range loop through	85...862 MHz
Insertion loss TV	14 dB
Insertion loss FM	14 dB
Insertion loss DATA	14 dB
Through loss	1,5...2,5 dB
Isolation DATA - TV	≥40 dB
Isolation DATA - FM	≥40 dB
Isolation DATA-DATA	74 dB (typ.)
Decoupling TV-FM	≥22 dB
Return loss IN	Cat B
Return loss OUT	Cat B
Return loss ALL	Cat C
Connectors	
Outer conductor clamp	7.5 mm
Inner conductor clamp	0,8...1,3 mm
F-socket	1 pcs.
IEC socket	1 pcs.
IEC-plug	1 pcs.
General data	
Screening factor	>85 dB (class A)
Dimensions (width x height x depth)	70 x 70 x 22 mm
Installation depth	35 mm

Packaging data	
Sales unit	10 pcs.
Dimensions (WxHxD) sales unit	212 x 148 x 78 mm
Packaging volume sales unit	dm³
Gross weight sales unit	0.110 kg
Shipping unit	100 pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	0.24 dm³
Gross weight shipping unit	0.11 kg
EAN	4010056193638
Article number	19363
Customs tariff number	85291095