



XPG GAMMIX S5 PCIe Gen3x4 M.2 2280 Solid State Drive

Boot, load, and transfer faster with the XPG GAMMIX S5 PCIe Gen3x4 M.2 2280 solid state drive (SSD). With support for NVMe 1.3 and equipped with 3D NAND Flash, it offers up to 4 times faster performance than SATA SSDs and up to 2TB of capacity. What's more, the GAMMIX S5 sports excellent heat dissipation capability with a built-in heatsink that can lower temperatures by up to 10°C.

Features

- Ultra-fast PCIe Gen3x4 interface:
 R/W speed up to 2100/1500MB/s
- NVMe 1.3 support
- 3D NAND Flash for higher capacity and durability
- Unique heatsink design makes SSD 10°C cooler
- Advanced LDPC ECC Technology
- HMB (Host Memory Buffer) and SLC Caching
- Compact M.2 2280 form factor ideal for highend desktops

Ordering Information

Capacity	Model Number	EAN Code		
256GB	AGAMMIXS5-256GT-C	4713218469250		
512GB	AGAMMIXS5-512GT-C	4713218469267		
1TB	AGAMMIXS5-1TT-C	4713218469274		
2ТВ	AGAMMIXS5-2TT-C	4710273778075		



Specifications

• Capacities: 256GB / 512GB / 1TB / 2TB

• NAND Flash: 3D TLC

• Interface: PCIe Gen3x4

• Form Factor: M.2 2280

• MTBF: 2,000,000 hours

• Dimensions (L x W x T): 80 x 22 x 3.7mm

• Weight: 11.2g

• Power Consumption: 0.33W Active (Typical),

0.14W Slumber (Typical) (*measured by power meter)

• Operating Temperature: 0°C~70°C

• Storage Temperature: -40°C~85°C

• Shock Resistance: 1500G/0.5ms

• Certifications: RoHS, CE, FCC, BSMI, VCCI, KC

• Warranty: 5-year limited

Performance

	Capacity	ATTO	ATTO	CDM	CDM	AS SSD	AS SSD	4K	4K	
		Seq.	Seq.	(QD32)	(QD32)	Seq.	Seq.	Random	Random	TBW
		Read	Write	Seq. Read	Seq. Write	Read	Write	Read	Write	IDVV
		(MB/sec)	(MB/sec)	(MB/sec)	(MB/sec)	(MB/sec)	(MB/sec)	IOPS	IOPS	
	256GB	2100	1200	2100	1200	1800	1200	190K	180K	150TB
-	512GB	2100	1400	2100	1500	1800	1300	250K	240K	300TB
	1TB	2100	1400	2100	1500	1800	1300	250K	240K	600TB
	2ТВ	2100	1400	2100	1500	1800	1300	250K	240K	1200TB

^{*}Performance may vary based on SSD capacity, hardware test platform, test software, operating system and other system variables

Schematics







