ONKRON
designed to support

TS1881E-B



Screen size: 50" - 86"	Max load: 105.9 kg	VESA: 200x200 - 800x500 mm	Height adjustment: 1350 mm-1650 mm

Made of	Plastic, SPCC cold rolled steel
Max. load of monitors/TVs	90.9 kg
VESA	200x200, 200x300, 200x400, 200x500, 300x200, 300x300, 300x400, 300x500, 400x200, 400x300, 400x400, 500x200, 500x400, 500x500, 600x200, 600x300, 600x400, 700x400, 700x500, 800x200, 800x400, 800x500 mm
Screen size (min)	50"
Screen size (max)	86"
Number of screens	1
Height adjustment (min)	1350 mm
Height adjustment (max)	1650 mm
Travel speed	13 mm/s
Remote control range	5 m
Security class	IP 20
Operating temperature, range	-15 +15 °C
Motor power	52.2 W
Warranty	5 years
Warranty on electric motor	12 months
Overall dimensions complete	96 x 73.5 x 225.8 cm
Dimensions of the individual package	106x74x18 cm
Individual package volume	1.41 m³
Gross weight individual	40 kg
Number of individual per pallet	9

ONKRON mounting solutions:
· Are suitable for continuous 24/7 use when installed and used in accordance with the applicable product documentation, installation instructions, and load specifications;
· Are intended for professional and commercial installations;
· Are designed to support secure and reliable installation of compatible displays in public environments;
· Comply with standard safety, installation, and mechanical requirements applicable to professional display mounting solutions;
· May be used in high-traffic public spaces, provided that installation is performed by qualified personnel and in accordance with all applicable local regulations, safety standards, and project requirements.

© 2026 Products or images of ONKRON™ are subject to change without notice.