

Product datasheet

Specifications



APC Smart-UPS On-Line, 1000VA, Rackmount 2U, 230V, 8x C13 IEC outlets, Network Card, W/ rail kit, W/ O Lithium-ion external battery

SRT1000UXI-NCLI

Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead time	Usually in Stock

Main

Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	900 W
Rated power in VA	1000 VA
Input Connection Type	IEC 60320 C14
Output connection type	8 IEC 60320 C13
Number of rack unit	2U
Provided equipment	CD with software Communication cable Documentation CD Installation guide Removable support feet USB cable Warranty card

Batteries & Runtime

Battery type	External battery system
Number of battery filled slots	0
Number of battery free slots	0
Extended runtime	1

General

UPS type	Double conversion online
Product web sub-family	High density
Number of power module free slots	0

Number of power module filled slots	0
Redundant	No
Physical	
Colour	Black
Height	8.5 cm
Width	43.2 cm
Depth	59 cm
Net weight	17.51 kg
Mounting preference	No preference
Mounting mode	Rack-mounted with kit
Two post mountable	0
USB compatible	Yes
Mounting position	Vertical
Input	
Network frequency	40...70 Hz auto-sensing
Input voltage limits	50...150 V 40% load 80...150 V
Output	
Maximum configurable power in VA	1000 VA
Maximum configurable power in W	900 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Wave type	Sine wave
Harmonic distortion	Less than 2 %
Crest factor	3 : 1
Bypass type	Built-in bypass
Conformance	
Product certifications	CE EAC RCM VDE
Marking	CE Mark
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Environmental	
Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 % non-condensing

Storage altitude	0.00...15240.00 m
Acoustic level	50 dBA
Heat dissipation	400 Btu/h
IP degree of protection	IP20

Communications & Management

Free slots	0
Preinstalled device	Network management card 3 with environmental monitoring
Alarm	Audible and visible alarms : prioritized by severity
Emergency power off	Yes

Surge Protection and Filtering

Surge energy rate	340 J
-------------------	-------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.5 cm
Package 1 Width	81 cm
Package 1 Length	60 cm
Package 1 Weight	28.21 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	5 year repair or replace
----------	--------------------------

Recommended replacement(s)