


41092045

SCHUKO socket outlet with LED orientation light enhanced contact protection, Screw-in lift terminals, Serie 1930/R.classic, black glossy

Technical features

Architecture

Design	according to DIN 49440

Main electrical features

Nominal voltage	250 V
Rated current	16 A
Rated voltage	250 V AC

Power

Power consumption	0.25 W/0.35 VA

Cover, door

- Central cover plate

Detection

- integrated brightness sensor that switches the orientation light on at twilight and off when there is sufficient brightness

Materials

RAL colour	RAL 9005 - Jet black
Colour of design line	black
Colour of labelling	217,217,217
Colour	deep black
Colour	black
Material	thermoplastic
Material for printing	PC-PMA black
Surface appearance	glossy

Dimensions

Insertion depth	32 mm

Lighting control

Light intensity (white)	0,2 cd
Switch-off brightness	≈ 4 lx
Switch-on brightness	≈ 2 lx

LED control

- white LED light
- long service life of the LED

Installation, mounting

- with spreader claws

Connection

Conductor cross-section (rigid)	max. 2,5 mm²
Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1

- with screw-in lift terminals

Cable

- through-wiring possible, therefore also ideal for retrofitting

Settings

Shading parameter	R1_czarny
Laser parameter	R1_schwarz

Equipment

Type of configuration	Laserdruck

- additional benefit by combination of a socket outlet with an orientation light

Use

- enhanced contact protection
- Screw-in lift terminals

Safety

Protection index IP	IP20
IK protection code against mecanical impacts	05
Enhanced contact protection (child protection)	according to IEC 60884-1
Enhanced contact protection (child protection)	according to VDE 0620-1

- Enhanced contact protection

Identification

Main design line	Serie 1930/R.classic

Instructions

- Caution!
  Items with special flush-mounted insert.
  Centre plates with LED orientation lights are not compatible with the standard socket outlets.
- Note:
  When integrating this product into the Serie 1930, the 1gang frame for centre plate Ø 58 mm, order no.: 1382 0... may only be used. Installation in multiple combinations of the Serie 1930 is not possible!